

## Microbox PC Embedded PC

Configuration Number: BASE CONFIG  
SL-EB-ICO300



(full size images available on web site)

### Completely Fanless

#### Type:

Microbox PC  
Dimension: 4.33" x 1.88" x 6.10"

#### Motherboard:

Featuring Intel ATOM SoC and Intel Atom E3815 (1.46GHz Single Core) TDP 5W

**Long Production Cycle Motherboard (Through Q4 2028)**

**LAN:** 2x GB (10/100/1000)

**Video:** VGA

**Audio:** No Onboard Audio

#### Ports:

2x USB 2.0 Ports ( 2 Front, 2 Rear )

4x COM Port (RS232/422/485 Rear)

See specifications for more ports

**Operating Temperature:** -20°C to 70°C (-4°F to 158°F)

#### Also Included:

**Memory:** 2GB DDR3L 1600MHz SODIMM RAM (Not Recommended - Use with Embedded Operating System Only) [Upgradeable]

**Hard Drive:** 120GB SSD SATA 6.0Gb/s, 520/320MB/s read/write (or greater) [Upgradeable]

**Operating System:** Not Included -

**Warranty:** One-Year Depot Warranty [Upgradeable]

## Technical Specifications

## MotherBoard Specifications:

### Motherboard Model

- Motherboard Type: Embedded
- Long Production Cycle
- Long Life: YES
- EOL Date: Q4 2028
- Fanless

### Supported CPU

- Number of Processors: 1
- Processor Type: Embedded CPUs (ultra-low power, soldered down)
- Embedded CPU: Intel Atom E3815 (1.46GHz Single Core) TDP 5W

### Chipset

- Chipset: Intel ATOM SoC

### Memory

- Memory Type: SO DIMM DDR3 1600MHz
- Memory Type: Non-ECC
- DIMMS: 1
- Maximum Memory: 4GB

### On Board Audio

- Audio Type: No Onboard Audio

### On Board Video

- Video Chipset: Supported by CPU - see Embedded CPU Information
- Video on IO: VGA
- VGA Port Out: 1

### LAN

- LAN Ports: 2
- LAN Type: GB (10/100/1000)
- LAN Chipset: Intel i211AT
- Second LAN Chipset: Intel i211AT
- Wireless LAN: Wireless antennas pre-assembled

### Drive Interface

- SATA II Ports (3GB): 1
- Compact Flash: 1

### mini PCIe

- mSATA
- USB and PCIe signals
- half and/or full size mini PCIe card: full size

### Rear IO

- USB 2.0 Ports (on IO): 2
- Serial 232/422/485 Ports: 4

## Chassis Specifications:

### General

- Form Factor: Micro PC
- Front Facing I/O
- Color: Gray & White
- Material: Metal/Steel
- Material Thickness: 1mm

### Expansion

- Internal 2.5" Bays: 1

### Front Ports

- USB 2.0 Port (Front): 2

### Physical

- Depth: 4.33"
- Width: 1.88"
- Height: 6.10"
- Shipping Box - Depth: 7.70"
- Shipping Box - Width: 6.50"
- Shipping Box - Height: 4.30"
- Shipping Weight: 4lbs

### Power

- Built-in Chassis Power Supply: Power Input Rating: 12-24 VDC, 1.21-0.66A

- Digital I/O (8 Bit)

#### **Management Features**

- Watch Dog

#### **Environmental**

- Operating Temperature: -20°C to 70°C (-4°F to 158°F)
- High Humidity: 95%
- Low Humidity: 10%

#### **Operating System Support**

- Windows 7 Ultimate (64-bit)
- Windows 7 Pro (64-bit)
- Windows 7 Pro (FES) 32-Bit
- Windows 7 Pro (FES) 64-Bit
- Windows Embedded 7 (32-Bit)
- Windows Embedded 7 (64-Bit)
- Windows Embedded 8 (32-bit)
- Windows Embedded 8 (64-bit)
- Windows 10 Home (64 Bit)
- Windows 10 Pro (64-Bit)
- Windows 10 IoT Ent-Entry

#### **Compliance of Component**

- UL
- CE
- FCC

#### **Warranty of Component**

- Motherboard Warranty: 1 Year

**SuperLogics**<sup>®</sup>

Simplifying Computing<sup>™</sup>

[www.superlogics.com](http://www.superlogics.com)  
Phone: 1-508-650-9500

[sales@superlogics.com](mailto:sales@superlogics.com)  
Fax: 1-508-650-9525