

## 2U Rack Mount Server Rackmount

Configuration Number: BASE CONFIG  
SL-2U-MCX-C621DPI-LF



(full size images available on web site)

### Intel Xeon Scalable Platform

#### Type:

- 2U Rack Mount Server
- Depth: 25.50", Max Card Depth: 8 - 14 Inches"

#### Motherboard:

- Featuring Intel C621 Chipset and Intel Xeon Scalable Processors processor
- **Low Profile Slots:**
  - 4 - PCIe x16
  - 2 - PCIe x8
- **LAN:** 2x Ports (1GbE (10/100/1000))
- **RAID:** 0,1,5,10
- **Video:** 1x VGA
- **Audio:** No Onboard Audio
- **Ports:**
  - 2x USB 2.0 Ports ( 2 Rear )
  - 4x USB 3.2 Gen 1 Ports ( 2 Rear, 2 Internal Headers )
  - 2x COM Ports (1 RS232 Rear, 1 RS232 Internal Headers)
  - See specifications for more ports
- **Operating Temperature:** 10°C to 35°C (50°F to 95°F)

#### Configuration summary:

- **Processor:** 2 x Xeon Bronze 3104 - 1.70GHz Six Core Intel Processor - 8.25MB Cache (85W)
- **Memory:** 2 x 8GB DDR4 2666MHz ECC Registered RAM
- **Hard Drive:** 250GB NVMe SSD M.2 2.9GB/1.3GB - Samsung 980
- **Power Supply:** 1000W Redundant Power

- Supplies with PMBus 80+ Titanium
- **Operating System:** Not Included -
- **Warranty:** One-Year Depot Warranty

## Technical Specifications

### MotherBoard Specifications:

#### Motherboard Model

- Motherboard Type: Extended ATX

#### Supported CPU

- Number of Processors: 2
- Processor Type: Intel Xeon Scalable Processors

#### Chipset

- Chipset: Intel C621 Chipset

#### Memory

- Memory Type: DDR4 2400MHz ECCR
- Memory Type: ECC Registered
- DIMMS: 16
- Maximum Memory: 2048GB

#### On Board Audio

- Audio Type: No Onboard Audio

#### On Board Video

- Video Chipset: ASPEED AST2500 BMC
- Video on IO: 1x VGA
- VGA Port Out: 1

#### LAN

- LAN Ports: 2
- LAN Type: 1GbE (10/100/1000)
- LAN Chipset: Intel X722
- Second LAN Chipset: Intel X722
- Wireless LAN: No Integrated WLAN

#### Drive Interface

- SATA III Ports (6GB): 14
- RAID
- RAID Type: Software RAID
- RAID Levels Supported on Motherboard: 0, 1, 5, 10

#### Expansion Slots

- PCI Express x16 Slots On Motherboard: 4
- PCI Express x8 Slots On Motherboard: 2

### Chassis Specifications:

#### General

- Form Factor: 2U Rackmount
- Color: Black
- Material: Steel & Plastic
- Material Thickness: 1mm
- Redundant Power Supply Capable
- Slide Rails: Optional

#### Expansion

- Low Profile Slots: 6
- Max Card Depth: 8 - 14 Inches"
- 3.5" Hot Swap Bays: 8

#### Front Ports

- USB 2.0 Ports (Front): 2

#### Cooling System

- Maximum Fan Count: 3
- Included Fans: 3

#### Physical

- Depth: 25.50"
- Depth (Inches): 25.5
- Width: 17.20"
- Height: 3.50"
- Shipping Box - Depth: 34.50"
- Shipping Box - Width: 11.40"
- Shipping Box - Height: 26.70"
- Shipping Weight: 37lbs

#### Power

- Built-in Chassis Power Supply: 1000W Redundant Power Supplies with PMBus 80+ Titanium

### **M.2 Slot Specs**

- Total M.2 NVMe SSD Slots: 1
- M.2 Slot #1 Specs
- PCIe Signal
- 22110 - 22 mm x 110 mm.
- 2260 - 22 mm x 60 mm.
- 2280 - 22 mm x 80 mm.

### **Rear IO**

- USB 2.0 Ports (on IO): 2
- USB 3.2 Gen 1 Type A Ports (on IO): 2
- Serial (Rear IO): 1

### **Headers**

- USB 3.2 Gen 1 Ports (on Headers): 2
- Serial (via Headers): 1
- FAN Connectors: 8
- Chassis Intrusion

### **Management Features**

- TPM Support: Via 2.0 Header

### **Environmental**

- Operating Temperature: 10°C to 35°C (50°F to 95°F )
- High Humidity: 90%
- Low Humidity: 8%

### **Operating System Support**

- Windows 10 Pro WS (64-Bit)
- Ubuntu Server Edition
- Windows Server 2016 STD
- Windows Server 2019 Std
- RED HAT Enterprise LINUX SERVER STANDARD

### **Compliance of Component**

- CE
- RoHS
- FCC

### **Warranty of Component**

- Motherboard Warranty: 1 Year

### **Other Features**

- Other Features:  
PCI-Express
  - 4 PCI-E 3.0 x16 (Low-profile)
  - 2 PCI-E 3.0 x8 (Low-profile)



Simplifying Computing™

[www.superlogics.com](http://www.superlogics.com)  
Phone: 1-508-650-9500

[sales@superlogics.com](mailto:sales@superlogics.com)  
Fax: 1-508-650-9525