

# Desktop PC Desktop

Configuration Number: BASE CONFIG

SL-DK-J3455B-IM













# Type:

- Desktop PC
- Dimension: 193mm x 76mm x 225mm

## Motherboard:

- Featuring Intel Celeron SoC and Intel Celeron J3455 Processor (1.5GHz Quad Core, Burst 2.3GHz) Intel HD Graphics 500, TDP 10W
- No Available Slots
- LAN: 1x Ports (GB (10/100/1000))
- Video: VGA + HDMI
- Audio: 8-Channel HD Audio by Realtek ALC887
- Ports:

3x USB 2.0 Ports ( 1 Rear, 2 Internal Headers )

4x USB 3.2 Gen 1 Ports (1 Front, 3 Rear) 2x COM Ports (1 RS232 Rear, 1 RS232 Internal Headers)

1x Parallel Port (Rear)

1x Front Audio Port

See specifications for more ports

• Operating Temperature: 0°C to 50°C (32°F to 122°F)

# Configuration summary:

- Memory: 4GB DDR3L 1600MHz SODIMM RAM 1.35V
- Hard Drive: 250GB SSD SATA 6.0Gb/s 560/530MB/s 2.5" - Samsung 870 EVO
- Power Supply:150W Internal PSU
- Operating System: Not Included -
- Warranty: One-Year Depot Warranty

# **Technical Specifications**

# MotherBoard Specifications:

# **Chassis Specifications:**

#### **Motherboard Model**

Motherboard Type: MiniITX

Fanless

## **Supported CPU**

• Number of Processors: 1

 Processor Type: Embedded CPUs (ultra-low power, soldered down)

 Embedded CPU: Intel Celeron J3455 Processor (1.5GHz Quad Core, Burst 2.3GHz) Intel HD Graphics 500, TDP 10W

#### Chipset

• Chipset: Intel Celeron SoC

## Memory

• Memory Type: SO DIMM DDR3 1600MHz

• Memory Type: Non-ECC

• DIMMS: 2

• Maximum Memory: 16GB

#### **On Board Audio**

 Audio Type: 8-Channel HD Audio by Realtek ALC887

## **On Board Video**

 Video Chipset: Supported by CPU - see Embedded CPU Information

• Video on IO: VGA + HDMI

VGA Port Out: 1HDMI Out: 1

#### LAN

• LAN Ports: 1

LAN Type: GB (10/100/1000)
LAN Chipset: Realtek RTL8111GR
Wireless LAN: No Integrated WLAN

# **Drive Interface**

• SATA III Ports (6GB): 2

#### **Expansion Slots**

PCI Express x16 Slots On Motherboard: 1

## Rear IO

PS/2 Mouse on IO

PS/2 Keyboard on IO

#### **General**

• Form Factor: Desktop PC

• Color: Black

Material: Steel & PlasticMaterial Thickness: 1mm

Motherboard Compatibility: Mini ITX

#### **Expansion**

• Internal 2.5" Bays: 1

#### **Front Ports**

• USB 3.2 Ports (Front): 2

• Front Audio Ports: 1

#### **Physical**

Depth: 193mmDepth (Inches): 7.6

Width: 76mmHeight: 225mm

Shipping Box - Depth: 120mm
Shipping Box - Width: 270mm
Shipping Box - Height: 273mm

• Shipping Weight: 10lbs

## **Compliance of Component**

CE

RoHS

• FCC

#### **Other Features**

• Features:

With a depth of less than 80mm, this system can easily be mounted behind a LCD monitor.

• Chassis Warranty: 1 Year

## **Power**

• Built-in Chassis Power Supply: 150W Internal PSU

- USB 2.0 Ports (on IO): 1
- USB 3.0 Ports (on IO): 3
- Serial (Rear IO): 1
- Parallel Ports: 1
- Audio on IO

#### **Headers**

- USB 2.0 Ports (on Headers): 2
- USB 3.0 Ports (on Headers): 1
- Serial (via Headers): 1
- FAN Connectors: 2
- Audio on Headers
- Chassis Intrusion
- TPM Support: Via 2.0 Header

## **Environmental**

- Operating Temperature: 0°C to 50°C (32°F to 122°F)
- High Humidity: 90%
- Low Humidity: 5%

## **Operating System Support**

- Windows 10 Home (64 Bit)
- Windows 10 Pro (64-Bit)
- Windows 10 IoT Entry
- Windows 10 IoT Entry 2019 LTSC

# **Compliance of Component**

- UL
- CE
- RoHS
- FCC

#### **Other Features**

- Other Features:
  - 1 x PCI Express 2.0 x16 Slot (PCIE1: x2 speed mode Only)
  - \* Access to PCI Express slot requires expansion slot and a riser in some chassis models. Please check Chassis Specification section for more information.

If you have any questions, please discuss with our Sales Engineers.

• Motherboard Warranty: 1 Year



www.superlogics.com Phone: 1-508-650-9500 sales@superlogics.com Fax: 1-508-650-9525