

HMI Panel PC Panel PC

Configuration Number: BASE CONFIG
SL-PPC-22AWHD-J4105B-S18



21.5" Open Frame Widescreen. Completely Fanless,

Type:

- Fanless Panel PC
- **Screen:**
 - 21.5" Multi-Touch Projected Capacitive, Native Resolution: 1920 x 1080, Front Panel Rating: Not Rated
- **Mounting:** Suitable for Mounting in Cut-Out

Motherboard:

- Featuring Intel Celeron SoC and Intel Celeron J4105 Processor (1.5GHz Quad Core, Burst 2.5GHz) TDP 10W
- **LAN:** 1x Ports (GB (10/100/1000))
- **Video:** VGA + HDMI
- **Audio:** 8-Channel HD Audio by Realtek ALC887
- **Ports:**
 - 5x USB 2.0 Ports (2 Front, 1 Rear, 2 Internal Headers)
 - 5x USB 3.2 Gen 1 Ports (3 Rear, 2 Internal Headers)
 - 2x COM Ports (1 RS232 Rear, 1 RS232 Internal Headers)
 - 1x Parallel Port (Rear)
 - See specifications for more ports
- **Operating Temperature:** 0°C to 50°C (32°F to 122°F)



Configuration summary:

- **Memory:** 8GB DDR4 2666MHz SODIMM RAM

- **Hard Drive:** 250GB SSD SATA 6.0Gb/s 560/530MB/s 2.5" - Samsung 870 EVO
- **Power Supply:** 90w output, 12v input DC-DC Power Supply - AC Adapter Included
- **Operating System:** Not Included -
- **Warranty:** One-Year Depot Warranty

Technical Specifications

MotherBoard Specifications:

Motherboard Model

- Motherboard Type: MiniITX
- Fanless

Supported CPU

- Number of Processors: 1
- Processor Type: Embedded CPUs (ultra-low power, soldered down)
- Embedded CPU: Intel Celeron J4105 Processor (1.5GHz Quad Core, Burst 2.5GHz) TDP 10W

Chipset

- Chipset: Intel Celeron SoC

Memory

- Memory Type: SO DIMM DDR4 2400MHz
- Memory Type: Non-ECC
- DIMMS: 2
- Maximum Memory: 8GB

On Board Audio

- Audio Type: 8-Channel HD Audio by Realtek ALC887

On Board Video

- Video Chipset: Integrated Intel UHD Graphics 600: 12 EUs inside (Up to 750MHz)
- Video on IO: VGA + HDMI
- VGA Port Out: 1
- HDMI Out: 1

LAN

- LAN Ports: 1
- LAN Type: GB (10/100/1000)
- LAN Chipset: Realtek RTL8111H
- Wireless LAN: No Integrated WLAN

Display Specifications

Display

- Screen Size (inches): 21.5
- Touch Type: Multi-Touch Projected Capacitive
- Aspect Ratio: 16 : 9
- Native Display Resolution: 1920 x 1080
- Brightness (nits): 250
- Screen Refresh Rate: 60Hz
- Display Area (H): 476.06mm
- Display Area (V): 267.79mm
- Aspect Ratio: 16 : 9
- DisplayColors: 16.7 M
- Contrast Ratio: 3000:1
- Backlight: LED
- Viewing Angle(U) : 178
- Viewing Angle(D) : 178
- Viewing Angle(L) : 178
- Viewing Angle(R) : 178

Connectivity

- VGA Port In: 1
- DVI-D In: 1
- HDMI In: 1
- Touchscreen Interface USB Port (Front): 1

Mounting Options

- Mounting Options: VESA 75mm x 75mm, VESA 100mm x 100mm, Other options sold separately
- Suggested Cut-Out Dimension (Width):
- Suggested Cut-Out Dimension (Height):

Physical

- Width:
- Height:
- Depth:
- Depth (Inches): Click Available Downloads Tab >

Drive Interface

- SATA III Ports (6GB): 2

Rear IO

- PS/2 Combo (Mouse/Keyboard)
- USB 2.0 Ports (on IO): 1
- USB 3.2 Gen 1 Type A Ports (on IO): 3
- Serial (Rear IO): 1
- Parallel Ports: 1
- Audio on IO

Headers

- USB 2.0 Ports (on Headers): 4
- USB 3.2 Gen 1 Ports (on Headers): 2
- Serial (via Headers): 1
- FAN Connectors: 2
- Audio on Headers

Environmental

- Operating Temperature: 0°C to 50°C (32°F to 122°F)
- High Humidity: 90%
- Low Humidity: 5%

Operating System Support

- Windows 10 Home (64 Bit)
- Windows 10 Pro (64-Bit)
- Windows 10 IoT Entry
- Windows 10 IoT Entry 2019 LTSC

Compliance of Component

- UL
- CE
- RoHS
- FCC

Other Features

- Other Features:

Microsoft® Windows® 10 64-bit*

*Supports UEFI mode only

*USB3_1_2 is shared with USB2_3.

1 x PCI Express 2.0 x16 Slot (PCIe1: x2 mode)

* Access to PCI Express slot requires expansion slot and a riser in some chassis models. Please check Chassis Specification section for more information.

If you have any questions, please discuss with our Sales Engineers.

- Motherboard Warranty: 1 Year

Mechanical Drawings.

- Unboxed Weight: 12lbs
- Shipping Weight: 18lbs

Environmental

- MTBF: 30000hours
- Maximum Operating Temperature: 50C
- Low Operating Temp: 00
- High Humidity: 90%
- Low Humidity: 5%
- Storage Temp (High): 60C
- Storage Temp (Low): -20C
- Storage Humidity (High): 90%
- Storage Humidity (Low): 5%

Power

- Power Supply: AC 100~240V/12V DC
- Power Consumption (on): 18Watts

Compliance of Component

- CCC

Warranty

- Warranty: 1 year

Other

- Features:

21.5" Open Frame Widescreen

Display Specifications

- Display
- Screen Size: 21.5"
- Touch Type: Multi-Touch Projected Capacitive
- Front Panel Rating: Not Rated
- Color: Black
- Native Display Resolution: 1920 x 1080
- Brightness (nits): 250
- Aspect Ratio: 16 : 9
- DisplayColors: 16.7 M
- Contrast Ratio: 3000:1
- Backlight: LED
- Connectivity
- VGA Port In: 1
- DVI-D In: 1
- HDMI In: 1

Chassis Specifications:

General

- Form Factor: Micro PC
- Color: Black
- Material: Metal/Steel
- Material Thickness: 1mm
- Motherboard Compatibility: Mini ITX
- Slide Rails: Optional

Expansion

- Full Height Slots: 1
- Max Card Depth: 7.5"
- Internal 2.5" Bays: 2
- Serial Port Punchouts: 3
- Parallel Port Punchouts: 1
- Antennae Punchout: 2

Front Ports

- USB 2.0 Port (Front): 2

Cooling System

- Maximum Fan Count: 2

Physical

- Depth: 2.60"
- Depth (Inches): 2.6
- Width: 12.30"
- Height: 8.27"
- Shipping Box - Depth: 16"
- Shipping Box - Width: 16"
- Shipping Box - Height: 8"
- Shipping Weight: 11lbs

Other Features

- Chassis Warranty: 1 Year

Power

- Built-in Chassis Power Supply: AC/DC Power Adapter Included



www.superlogics.com
Phone: 1-508-650-9500

sales@superlogics.com
Fax: 1-508-650-9525