

HMI Panel PC Panel PC

Configuration Number: BASE CONFIG
SL-PPC-22AWHD-LLH110A-S19



21.5" Open Frame Widescreen

Type:

- Panel PC
- **Screen:**
 - 21.5" Multi-Touch Projected Capacitive, Native Resolution: 1920 x 1080, Front Panel Rating: Not Rated
- **Mounting:** Suitable for Mounting in Cut-Out

Motherboard:

- Featuring Intel H110 Chipset and 7th and 6th Gen Core i7/i5/i3 (LGA1151) processor
- **Long Production Cycle Motherboard (Through Q1 2030)**
- **Low Profile Slots:**
 - 1 - PCIe x16
- **LAN:** 2x Ports (1GbE + 1GbE)
- **Video:** VGA + DisplayPort + HDMI
- **Audio:** Intel HD Audio
- **Ports:**
 - 4x USB 2.0 Ports (2 Front, 2 Internal Headers)
 - 4x USB 3.2 Gen 1 Ports (4 Rear)
 - 4x COM Ports (1 RS232 Rear, 2 RS232 Internal Headers, 1 RS232/422/485 Rear)
 - See specifications for more ports
- **Operating Temperature:** 0°C to 60°C (32°F to 140°F)

Configuration summary:

- **Processor:** G4400 - 3.3GHz Intel Pentium Dual Core - 3MB Cache, HD

- Graphics 510 (54W) (ERM) or Better
- **Memory:** 8GB DDR4 2666MHz SODIMM RAM
- **Hard Drive:** 250GB SSD SATA 6.0Gb/s 560/530MB/s 2.5" - Samsung 870 EVO
- **Power Supply:** 160w output, 12v input DC-DC Power Supply - AC Adapter Included
- **Operating System:** Not Included -
- **Warranty:** One-Year Depot Warranty

Technical Specifications

MotherBoard Specifications:

Motherboard Model

- Motherboard Type: MiniITX
- Long Production Cycle
- Long Life: YES
- EOL Date: Q1 2030

Supported CPU

- Number of Processors: 1
- Processor Type: 7th and 6th Gen Core i7/i5/i3 (LGA1151)

Chipset

- Chipset: Intel H110 Chipset

Memory

- Memory Type: SO DIMM DDR4 2133MHz
- Memory Type: Non-ECC
- DIMMS: 2
- Maximum Memory: 32GB

On Board Audio

- Audio Type: Intel HD Audio

On Board Video

- Video Chipset: Supported by CPU - depends on CPU selected
- Video on IO: VGA + DisplayPort + HDMI
- VGA Port Out: 1
- Display Port Out: 1
- HDMI Out: 1

LAN

- LAN Ports: 2
- LAN Type: 1GbE + 1GbE

Display Specifications

Display

- Screen Size (inches): 21.5
- Touch Type: Multi-Touch Projected Capacitive
- Aspect Ratio: 16 : 9
- Native Display Resolution: 1920 x 1080
- Brightness (nits): 250
- Screen Refresh Rate: 60Hz
- Display Area (H): 476.06mm
- Display Area (V): 267.79mm
- Aspect Ratio: 16 : 9
- DisplayColors: 16.7 M
- Contrast Ratio: 3000:1
- Backlight: LED
- Viewing Angle(U) : 178
- Viewing Angle(D) : 178
- Viewing Angle(L) : 178
- Viewing Angle(R) : 178

Connectivity

- HDMI In: 1
- Display Port In: 1
- Touchscreen Interface USB Port (Front): 1

Mounting Options

- Mounting Options: VESA 75mm x 75mm, VESA 100mm x 100mm, Other options sold separately
- Suggested Cut-Out Dimension (Width):
- Suggested Cut-Out Dimension (Height):

Physical

- Width:
- Height:

- LAN Chipset: Intel i219V
- Second LAN Chipset: Intel i210AT
- Wireless LAN: No Integrated WLAN

Drive Interface

- SAS 6G Ports: 4

Expansion Slots

- PCI Express x16 Slots On Motherboard: 1

Mini PCIe

- mini PCIe
- mSATA
- USB and PCIe signals (Internal)
- half and/or full size mini PCIe card: full/half size

M.2 Slot Specs

Rear IO

- USB 3.2 Gen 1 Type A Ports (on IO): 4
- Serial (Rear IO): 1
- Serial 232/422/485 Ports: 1
- Audio on IO

Headers

- USB 2.0 Ports (on Headers): 4
- Serial (via Headers): 2
- LVDS
- TPM Support: Via 2.0 Header

Environmental

- Operating Temperature: 0°C to 60°C (32°F to 140°F)
- High Humidity: 90%
- Low Humidity: 5%

Operating System Support

- Windows 7 Ultimate (64-bit)
- Windows 7 Pro (32-bit)
- Windows 7 Pro (64-bit)
- Windows 7 Pro (FES) 32-Bit
- Windows 7 Pro (FES) 64-Bit
- Windows 7 PRO (FES) DGS 32-BIT
- Windows 7 PRO (FES) DGS 64-BIT
- SL-Windows 10PRO to 7PRO 32-bit
- SL-Windows 10PRO to 7PRO 64-bit
- Windows Embedded 7 (32-Bit)
- Windows Embedded 7 (64-Bit)
- Windows 8.1 (32-bit)
- Windows 8.1 (64-bit)
- Windows 8.1 Pro (32-bit)
- Windows 8.1 Pro (64-bit)
- Windows Embedded 8 (32-bit)
- Windows Embedded 8 (64-bit)

- Depth:
- Depth (Inches): Click Available Downloads Tab > Mechanical Drawings.
- Unboxed Weight: 12lbs
- Shipping Weight: 18lbs

Environmental

- MTBF: 30000hours
- Maximum Operating Temperature: 50C
- High Humidity: 90%
- Low Humidity: 5%
- Storage Temp (High): 60C
- Storage Temp (Low): -20C
- Storage Humidity (High): 90%
- Storage Humidity (Low): 5%

Power

- Power Supply: AC 100~240V/12V DC
- Power Consumption (on): 18Watts

Compliance of Component

- CCC

Warranty

- Warranty: 1 year

Other

- Built-in Chassis Power Supply: Wide Voltage 9-36VDC Input
- Features:

21.5" Open Frame Widescreen

Display Specifications

- Display
- Screen Size: 21.5"
- Touch Type: Multi-Touch Projected Capacitive
- Front Panel Rating: Not Rated
- Color: Black
- Native Display Resolution: 1920 x 1080
- Brightness (nits): 250
- Aspect Ratio: 16 : 9
- DisplayColors: 16.7 M
- Contrast Ratio: 3000:1
- Backlight: LED
- Wide Voltage 9-36VDC Power input
- Connectivity
- Displayport: 1

- Windows 10 Home (32 Bit)
- Windows 10 Home (64 Bit)
- Windows 10 Pro (32 Bit)
- Windows 10 Pro (64-Bit)
- SL-Windows 11PRO to 10PRO 32bit
- SL-Windows 11PRO to 10PRO 64bit
- Windows 10 IoT Value
- Windows 10 IoT Ent
- Windows 10 IoT Value 2019 LTSC
- Windows 10 IoT Ent 2019 LTSC
- Windows 10 IoT 2021 LTSC Value
- Windows 10 IoT 2021 LTSC High End
- LINUX Ubuntu Desktop
- Ubuntu Server Edition
- HDMI In: 1

Compliance of Component

- UL
- CE
- RoHS
- FCC

Other Features

- Other Features:
 - 1 x PCIe 3.0 x16 (in x16) slot
 - 1 (half/full size, supports PCIe x1 and USB device)
 - 1 (full size, shared SATA and USB device)

* Access to PCI Express slot requires expansion slot and a riser in some chassis models. Please check Chassis Specification section for more information.

If you have any questions, please discuss with our Sales Engineers.

- Motherboard Warranty: 1 Year

Chassis Specifications:

General

- Form Factor: Embedded PC
- Color: Black
- Material: Metal/Steel
- Material Thickness: 1mm
- Motherboard Compatibility: Mini ITX

Expansion

- Low Profile Slots: 1
- Max Card Depth: 7.5"
- Internal 2.5" Bays: 2
- Serial Port Punchouts: 2

- Parallel Port Punchouts: 1

Front Ports

- USB 2.0 Ports (Front): 2

Cooling System

- Maximum Fan Count: 2

Physical

- Depth: 8.30"
- Depth (Inches): 8.27
- Width: 8"
- Height: 3.50"
- Shipping Box - Depth: 150mm
- Shipping Box - Width: 380mm
- Shipping Box - Height: 27mm
- Shipping Weight: 13lbs

Other Features

- Chassis Warranty: 1 Year

Power

- Built-in Chassis Power Supply: Power Adapter
Included



www.superlogics.com
Phone: 1-508-650-9500

sales@superlogics.com
Fax: 1-508-650-9525