

1U Rack Mount Server Rackmount

Configuration Number: BASE CONFIG
SL-1U-MCX-C232SSL-LD



(full size images available on web site)

Type:

1U Rack Mount Server
Depth: 11.30"

Motherboard:

Featuring Intel C232 Chipset and Xeon E3-1200v5/v6 (LGA1151, 'Skylake, Kaby Lake') processor

LAN: 3x GB (10/100/1000)

RAID: 0,1,5,10

Video: VGA

Audio: No Onboard Audio

Ports:

6x USB 2.0 Ports (2 Rear, 4 via internal headers)

4x USB 3.0 Ports (2 Rear , 2 via internal headers)

1x COM Port (Rear)

See specifications for more ports

Operating Temperature: 0°C to 50°C (32°F to 122°F)

Also Included:

Processor: G4400 - 3.3GHz Intel Pentium Dual Core - 3MB Cache, HD Graphics 510 (54W) (ERM) or Better [Upgradeable]

Memory: 4GB DDR4 2400MHz RAM [Upgradeable]

Hard Drive: 250GB SSD SATA 6.0Gb/s, 500/300MB/s read/write (or greater) [Upgradeable]

Operating System: Not Included -

Warranty: One-Year Depot Warranty [Upgradeable]

Technical Specifications

MotherBoard Specifications:

Motherboard Model

- Motherboard Type: MicroATX

Supported CPU

- Number of Processors: 1
- Processor Type: Xeon E3-1200v5/v6 (LGA1151, 'Skylake, Kaby Lake')

Chipset

- Chipset: Intel C232 Chipset

Memory

- Memory Type: DDR4 2400MHz ECCU
- Memory Type: ECC Unbuffered
- DIMMS: 4
- Maximum Memory: 64GB

On Board Audio

- Audio Type: No Onboard Audio

On Board Video

- Video Chipset: Supported by CPU - depends on CPU selected
- Video on IO: VGA
- VGA Port Out: 1

LAN

- LAN Ports: 3
- LAN Type: GB (10/100/1000)
- LAN Chipset: Intel i210AT
- Second LAN Chipset: Intel i210AT
- Third LAN Chipset: Dedicated IPMI
- Wireless LAN: No Integrated WLAN

Drive Interface

- SATA III Ports (6GB): 6
- RAID
- RAID Type: Software RAID
- RAID Levels Supported on Motherboard: 0, 1, 5, 10

mini PCIe

Rear IO

- USB 2.0 Ports (on IO): 2
- USB 3.0 Ports (on IO): 2
- Serial (Rear IO): 1

Chassis Specifications:

General

- Form Factor: 1U Rackmount
- Color: Black
- Material: Metal/Steel
- Material Thickness: 1mm

Expansion

- Full Height Slots: 1
- Internal 3.5" Bays: 1
- Internal 2.5" Bays: 2

Cooling System

- Maximum Fan Count: 2
- Included Fans: 2

Physical

- Depth: 11.30"
- Depth (Inches): 11.3
- Width: 17.20"
- Height: 1.70"
- Shipping Box - Depth: 19.80"
- Shipping Box - Width: 25.40"
- Shipping Box - Height: 6.10"
- Shipping Weight: 13lbs

Power

- Built-in Chassis Power Supply: 200W Low Noise AC-DC power supply with PFC

Headers

- USB 2.0 Ports (on Headers): 4
- USB 3.0 Ports (on Headers): 2
- FAN Connectors: 5
- Chassis Intrusion

Management Features

- IPMI
- Watch Dog
- TPM Support: Via 2.0 Header

Environmental

- High Humidity: 90%
- Low Humidity: 8%

Operating System Support

- Windows 7 Ultimate (64-bit)
- Windows 7 Pro (64-bit)
- Windows 7 Pro (FES) 64-Bit
- SL-Windows 10PRO to 7PRO 64-bit
- Windows 10 Home (64 Bit)
- Windows 10 Pro (64-Bit)
- Windows 10 Pro WS (64-Bit)
- Windows 10 IoT Value 2019 LTSC
- Windows 10 IoT Ent 2019 LTSC
- LINUX Ubuntu Desktop
- Ubuntu Server Edition
- Windows Server 2012
- Windows Server 2016 STD
- RED HAT Enterprise LINUX SERVER BASIC
- RED HAT Enterprise LINUX WORKSTATION STANDARD
- RED HAT Enterprise LINUX SERVER STANDARD
- VMWare Compatible

Compliance of Component

- UL
- CE
- RoHS
- FCC

Warranty of Component

- Motherboard Warranty: 1 Year

Other Features

- Other Features:

PCI-E

- 1 PCI-E 3.0 x8 (in x16 slot),
- 1 PCI-E 3.0 x8,
- 1 PCI-E 3.0 x4 (in x8 slot)

SuperLogics[®]

Simplifying Computing[™]

www.superlogics.com
Phone: 1-508-650-9500

sales@superlogics.com
Fax: 1-508-650-9525