

# 4U Rack Mount Industrial PC Rackmount

Configuration Number: BASE CONFIG

SL-4U-LLQ370J-HA





# **TPM Support: 2.0 Module Included**

# Type:

- 4U Rack Mount Industrial PC
- Depth: 17.70", Max Card Depth: 12.28", Locking Front Bezel

# Motherboard:

- Featuring Intel Q370 Chipset and 8th and 9th Gen Core i7/i5/i3 (LGA1151) processor
- Long Production Cycle Motherboard (Through Q2 2033)
- Full Height Slots:
  - 2 PCle x16
  - 1 PCle x4
  - 1 PCle x1
  - 2 PCI
- LAN: 2x Ports (1GbE + 1GbE)
- **RAID:** 0,1,5,10
- Video: 1x VGA, 1x HDMI, 1x DVI-I, 1x DisplayPort
- Audio: Realtek ALC662 HD Audio
- Ports:

4x USB 2.0 Ports ( 2 Front, 2 Internal Headers )

4x USB 3.2 Gen 1 Ports ( 2 Rear, 2

Internal Headers )

4x USB 3.2 Gen 2 Ports ( 4 Rear )

10x COM Ports (8 RS232 Internal Headers, 1 RS232/422/485 Rear, 1

RS232/422/485 Internal Headers)

See specifications for more ports

• Operating Temperature: 0°C to 60°C (32°F to 140°F)

# Configuration summary:

 Processor: G4900 - 3.1GHz Intel Celeron CPU - Dual Core, 2MB Cache, UHD Graphics 610 (54W) (ERM) - or Better

Memory: 8GB DDR4 3200MHz RAM
Hard Drive: 250GB NVMe SSD M.2 2.9GB/1.3GB - Samsung 980

Power Supply: 400W Power Supply
 Operating System: Not Included Warranty: One-Year Depot Warranty

# **Technical Specifications**

# MotherBoard Specifications:

#### **Motherboard Model**

Motherboard Type: ATXLong Production Cycle

Long Life: YESEOL Date: Q2 2033

#### **Supported CPU**

• Number of Processors: 1

 Processor Type: 8th and 9th Gen Core i7/i5/i3 (LGA1151)

## Chipset

• Chipset: Intel Q370 Chipset

#### Memory

• Memory Type: DDR4 2666MHz

• Memory Type: Non-ECC

• DIMMS: 4

• Maximum Memory: 128GB

#### **On Board Audio**

• Audio Type: Realtek ALC662 HD Audio

### **On Board Video**

 Video Chipset: Supported by CPU - depends on CPU selected

 Video on IO: 1x VGA, 1x HDMI, 1x DVI-I, 1x DisplayPort

VGA Port Out: 1

• DVI-D Out: 1

• Display Port Out: 1

• HDMI Out: 1

# **Chassis Specifications:**

#### General

• Form Factor: 4U Rackmount

• Color: Black

• Material: Metal/Steel

Material Thickness: 1mm

Motherboard Compatibility: ATXRedundant Power Supply Capable

• Slide Rails: Optional

## **Expansion**

• Full Height Slots: 7

• Max Card Depth: 12.28"

• External 5.25" Bays: 3

• Internal 3.5" Bays: 2

• External 3.5" Bays: 1

#### **Front Ports**

• USB 2.0 Ports (Front): 2

#### **Cooling System**

• Maximum Fan Count: 2

• Included Fans: 1

## **Physical**

• Depth: 17.70"

• Depth (Inches): 17.7

Width: 19"

• Height: 7"

• Shipping Box - Depth: 26"

• Shipping Box - Width: 23"

• Shipping Box - Height: 12"

#### LAN

• LAN Ports: 2

• LAN Type: 1GbE + 1GbE

• LAN Chipset: Intel i211AT

Second LAN Chipset: Intel i219LMWireless LAN: No Integrated WLAN

#### **Drive Interface**

• SATA III Ports (6GB): 5

• RAID

• RAID Type: Software RAID

• RAID Levels Supported on Motherboard: 0, 1, 5,

10

#### **Expansion Slots**

• PCI Express x16 Slots On Motherboard: 2

• PCI Express x4 Slots On Motherboard: 1

• PCI Express x1 Slots On Motherboard: 1

• PCI Slots (Conventional 32-Bit): 2

#### M.2 Slot Specs

• Total M.2 NVMe SSD Slots: 1

• M.2 Slot #1 Specs

• M.2 SATA SSD

• PCIe Signal

• 22110 - 22 mm x 110 mm.

• 2242 - 22 mm x 42 mm.

• 2260 - 22 mm x 60 mm.

• 2280 - 22 mm x 80 mm.

#### Rear IO

• USB 3.2 Gen 1 Type A Ports (on IO): 2

• USB 3.2 Gen 2 Type A Ports (on IO): 4

• Serial 232/422/485 Ports: 1

Audio on IO

#### **Headers**

• USB 2.0 Ports (on Headers): 4

• USB 3.2 Gen 1 Ports (on Headers): 2

• Serial (via Headers): 8

• Serial 232/422/485 Ports: 1

SPDIF Connector: 1

• FAN Connectors: 3

· Audio on Headers

• TPM Support: 2.0 Module Included

## **Management Features**

AMT

Watch Dog

#### **Environmental**

 Operating Temperature: 0°C to 60°C (32°F to 140°F) • Shipping Weight: 45lbs

#### Other Features

• Chassis Warranty: 1 Year

• High Humidity: 95%

• Low Humidity: 10%

# **Operating System Support**

- Windows 10 Home (64 Bit)
- Windows 10 Pro (64-Bit)
- Windows 10 Pro WS (64-Bit)
- SL-Windows 11PRO to 10PRO 64bit
- Windows 10 IoT Value 2019 LTSC
- Windows 10 IoT Ent 2019 LTSC
- Windows 10 IoT 2021 LTSC Value
- Windows 10 IoT 2021 LTSC High End
- Windows 11 Home (64 Bit)
- Windows 11 Pro (64 Bit)
- Windows 11 Pro for WS (64 Bit)
- Windows 11 IoT 2024 LTSC Value
- Windows 11 IoT 2024 LTSC High End
- LINUX Ubuntu Desktop
- Ubuntu Server Edition

# **Compliance of Component**

- CE
- RoHS
- FCC

#### **Other Features**

• Features:

4 x 288-pin UDIMM Unbuffered Dual Channel DDR4-2666 up to 128GB Total

\* Core i3, Pentium, and Celeron can only support DDR4-2400 up to 64GB Total

1x PCI-E 3.0 x16 Slot (by 16-lane)

1x PCI-E 3.0 x16 Slot (by 8-lane)

1x PCI-E x4 Slot

1x PCI-E x1 Slot

\* Access to PCI Express slot requires expansion slot and a riser in some chassis models. Please check Chassis Specification section for more information.

If you have any questions, please discuss with our Sales Engineers

• Motherboard Warranty: 1 Year



www.superlogics.com sales@superlogics.com Phone: 1-508-650-9500 Fax: 1-508-650-9525