

Desktop PC Desktop

Configuration Number: BASE CONFIG
SL-DK-AX299WS-FW



Please call for availability.

Type:

- Desktop PC
- Dimension: 547mm x 240mm x 475mm

Motherboard:

- Featuring Intel X299 Chipset and Intel Core™ X-series Processors (FCLGA2066) processor
- **Full Height Slots:**
7 - PCIe x16
- **LAN:** 2x Ports (1GbE + 1GbE)
- **RAID:** 0,1,5,10
- **Video:** None
- **Audio:** 8-Channel High Definition Audio CODEC Realtek ALC S1220A
- **Ports:**
4x USB 2.0 Ports (4 Rear)
8x USB 3.2 Gen 1 Ports (2 Front, 6 Rear)
1x USB 3.2 Gen 2 Port (1 Rear)
2x USB 3.2 Gen 2 Type-C Ports (1 Rear, 1 Internal Headers)
1x COM Port (RS232 Internal Headers)
See specifications for more ports
- **Operating Temperature:** 10°C to 35°C (50°F to 95°F)

Configuration summary:

- **Processor:** i9-10900X - 3.7GHz (up to 4.5GHz) Intel Deca (10) Core CPU - 19.25MB Cache, No Onboard Graphics (165W)
- **Memory:** 4 x 8GB DDR4 3200MHz RAM
- **Hard Drive:** 500GB M.2 2280 NVMe SSD or greater 5,000/3,000MB/s

- **Power Supply:** 550W Fully Modular ATX Power Supply - 80+ Bronze
- **Operating System:** Not Included -
- **Warranty:** One-Year Depot Warranty

Technical Specifications

MotherBoard Specifications:

Motherboard Model

- Motherboard Type: SSI CEB

Supported CPU

- Number of Processors: 1
- Processor Type: Intel Core™ X-series Processors (FCLGA2066)

Chipset

- Chipset: Intel X299 Chipset

Memory

- Memory Type: DDR4 2666MHz
- Memory Type: Non-ECC
- DIMMS: 8
- Maximum Memory: 128GB

On Board Audio

- Audio Type: 8-Channel High Definition Audio CODEC Realtek ALC S1220A

On Board Video

- Video Chipset: Supported by CPU - depends on CPU selected
- Video on IO: None

LAN

- LAN Ports: 2
- LAN Type: 1GbE + 1GbE
- LAN Chipset: Intel i210AT
- Second LAN Chipset: Intel i219LM
- Wireless LAN: No Integrated WLAN

Drive Interface

- SATA III Ports (6GB): 8
- RAID
- RAID Type: Software RAID
- RAID Levels Supported on Motherboard: 0, 1, 5, 10

Expansion Slots

Chassis Specifications:

General

- Form Factor: Full Tower
- Front Facing I/O
- Front Changeable Air Filter
- Color: Black
- Material: Metal/Steel
- Material Thickness: 1mm
- Motherboard Compatibility: E-ATX

Expansion

- Full Height Slots: 7
- Max Card Depth: Storage layout: 315 mm - Open layout: 491 mm (467 mm w/ front fan)"
- External 5.25" Bays: 1
- Internal 3.5" Bays: 6
- Internal 2.5" Bays: 2

Front Ports

- USB 3.2 Ports (Front): 5
- Front Audio Ports: 1

Cooling System

- Maximum Fan Count: 9
- Included Fans: 4

Physical

- Depth: 547mm
- Depth (Inches): 21.5
- Width: 240mm
- Height: 475mm
- Shipping Box - Depth: 558mm
- Shipping Box - Width: 363mm
- Shipping Box - Height: 641mm
- Shipping Weight: 36lbs

Other Features

- Chassis Warranty: 1 Year

- PCI Express x16 Slots On Motherboard: 7

M.2 Slot Specs

- Total M.2 NVMe SSD Slots: 2

- M.2 Slot #1 Specs

- PCIe Signal

- 22110 - 22 mm x 110 mm.

- 2242 - 22 mm x 42 mm.

- 2260 - 22 mm x 60 mm.

- 2280 - 22 mm x 80 mm.

- M.2 Slot #2 Specs

- PCIe Signal

- 2242 - 22 mm x 42 mm.

- 2260 - 22 mm x 60 mm.

- 2280 - 22 mm x 80 mm.

Rear IO

- USB 2.0 Ports (on IO): 4

- USB 3.2 Gen 1 Type A Ports (on IO): 6

- USB 3.2 Gen 2 Type A Ports (on IO): 1

- USB 3.2 Gen 2 Type C Ports (on I/O): 1

- SPDIF Connector: 1

- Audio on IO

Headers

- USB 3.2 Gen 1 Ports (on Headers): 2

- USB 3.2 Gen 2 Type-C (on Headers): 1

- Thunderbolt 3 via Header: 1

- Serial (via Headers): 1

- FAN Connectors: 4

- TPM Support: Via 2.0 Header

Environmental

- Operating Temperature: 10°C to 35°C (50°F to 95°F)

- High Humidity: 90%

- Low Humidity: 20%

Operating System Support

- Windows 10 Home (64 Bit)

- Windows 10 Pro (64-Bit)

- Windows 10 Pro WS (64-Bit)

- SL-Windows 11PRO to 10PRO 64bit

- LINUX Ubuntu Desktop

- Ubuntu Server Edition

Compliance of Component

- RoHS

- FCC

Other Features

- Features:

7 x PCIe 3.0/2.0 x16 (single x16 or dual x16/x16

or triple x16/x16/x16 or quad x16/x16/x16/x16 or
seven x16/x8/x8/x8/x8/x8/x8)

PCIe speed may vary due to processor's
limitation. Please check processor's specs for # of
PCIe Lanes.

Supports NVIDIA® 4-Way SLI™ Technology

Supports AMD 4-Way CrossFireX Technology

- Motherboard Warranty: 1 Year



www.superlogics.com
Phone: 1-508-650-9500

sales@superlogics.com
Fax: 1-508-650-9525