

HMI Panel PC Panel PC

Configuration Number: BASE CONFIG
SL-PPC-17A-LLH310J-S18



(Not all images available on web site)

Type:

- Panel PC
- **Screen:**
 - 17" 5-Wire Resistive, Native
Resolution: 1280 x 1024, Front Panel
Rating: IP65 / NEMA4
- **Mounting:** Bezel Mounting Hardware Included, Suitable for Mounting in Cut-Out

Motherboard:

- Featuring Intel H310 Chipset and 8th and 9th Gen Core i7/i5/i3 Processors, LGA1151 processor
- **Long Production Cycle Motherboard (Through Q2 2026)**
- **LAN:** 2x Ports (1GbE + 1GbE)
- **Video:** 1x VGA, 1x DisplayPort, 1x HDMI
- **Audio:** Realtek ALC662 HD Audio
- **Ports:**
 - 2x USB 2.0 Ports (2 Front)
 - 4x USB 3.2 Gen 1 Ports (4 Rear)
 - 6x COM Ports (1 RS232 Rear, 4 RS232 Internal Headers, 1 RS232/422/485 Rear)
 - See specifications for more ports
- **Operating Temperature:** 0°C to 60°C (32°F to 140°F)

Configuration summary:

- **Processor:** G4900 - 3.1GHz Intel Celeron CPU - Dual Core, 2MB Cache, UHD Graphics 610 (54W) (ERM) - or Better
- **Memory:** 8GB DDR4 3200MHz SODIMM RAM
- **Hard Drive:** 500GB M.2 2280 NVMe SSD or greater 5,000/3,000MB/s
- **Power Supply:** 160w output, 12v input

DC-DC Power Supply - AC Adapter
Included

- **Operating System:** Not Included -
- **Warranty:** One-Year Depot Warranty

Technical Specifications

MotherBoard Specifications:

Motherboard Model

- Motherboard Type: MiniITX
- Long Production Cycle
- Long Life: YES
- EOL Date: Q2 2026

Supported CPU

- Number of Processors: 1
- Processor Type: 8th and 9th Gen Core i7/i5/i3 Processors, LGA1151

Chipset

- Chipset: Intel H310 Chipset

Memory

- Memory Type: SO DIMM DDR4 2400MHz
- Memory Type: Non-ECC
- DIMMS: 2
- Maximum Memory: 64GB

On Board Audio

- Audio Type: Realtek ALC662 HD Audio

On Board Video

- Video Chipset: Supported by CPU - depends on CPU selected
- Video on IO: 1x VGA, 1x DisplayPort, 1x HDMI
- VGA Port Out: 1
- Display Port Out: 1
- HDMI Out: 1

LAN

- LAN Ports: 2
- LAN Type and IPMI: 1GbE + 1GbE
- LAN Chipset: Intel i211AT
- Second LAN Chipset: Intel i219LM
- Wireless LAN: No Integrated WLAN

Drive Interface

- SATA III Ports (6GB): 3

Display Specifications

Display

- Screen Size (inches): 17
- Touch Type: 5-Wire Resistive
- Front Panel Rating: IP65 / NEMA4
- Aspect Ratio: 4:3
- Native Display Resolution: 1280 x 1024
- Brightness (nits): 250
- Screen Refresh Rate: 60Hz
- Display Area (H): 337.92mm
- Display Area (V): 270.33mm
- Aspect Ratio: 4:3
- DisplayColors: 16.7 M
- Contrast Ratio: 1000:1
- Backlight: LED
- Viewing Angle(U) : 80
- Viewing Angle(D) : 80
- Viewing Angle(L) : 80
- Viewing Angle(R) : 80

Connectivity

- HDMI In: 1
- Display Port In: 1
- Touchscreen Interface USB Port (Front): 1

Mounting Options

- Mounting Options: VESA 75mm x 75mm, VESA 100mm x 100mm, Bezel Mounting Hardware Included, Other options sold separately
- Suggested Cut-Out Dimension (Width):
- Suggested Cut-Out Dimension (Height):

Physical

- Width:
- Height:
- Depth:
- Depth (Inches): Click Available Downloads Tab > Mechanical Drawings.
- Unboxed Weight: 12lbs

M.2 Slot Specs

- Total M.2 NVMe SSD Slots: 1
- M.2 Slot #1 Specs
- M.2 SATA SSD
- PCIe Signal
- 2242 - 22 mm x 42 mm.
- 2280 - 22 mm x 80 mm.

Rear IO

- USB 3.2 Gen 1 Type A Ports (on IO): 4
- Serial (Rear IO): 1
- Serial 232/422/485 Ports: 1
- Audio on IO

Headers

- USB 2.0 Ports (on Headers): 2
- Serial (via Headers): 4
- FAN Connectors: 2
- Audio on Headers
- LVDS

Environmental

- Operating Temperature: 0°C to 60°C (32°F to 140°F)
- High Humidity: 90%
- Low Humidity: 10%

Operating System Support

- Windows 10 Home (64 Bit)
- Windows 10 Pro (64-Bit)
- Windows 10 Pro WS (64-Bit)
- SL-Windows 11PRO to 10PRO 64bit
- Windows 10 IoT Value 2019 LTSC
- Windows 10 IoT Ent 2019 LTSC
- Windows 10 IoT 2021 LTSC Value
- Windows 10 IoT 2021 LTSC High End
- Windows 11 Pro (64 Bit)
- Windows 11 IoT 2024 LTSC Value
- Windows 11 IoT 2024 LTSC High End
- LINUX Ubuntu Desktop
- Ubuntu Server Edition

Compliance of Component

- CE
- RoHS
- FCC

Other Features

- Other Features:
 - 1 x PCI Express x16 slot, running at x16 (PCIEX16)
(The PCIEX16 slot conforms to PCI Express

- Shipping Weight: 35lbs

Environmental

- MTBF: 30000hours
- Maximum Operating Temperature: 50C
- High Humidity: 90%
- Low Humidity: 8%
- Storage Temp (High): 60C
- Storage Humidity (High): 90%
- Storage Humidity (Low): 8%

Power

- Power Supply: AC 100~240V/12V DC
- Power Consumption (on): 13Watts

Compliance of Component

- CE
- RoHS
- FCC
- CCC

Warranty

- Warranty: 1 year

Other

- Built-in Chassis Power Supply: Wide DC Voltage Input: 9 - 36VDC
- Features:

Industrial Display

- Screen Size: 17"
- Touch Type: 5-Wire Resistive
- Front Panel Rating: IP65 / NEMA4
- Native Display Resolution: 1280 x 1024
- Brightness (nits): 250
- Wide DC Voltage Input: 9 - 36VDC

3.0 standard.)

- 1 x M.2 Socket 1 connector for an Intel CNVi or PCIe wireless module (CNVi)
- Motherboard Warranty: 1 Year

Chassis Specifications:

General

- Form Factor: Micro PC
- Color: Black
- Material: Metal/Steel
- Material Thickness: 1mm
- Motherboard Compatibility: Mini ITX
- Slide Rails: Optional

Expansion

- Full Height Slots: 1
- Max Card Depth: 7.5"
- Internal 2.5" Bays: 2
- Serial Port Punchouts: 3
- Parallel Port Punchouts: 1
- Antennae Punchout: 2

Front Ports

- USB 2.0 Ports (Front): 2

Cooling System

- Maximum Fan Count: 2

Physical

- Depth: 2.60"
- Depth (Inches): 2.6
- Width: 12.30"
- Height: 8.27"
- Shipping Box - Depth: 16"
- Shipping Box - Width: 16"
- Shipping Box - Height: 8"
- Shipping Weight: 11lbs

Other Features

- Chassis Warranty: 1 Year

Power

- Built-in Chassis Power Supply: AC/DC Power Adapter Included