

## HMI Panel PC Panel PC

Configuration Number: BASE CONFIG  
SL-PPC-17A-AH610I-S18



(Not all images available on web site)

### Type:

- Panel PC
- **Screen:**
  - 17" 5-Wire Resistive, Native  
Resolution: 1280 x 1024, Front Panel  
Rating: IP65 / NEMA4
- **Mounting:** Bezel Mounting Hardware Included, Suitable for Mounting in Cut-Out

### Motherboard:

- Featuring Intel H610 Chipset and 12th Gen Core, Pentium Gold and Celeron (LGA1700) processor
- **LAN:** 1x Ports (1GbE (10/100/1000))
- **WiFi:** Wireless AC + BT
- **Video:** 1x DisplayPort + HDMI
- **Audio:** Realtek ALC897
- **Ports:**
  - 4x USB 2.0 Ports ( 2 Front, 2 Rear )
  - 4x USB 3.2 Gen 1 Ports ( 2 Rear, 2 Internal Headers )
  - See specifications for more ports
- **Operating Temperature:** 5°C to 50°C (41°F to 122°F)

### Configuration summary:

- **Processor:** G7400 - 3.70GHz Intel Pentium Gold CPU - Dual Core, 6MB Cache, UHD Graphics 710 (Base 46W) (ERM)
- **Memory:** 8GB DDR4 3200MHz RAM
- **Hard Drive:** 250GB NVMe SSD M.2 2.9GB/1.3GB - Samsung 980
- **Power Supply:** 160w output, 12v input DC-DC Power Supply - AC Adapter Included

- **Operating System:** Not Included -
- **Warranty:** One-Year Depot Warranty

# Technical Specifications

## MotherBoard Specifications:

### Motherboard Model

- Motherboard Type: MiniITX

### Supported CPU

- Number of Processors: 1
- Processor Type: 12th Gen Core, Pentium Gold and Celeron (LGA1700)

### Chipset

- Chipset: Intel H610 Chipset

### Memory

- Memory Type: DDR4 2666MHz
- Memory Type: Non-ECC
- DIMMS: 2
- Maximum Memory: 64GB

### On Board Audio

- Audio Type: Realtek ALC897

### On Board Video

- Video Chipset: Supported by CPU - depends on CPU selected
- Video on IO: 1x DisplayPort + HDMI
- Display Port Out: 1
- HDMI Out: 1

### LAN

- LAN Ports: 1
- LAN Type: 1GbE (10/100/1000)
- LAN Chipset: Intel i219V
- Wireless LAN: Wireless AC + BT

### Drive Interface

- SATA III Ports (6GB): 4

### M.2 Slot Specs

- Total M.2 NVMe SSD Slots: 1
- M.2 Slot #1 Specs
- M.2 SATA SSD
- PCIe Signal
- 2280 - 22 mm x 80 mm.

## Display Specifications

### Display

- Screen Size (inches): 17
- Touch Type: 5-Wire Resistive
- Front Panel Rating: IP65 / NEMA4
- Aspect Ratio: 4:3
- Native Display Resolution: 1280 x 1024
- Brightness (nits): 250
- Screen Refresh Rate: 60Hz
- Display Area (H): 337.92mm
- Display Area (V): 270.33mm
- Aspect Ratio: 4:3
- DisplayColors: 16.7 M
- Contrast Ratio: 1000:1
- Backlight: LED
- Viewing Angle(U) : 80
- Viewing Angle(D) : 80
- Viewing Angle(L) : 80
- Viewing Angle(R) : 80

### Connectivity

- HDMI In: 1
- Display Port In: 1
- Touchscreen Interface USB Port (Front): 1

### Mounting Options

- Mounting Options: VESA 75mm x 75mm, VESA 100mm x 100mm, Bezel Mounting Hardware Included, Other options sold separately
- Suggested Cut-Out Dimension (Width):
- Suggested Cut-Out Dimension (Height):

### Physical

- Width:
- Height:
- Depth:
- Depth (Inches): Click Available Downloads Tab > Mechanical Drawings.
- Unboxed Weight: 12lbs
- Shipping Weight: 35lbs

### Environmental

### **Rear IO**

- PS/2 Combo (Mouse/Keyboard)
- USB 2.0 Ports (on IO): 2
- USB 3.2 Gen 1 Type A Ports (on IO): 2
- Audio on IO

### **Headers**

- USB 2.0 Ports (on Headers): 2
- USB 3.2 Gen 1 Ports (on Headers): 2
- FAN Connectors: 2
- Audio on Headers

### **Environmental**

- Operating Temperature: 5°C to 50°C (41°F to 122°F )
- High Humidity: 90%
- Low Humidity: 5%

### **Operating System Support**

- Windows 10 Home (64 Bit)
- Windows 10 Pro (64-Bit)
- SL-Windows 11PRO to 10PRO 64bit
- Windows 10 IoT Value 2019 LTSC
- Windows 10 IoT Ent 2019 LTSC
- Windows 10 IoT 2021 LTSC Value
- Windows 10 IoT 2021 LTSC High End
- Windows 11 Home (64 Bit)
- Windows 11 Pro (64 Bit)
- Windows 11 IoT 2024 LTSC Value
- Windows 11 IoT 2024 LTSC High End
- LINUX Ubuntu Desktop
- Ubuntu Server Edition

### **Compliance of Component**

- CE
- FCC

### **Other Features**

- Other Features:  
Expansion Slot
  - 1 x PCIe 4.0 x16 Slot (PCIe1), supports x16 mode\*

\* Access to PCI Express slot requires expansion slot and a riser in some chassis models. Please check Chassis Specification section for more information.

If you have any questions, please discuss with our Sales Engineers.

- Motherboard Warranty: 1 Year

- MTBF: 30000hours
- Maximum Operating Temperature: 50C
- High Humidity: 90%
- Low Humidity: 8%
- Storage Temp (High): 60C
- Storage Humidity (High): 90%
- Storage Humidity (Low): 8%

### **Power**

- Power Supply: AC 100~240V/12V DC
- Power Consumption (on): 13Watts

### **Compliance of Component**

- CE
- RoHS
- FCC
- CCC

### **Warranty**

- Warranty: 1 year

### **Other**

- Built-in Chassis Power Supply: Wide DC Voltage Input: 9 - 36VDC

- Features:

### **Industrial Display**

- Screen Size: 17"
- Touch Type: 5-Wire Resistive
- Front Panel Rating: IP65 / NEMA4
- Native Display Resolution: 1280 x 1024
- Brightness (nits): 250
- Wide DC Voltage Input: 9 - 36VDC

## Chassis Specifications:

### General

- Form Factor: Micro PC
- Color: Black
- Material: Metal/Steel
- Material Thickness: 1mm
- Motherboard Compatibility: Mini ITX
- Slide Rails: Optional

### Expansion

- Full Height Slots: 1
- Max Card Depth: 7.5"
- Internal 2.5" Bays: 2
- Serial Port Punchouts: 3
- Parallel Port Punchouts: 1
- Antennae Punchout: 2

### Front Ports

- USB 2.0 Ports (Front): 2

### Cooling System

- Maximum Fan Count: 2

### Physical

- Depth: 2.60"
- Depth (Inches): 2.6
- Width: 12.30"
- Height: 8.27"
- Shipping Box - Depth: 16"
- Shipping Box - Width: 16"
- Shipping Box - Height: 8"
- Shipping Weight: 11lbs

### Other Features

- Chassis Warranty: 1 Year

### Power

- Built-in Chassis Power Supply: AC/DC Power Adapter Included



www.superlogics.com  
Phone: 1-508-650-9500

sales@superlogics.com  
Fax: 1-508-650-9525