

3U Rack Mount Industrial PC Rackmount

Configuration Number: BASE CONFIG

SL-3U-LLQ370J-3N





TPM Support: 2.0 Module Included

Type:

- 3U Rack Mount Industrial PC
- Depth: 21"

Motherboard:

- Featuring Intel Q370 Chipset and 8th and 9th Gen Core i7/i5/i3 (LGA1151) processor
- Long Production Cycle Motherboard (Through Q2 2033)
- Full Height Slots:
 - 2 PCle x16
 - 1 PCle x4
 - 1 PCle x1
 - 2 PCI
- **LAN:** 2x Ports (1GbE + 1GbE)
- **RAID:** 0,1,5,10
- Video: 1x VGA, 1x HDMI, 1x DVI-I, 1x DisplayPort
- Audio: Realtek ALC662 HD Audio
- Ports:

4x USB 2.0 Ports (4 Internal Headers)
4x USB 3.2 Gen 1 Ports (2 Front, 2 Rear)
4x USB 3.2 Gen 2 Ports (4 Rear)
10x COM Ports (8 RS232 Internal
Headers, 1 RS232/422/485 Rear, 1
RS232/422/485 Internal Headers)
See specifications for more ports

• Operating Temperature: 0°C to 60°C (32°F to 140°F)

Configuration summary:

 Processor: G4900 - 3.1GHz Intel Celeron CPU - Dual Core, 2MB Cache, UHD

Graphics 610 (54W) (ERM) - or Better

• Memory: 8GB DDR4 3200MHz RAM

 Hard Drive: 500GB M.2 2280 NVMe SSD or greater 5,000/3,000MB/s

Power Supply: 500W 211

 Power Supply: 500W 2U Power Supply -80+ Gold efficiency rating

Operating System: Not Included Warranty: One-Year Depot Warranty

Technical Specifications

MotherBoard Specifications:

Motherboard Model

Motherboard Type: ATXLong Production Cycle

Long Life: YESEOL Date: Q2 2033

Supported CPU

• Number of Processors: 1

 Processor Type: 8th and 9th Gen Core i7/i5/i3 (LGA1151)

Chipset

• Chipset: Intel Q370 Chipset

Memory

• Memory Type: DDR4 2666MHz

• Memory Type: Non-ECC

• DIMMS: 4

• Maximum Memory: 128GB

On Board Audio

• Audio Type: Realtek ALC662 HD Audio

On Board Video

 Video Chipset: Supported by CPU - depends on CPU selected

 Video on IO: 1x VGA, 1x HDMI, 1x DVI-I, 1x DisplayPort

• VGA Port Out: 1

• DVI-D Out: 1

Display Port Out: 1

• HDMI Out: 1

LΔN

• LAN Ports: 2

• LAN Type: 1GbE + 1GbE

Chassis Specifications:

General

Color: Black & SilverMaterial: Metal/SteelMaterial Thickness: 1mm

• Motherboard Compatibility: SSI CEB

• Slide Rails: Optional

Expansion

Full Height Slots: 7
External 5.25" Bays: 6
Internal 3.5" Bays: 1
External 3.5" Bays: 1
Serial Port Punchouts: 2

Front Ports

• USB 3.2 Ports (Front): 2

• Parallel Port Punchouts: 2

Cooling System

• Maximum Fan Count: 2

• Included Fans: 2

Physical

Depth: 21"Width: 16.80"Height: 5.20"

Shipping Box - Depth: 28.10"
Shipping Box - Width: 23.20"
Shipping Box - Height: 12"
Shipping Weight: 33lbs

Compliance of Component

RoHS

- LAN Chipset: Intel i211AT
- Second LAN Chipset: Intel i219LM
- Wireless LAN: No Integrated WLAN

Drive Interface

- SATA III Ports (6GB): 5
- RAID
- RAID Type: Software RAID
- RAID Levels Supported on Motherboard: 0, 1, 5, 10

Expansion Slots

- PCI Express x16 Slots On Motherboard: 2
- PCI Express x4 Slots On Motherboard: 1
- PCI Express x1 Slots On Motherboard: 1
- PCI Slots (Conventional 32-Bit): 2

M.2 Slot Specs

- Total M.2 NVMe SSD Slots: 1
- M.2 Slot #1 Specs
- M.2 SATA SSD
- PCIe Signal
- 22110 22 mm x 110 mm.
- 2242 22 mm x 42 mm.
- 2260 22 mm x 60 mm.
- 2280 22 mm x 80 mm.

Rear IO

- USB 3.2 Gen 1 Type A Ports (on IO): 2
- USB 3.2 Gen 2 Type A Ports (on IO): 4
- Serial 232/422/485 Ports: 1
- Audio on IO

Headers

- USB 2.0 Ports (on Headers): 4
- USB 3.2 Gen 1 Ports (on Headers): 2
- Serial (via Headers): 8
- Serial 232/422/485 Ports: 1
- SPDIF Connector: 1
- FAN Connectors: 3
- Audio on Headers
- TPM Support: 2.0 Module Included

Management Features

- AMT
- Watch Dog

Environmental

- Operating Temperature: 0°C to 60°C (32°F to 140°F)
- High Humidity: 95%
- Low Humidity: 10%

Operating System Support

- Windows 10 Home (64 Bit)
- Windows 10 Pro (64-Bit)
- Windows 10 Pro WS (64-Bit)
- SL-Windows 11PRO to 10PRO 64bit
- Windows 10 IoT Value 2019 LTSC
- Windows 10 IoT Ent 2019 LTSC
- Windows 10 IoT 2021 LTSC Value
- Windows 10 IoT 2021 LTSC High End
- Windows 11 Home (64 Bit)
- Windows 11 Pro (64 Bit)
- Windows 11 Pro for WS (64 Bit)
- Windows 11 IoT 2024 LTSC Value
- Windows 11 IoT 2024 LTSC High End
- LINUX Ubuntu Desktop
- Ubuntu Server Edition

Compliance of Component

- CE
- RoHS
- FCC

Other Features

• Features:

4 x 288-pin UDIMM Unbuffered Dual Channel
DDR4-2666 up to 128GB Total
* Care in Partition and Calaran can appropriate

* Core i3, Pentium, and Celeron can only support DDR4-2400 up to 64GB Total

1x PCI-E 3.0 x16 Slot (by 16-lane)

1x PCI-E 3.0 x16 Slot (by 8-lane)

1x PCI-E x4 Slot

1x PCI-E x1 Slot

* Access to PCI Express slot requires expansion slot and a riser in some chassis models. Please check Chassis Specification section for more information.

If you have any questions, please discuss with our Sales Engineers

• Motherboard Warranty: 1 Year



www.superlogics.com sales@superlogics.com Phone: 1-508-650-9500 Fax: 1-508-650-9525