

## 2U Rack Mount Industrial PC Rackmount

Configuration Number: BASE CONFIG  
SL-2U-LLQ470J-WD



### Type:

- 2U Rack Mount Industrial PC
- Depth: 18", Max Card Depth: 12.25", Locking Front Bezel

### Motherboard:

- Featuring Intel Q470E Chipset and 10th/11th Gen Core i7/i5/i3 (LGA1200) processor
- **Long Production Cycle Motherboard (Through Q2 2035)**
- **Low Profile Slots:**
  - 1 - PCIe x16
  - 1 - PCIe x8
  - 1 - PCIe x4
  - 1 - PCIe x1
- **LAN:** 4x Ports (2.5GbE + 2.5GbE + 1GbE + 1GbE)
- **RAID:** 0,1,5,10
- **Video:** Dual HDMI
- **Audio:** No Onboard Audio
- **Ports:**
  - 4x USB 2.0 Ports ( 4 Internal Headers )
  - 2x USB 3.2 Gen 1 Ports ( 2 Front )
  - 4x USB 3.2 Gen 2 Ports ( 4 Rear )
  - 6x COM Ports (4 RS232 Internal Headers, 2 RS232/422/485 Rear)
  - See specifications for more ports
- **Operating Temperature:** 0°C to 60°C (32°F to 140°F)

### Configuration summary:

- **Processor:** G5905- 3.50GHz Intel Celeron CPU - Dual Core, 4MB Cache, UHD Graphics 610 (58W)
- **Memory:** 8GB DDR4 3200MHz RAM

- **Hard Drive:** 250GB NVMe SSD M.2 2.9GB/1.3GB - Samsung 980
- **Power Supply:** 400W Power Supply
- **Operating System:** Not Included -
- **Warranty:** One-Year Depot Warranty

## Technical Specifications

### MotherBoard Specifications:

#### Motherboard Model

- Motherboard Type: MicroATX
- Long Production Cycle
- Long Life: YES
- EOL Date: Q2 2035

#### Supported CPU

- Number of Processors: 1
- Processor Type: 10th/11th Gen Core i7/i5/i3 (LGA1200)

#### Chipset

- Chipset: Intel Q470E Chipset

#### Memory

- Memory Type: DDR4 2666MHz
- Memory Type: Non-ECC
- DIMMS: 4
- Maximum Memory: 128GB

#### On Board Audio

- Audio Type: No Onboard Audio

#### On Board Video

- Video Chipset: Supported by CPU - depends on CPU selected
- Video on IO: Dual HDMI
- HDMI Out: 2

#### LAN

- LAN Ports: 4
- LAN Type: 2.5GbE + 2.5GbE + 1GbE + 1GbE
- LAN Chipset: Intel i225-LM 2.5GbE Ethernet
- Second LAN Chipset: Intel i225-LM 2.5GbE Ethernet
- Third LAN Chipset: Intel i219-LM
- Fourth LAN Chipset: Intel i210AT
- Wireless LAN: No Integrated WLAN

### Chassis Specifications:

#### General

- Form Factor: 2U Rackmount
- Color: Black & Silver
- Material: Metal/Steel
- Material Thickness: 1mm
- Motherboard Compatibility: ATX
- Slide Rails: Optional

#### Expansion

- Low Profile Slots: 7
- Max Card Depth: 12.25"
- External 5.25" Bays: 1
- Internal 3.5" Bays: 2
- External 3.5" Bays: 1
- Internal 2.5" Bays: 1

#### Front Ports

- USB 3.2 Ports (Front): 2

#### Cooling System

- Maximum Fan Count: 3
- Included Fans: 1

#### Physical

- Depth: 18"
- Depth (Inches): 18
- Width: 16.90"
- Height: 3.50"
- Shipping Box - Depth: 20"
- Shipping Box - Width: 40"
- Shipping Box - Height: 40"
- Shipping Weight: 35lbs

#### Compliance of Component

- RoHS

#### Other Features

- Chassis Warranty: 1 Year

### **Drive Interface**

- SATA III Ports (6GB): 6
- RAID
- RAID Type: Software RAID
- RAID Levels Supported on Motherboard: 0, 1, 5, 10

### **Expansion Slots**

- PCI Express x16 Slots On Motherboard: 1
- PCI Express x8 Slots On Motherboard: 1
- PCI Express x4 Slots On Motherboard: 1
- PCI Express x1 Slots On Motherboard: 1

### **M.2 Slot Specs**

- Total M.2 NVMe SSD Slots: 2
- M.2 Slot #1 Specs
  - PCIe Signal
  - 22110 - 22 mm x 110 mm.
  - 2242 - 22 mm x 42 mm.
  - 2260 - 22 mm x 60 mm.
  - 2280 - 22 mm x 80 mm.
- M.2 Slot #2 Specs
  - PCIe Signal
  - 2260 - 22 mm x 60 mm.
  - 2280 - 22 mm x 80 mm.

### **Rear IO**

- USB 3.2 Gen 2 Type A Ports (on IO): 4
- Serial 232/422/485 Ports: 2

### **Headers**

- USB 2.0 Ports (on Headers): 4
- USB 3.2 Gen 1 Ports (on Headers): 2
- Serial (via Headers): 4
- FAN Connectors: 7
- TPM Support: 2.0 Module Included

### **Management Features**

- AMT

### **Environmental**

- Operating Temperature: 0°C to 60°C (32°F to 140°F )
- High Humidity: 90%
- Low Humidity: 10%

### **Operating System Support**

- Windows 10 Home (64 Bit)
- Windows 10 Pro (64-Bit)
- Windows 10 Pro WS (64-Bit)
- SL-Windows 11PRO to 10PRO 64bit
- Windows 10 IoT Value 2019 LTSC
- Windows 10 IoT Ent 2019 LTSC

### **Power**

- Remote Server Management:

- Windows 10 IoT 2021 LTSC Value
- Windows 10 IoT 2021 LTSC High End
- Windows 11 Home (64 Bit)
- Windows 11 Pro (64 Bit)
- Windows 11 Pro for WS (64 Bit)
- Windows 11 IoT 2024 LTSC Value
- Windows 11 IoT 2024 LTSC High End
- RED HAT Enterprise LINUX WORKSTATION STANDARD
- RED HAT Enterprise LINUX SERVER BASIC
- RED HAT Enterprise LINUX SERVER STANDARD
- LINUX Ubuntu Desktop
- Ubuntu Server Edition

#### **Compliance of Component**

- CE
- RoHS
- FCC

#### **Other Features**

- Features:
  - 1 PCI-E x16 Slot (Gen 3)
  - 1 PCI-E x8 Slot (Gen 3)
  - 1 PCI-E x4 Slot (Gen 3)
  - 1 PCI-E x1 Slot (Gen 3)

\* Access to PCI Express slot requires expansion slot and a riser in some chassis models. Please check Chassis Specification section for more information.

If you have any questions, please discuss with our Sales Engineers.

- Motherboard Warranty: 1 Year



www.superlogics.com  
Phone: 1-508-650-9500

sales@superlogics.com  
Fax: 1-508-650-9525