

1U Rack Mount Server Rackmount

Configuration Number: BASE CONFIG
SL-1U-MCX-C622SPI-LV



(Full size images available on web site)

Type:

- 1U Rack Mount Server
- Depth: 19.85"

Motherboard:

- Featuring Intel C622 Chipset and Intel Xeon Scalable Processors 2nd Gen processor
- **LAN:** 2x Ports (10GbE + 10GbE)
- **RAID:** 0,1,5,10
- **Video:** 1x VGA
- **Audio:** No Onboard Audio
- **Ports:**
 - 6x USB 2.0 Ports (2 Rear, 4 Internal Headers)
 - 4x USB 3.2 Gen 1 Ports (2 Front, 2 Rear)
 - 1x COM Port (RS232 Internal Headers)

See specifications for more ports
- **Operating Temperature:** 0°C to 50°C (32°F to 122°F)

Configuration summary:

- **Processor:** 2nd Gen Xeon Bronze 3204 - 1.90GHz Six Core Intel Processor - 8.25MB Cache (85W)
- **Memory:** 2 x 8GB DDR4 3200MHz ECC Registered RAM
- **Hard Drive:** 500GB M.2 2280 NVMe SSD or greater 5,000/3,000MB/s
- **Power Supply:** 400W Redundant Power Supply Platinum with PMBUS
- **Operating System:** Not Included -
- **Warranty:** One-Year Depot Warranty

Technical Specifications

MotherBoard Specifications:

Motherboard Model

- Motherboard Type: ATX

Supported CPU

- Number of Processors: 1
- Processor Type: Intel Xeon Scalable Processors 2nd Gen

Chipset

- Chipset: Intel C622 Chipset

Memory

- Memory Type: DDR4 2666MHz ECCR
- Memory Type: ECC Registered
- DIMMS: 8
- Maximum Memory: 2048GB

On Board Audio

- Audio Type: No Onboard Audio

On Board Video

- Video Chipset: ASPEED AST2500 BMC
- Video on IO: 1x VGA
- VGA Port Out: 1

LAN

- LAN Ports: 2
- LAN Type and IPMI: 10GbE + 10GbE
- LAN Chipset: Intel X722
- Second LAN Chipset: Intel X557
- Wireless LAN: No Integrated WLAN

Drive Interface

- SATA III Ports (6GB): 10
- RAID
- RAID Type: Software RAID
- RAID Levels Supported on Motherboard: 0, 1, 5, 10

M.2 Slot Specs

- Total M.2 NVMe SSD Slots: 1
- M.2 Slot #1 Specs
- M.2 SATA SSD
- PCIe Signal
- 22110 - 22 mm x 110 mm.
- 2280 - 22 mm x 80 mm.

Chassis Specifications:

General

- Form Factor: 1U Rackmount
- Color: Black & Silver
- Material: Steel & Plastic
- Material Thickness: 1mm
- Motherboard Compatibility: ATX
- Redundant Power Supply Capable
- Slide Rails: Included

Expansion

- Full Height Slots: 1
- 3.5" Hot Swap Bays: 4

Front Ports

- USB 3.2 Ports (Front): 2

Cooling System

- Maximum Fan Count: 4
- Included Fans: 4

Physical

- Depth: 19.85"
- Depth (Inches): 19.85
- Width: 17.20"
- Height: 1.70"
- Shipping Box - Depth: 29.70"
- Shipping Box - Width: 23.40"
- Shipping Box - Height: 8.50"
- Shipping Weight: 34lbs

Compliance of Component

- UL
- CE
- FCC
- CB

Other Features

- Chassis Warranty: 1 Year

Power

- Built-in Chassis Power Supply: 400W Redundant Power Supply Platinum with PMBUS
- Remote Server Management:

Rear IO

- USB 2.0 Ports (on IO): 2
- USB 3.2 Gen 1 Type A Ports (on IO): 2

Headers

- USB 2.0 Ports (on Headers): 4
- USB 3.2 Gen 1 Ports (on Headers): 2
- USB 3.0 Type A Internal: 1
- Serial (via Headers): 1
- FAN Connectors: 7
- TPM Support: Via 2.0 Header

Management Features

- NMI
- Watch Dog

Environmental

- Operating Temperature: 0°C to 50°C (32°F to 122°F)
- High Humidity: 90%
- Low Humidity: 5%

Operating System Support

- Windows 10 Pro (64-Bit)
- Windows 10 Pro WS (64-Bit)
- SL-Windows 11PRO to 10PRO 64bit
- Windows Server 2016 STD
- Windows Server 2019 Std
- RED HAT Enterprise LINUX SERVER BASIC
- RED HAT Enterprise LINUX WORKSTATION STANDARD
- RED HAT Enterprise LINUX SERVER STANDARD
- Ubuntu Server Edition

Compliance of Component

- CE
- FCC

Other Features

- Other Features:

PCI-E

- 1 PCI-E 3.0 x16,
- 1 PCI-E 3.0 x16 (x16 or x8),
- 1 PCI-E 3.0 x8 (x0 or x8),
- 1 PCI-E 3.0 x8,
- 1 PCI-E 3.0 x4 (in x8 slot)

- Motherboard Warranty: 1 Year



Simplifying Computing™

www.superlogics.com
Phone: 1-508-650-9500

sales@superlogics.com
Fax: 1-508-650-9525