

## 2U Rack Mount Industrial PC Rackmount

Configuration Number: BASE CONFIG  
SL-2U-MCX-C621ASPL-DN



### Type:

- 2U Rack Mount Industrial PC
- Depth: 17.72"

### Motherboard:

- Featuring Intel C621A Chipset and Intel Xeon Scalable Processors 3rd Gen processor
- **Low Profile Slots:**
  - 2 - PCIe x16
  - 5 - PCIe x8
- **LAN:** 2x Ports (1GbE + 1GbE)
- **RAID:** 0,1,5,10
- **Video:** 1x VGA
- **Audio:** No Onboard Audio
- **Ports:**
  - 6x USB 2.0 Ports ( 2 Rear, 4 Internal Headers )
  - 4x USB 3.2 Gen 1 Ports ( 2 Front, 2 Rear )
  - 1x COM Port (RS232 Internal Headers)

See specifications for more ports
- **Operating Temperature:** 5°C to 50°C (41°F to 122°F)

### Configuration summary:

- **Processor:** 3rd Gen Xeon Silver 4310 - 2.1GHz (up to 3.3GHz) Twelve Core Intel Processor - 18MB Cache (120W)
- **Memory:** 2 x 8GB DDR4 3200MHz ECC Registered RAM
- **Hard Drive:** 500GB M.2 2280 NVMe SSD or greater 5,000/3,000MB/s
- **Power Supply:** 800W 1+1 redundant PSU 80+ Platinum
- **Operating System:** Not Included -
- **Warranty:** One-Year Depot Warranty

# Technical Specifications

## MotherBoard Specifications:

### Motherboard Model

- Motherboard Type: ATX

### Supported CPU

- Number of Processors: 1
- Processor Type: Intel Xeon Scalable Processors 3rd Gen

### Chipset

- Chipset: Intel C621A Chipset

### Memory

- Memory Type: DDR4 2666MHz ECCR
- Memory Type: ECC Registered
- DIMMS: 8
- Maximum Memory: 2048GB

### On Board Audio

- Audio Type: No Onboard Audio

### On Board Video

- Video Chipset: ASPEED AST2600 BMC
- Video on IO: 1x VGA
- VGA Port Out: 1

### LAN

- LAN Ports: 2
- LAN Type: 1GbE + 1GbE
- LAN Chipset: Intel i210
- Second LAN Chipset: Intel i210
- Wireless LAN: No Integrated WLAN

### Drive Interface

- SATA III Ports (6GB): 10
- RAID
- RAID Type: Software RAID
- RAID Levels Supported on Motherboard: 0, 1, 5, 10

### Expansion Slots

- PCI Express x16 Slots On Motherboard: 2
- PCI Express x8 Slots On Motherboard: 5

### M.2 Slot Specs

- Total M.2 NVMe SSD Slots: 1
- M.2 Slot #1 Specs
- PCIe Signal

## Chassis Specifications:

### General

- Form Factor: 2U Rackmount
- Color: Black
- Material: Metal/Steel
- Material Thickness: 1mm
- Motherboard Compatibility: E-ATX
- Redundant Power Supply Capable
- Slide Rails: Optional

### Expansion

- Low Profile Slots: 7
- 2.5" Hot Swap Bays: 4

### Front Ports

- USB 3.2 Ports (Front): 2

### Cooling System

- Maximum Fan Count: 4
- Included Fans: 4

### Physical

- Depth: 450mm
- Depth (Inches): 17.7
- Width: 438mm
- Height: 88mm
- Shipping Box - Depth: 580mm
- Shipping Box - Width: 655mm
- Shipping Box - Height: 244mm
- Shipping Weight: 29lbs

### Power

- Built-in Chassis Power Supply: 800W 1+1 redundant PSU 80+ Platinum
- Remote Server Management:

- 22110 - 22 mm x 110 mm.
- 2280 - 22 mm x 80 mm.

#### **Rear IO**

- USB 2.0 Ports (on IO): 2
- USB 3.2 Gen 1 Type A Ports (on IO): 2

#### **Headers**

- USB 2.0 Ports (on Headers): 4
- USB 3.2 Gen 1 Ports (on Headers): 2
- USB 3.0 Type A Internal: 1
- Serial (via Headers): 1
- FAN Connectors: 7
- TPM Support: Via 2.0 Header

#### **Management Features**

- Watch Dog

#### **Environmental**

- Operating Temperature: 5°C to 50°C (41°F to 122°F )
- High Humidity: 85%
- Low Humidity: 10%

#### **Operating System Support**

- Windows 10 Pro (64-Bit)
- Windows 10 Pro WS (64-Bit)
- SL-Windows 11PRO to 10PRO 64bit
- Windows Server 2016 STD
- Windows Server 2019 Std
- RED HAT Enterprise LINUX WORKSTATION STANDARD
- RED HAT Enterprise LINUX SERVER BASIC
- RED HAT Enterprise LINUX SERVER STANDARD
- Ubuntu Server Edition

#### **Compliance of Component**

- CE
- RoHS
- FCC

#### **Other Features**

- Other Features:

##### **PCI-E**

- 1 PCI-E 4.0 x16,
- 1 PCI-E 4.0 x8 (in x16 slot),
- 2 PCI-E 4.0 x8,
- 3 PCI-E 3.0 x8

- Motherboard Warranty: 1 Year



Simplifying Computing™

[www.superlogics.com](http://www.superlogics.com)  
Phone: 1-508-650-9500

[sales@superlogics.com](mailto:sales@superlogics.com)  
Fax: 1-508-650-9525