

## 2U Rack Mount Industrial PC Rackmount

Configuration Number: BASE CONFIG  
SL-2U-MCX-C621A-HB1-DS

### Front Facing I/O



#### Type:

- 2U Rack Mount Industrial PC
- Depth: 17.72"



#### Motherboard:

- Featuring Intel C621A Chipset and Intel Xeon Scalable Processors 3rd Gen processor
- **Long Production Cycle Motherboard (Through Q1 2025)**
- **Full Height Slots:**
  - 1 - PCIe x16
  - 1 - PCIe x8
- **LAN:** 2x Ports (1GbE + 1GbE)
- **RAID:** 0,1,5,10
- **Video:** 1x VGA
- **Audio:** No Onboard Audio
- **Ports:**
  - 4x USB 3.2 Gen 1 Ports ( 2 Rear, 2 Internal Headers )

See specifications for more ports

- **Operating Temperature:** 0°C to 0°C (0°F to 0°F)

#### Configuration summary:

- **Processor:** 2 x 3rd Gen Xeon Silver 4310 - 2.1GHz (up to 3.3GHz) Twelve Core Intel Processor - 18MB Cache (120W)
- **Memory:** 4 x 8GB DDR4 3200MHz ECC Registered RAM
- **Hard Drive:** 500GB M.2 2280 NVMe SSD or greater 5,000/3,000MB/s
- **Power Supply:** 800W 1+1 redundant PSU 80+ Platinum

- **Operating System:** Not Included -
- **Warranty:** One-Year Depot Warranty

# Technical Specifications

## MotherBoard Specifications:

### **Motherboard Model**

- Motherboard Type: Extended ATX
- Long Production Cycle
- Long Life: YES
- EOL Date: Q1 2025

### **Supported CPU**

- Number of Processors: 2
- Processor Type: Intel Xeon Scalable Processors 3rd Gen

### **Chipset**

- Chipset: Intel C621A Chipset

### **Memory**

- Memory Type: DDR4 2666MHz ECCR
- Memory Type: ECC Registered
- DIMMS: 16
- Maximum Memory: 128GB

### **On Board Audio**

- Audio Type: No Onboard Audio

### **On Board Video**

- Video Chipset: ASPEED AST2500 BMC
- Video on IO: 1x VGA
- VGA Port Out: 1

### **LAN**

- LAN Ports: 2
- LAN Type: 1GbE + 1GbE
- LAN Chipset: Intel i210AT
- Second LAN Chipset: Intel i210AT
- Wireless LAN: No Integrated WLAN

### **Drive Interface**

- SATA III Ports (6GB): 14
- RAID
- RAID Type: Software RAID
- RAID Levels Supported on Motherboard: 0, 1, 5, 10

## **M.2 Slot Specs**

## Chassis Specifications:

### **General**

- Form Factor: 2U Rackmount
- Front Facing I/O
- Color: Black
- Material: Metal/Steel
- Material Thickness: 1mm
- Motherboard Compatibility: E-ATX
- Redundant Power Supply Capable
- Slide Rails: Optional

### **Expansion**

- Full Height Slots: 2
- 2.5" Hot Swap Bays: 4

### **Cooling System**

- Maximum Fan Count: 4
- Included Fans: 4

### **Physical**

- Depth: 450mm
- Depth (Inches): 17.7
- Width: 438mm
- Height: 88mm
- Shipping Box - Depth: 580mm
- Shipping Box - Width: 655mm
- Shipping Box - Height: 244mm
- Shipping Weight: 29lbs

### **Power**

- Built-in Chassis Power Supply: 800W 1+1 redundant PSU 80+ Platinum

- Total M.2 NVMe SSD Slots: 2

- M.2 Slot #1 Specs

- PCIe Signal

- 22110 - 22 mm x 110 mm.

- 2280 - 22 mm x 80 mm.

- M.2 Slot #2 Specs

- PCIe Signal

- 22110 - 22 mm x 110 mm.

- 2280 - 22 mm x 80 mm.

### **Rear IO**

- USB 3.2 Gen 1 Type A Ports (on IO): 2

### **Headers**

- USB 3.2 Gen 1 Ports (on Headers): 2

- FAN Connectors: 7

- TPM Support: Via 2.0 Header

### **Environmental**

- Operating Temperature: 0°C to 0°C (0°F to 0°F )

### **Operating System Support**

- Windows Server 2016 STD

- Windows Server 2019 Std

- RED HAT Enterprise LINUX WORKSTATION  
STANDARD

- RED HAT Enterprise LINUX SERVER BASIC

- RED HAT Enterprise LINUX SERVER STANDARD

- Ubuntu Server Edition

- VMWare Compatible: Partially Supported

### **Compliance of Component**

- CE

- FCC

### **Other Features**

- Features:

Expansion Slots	Slot_6: 1 x PCIe x16 (Gen4 x16 bus) slot, from CPU_0
	Slot_5: 1 x PCIe x16 (Gen4 x16 bus) slot, from CPU_1
	Slot_4: 1 x PCIe x16 (Gen4 x16 bus) slot, from CPU_1
	Slot_3: 1 x PCIe x16 (Gen4 x16 bus) slot, from CPU_0
	Slot_2: 1 x PCIe x16 (Gen4 x16 bus) slot, from CPU_0
	Slot_1: 1 x PCIe x16

(Gen4 x16 bus) slot,  
from CPU\_1

2 x M.2 slots:

- M-key
- PCIe Gen4 x4 per slot
- Supports

NGFF-22110/2280 cards

- From CPU

\* Access to PCI Express  
slot requires expansion  
slot and a riser in some  
chassis models. Please  
check Chassis  
Specification section for  
more information.

If you have any  
questions, please  
discuss with our Sales  
Engineers.

- Motherboard Warranty: 1 Year

**SuperLogics®**  
Simplifying Computing™

[www.superlogics.com](http://www.superlogics.com)  
Phone: 1-508-650-9500

[sales@superlogics.com](mailto:sales@superlogics.com)  
Fax: 1-508-650-9525