uperLogics

2U Rack Mount Industrial PC Rackmount

Configuration Number: BASE CONFIG SL-2U-LLH610M-GD





Type:

- 2U Rack Mount Industrial PC
- Depth: 15.35", Max Card Depth: 9.00"

Motherboard:

- Featuring Intel H610 Chipset and 13th & 12th Gen Intel Core[™], Pentium Gold and Celeron processor
- Low Profile Slots:
 - 1 PCIe x16
 - 2 PCle x1
 - 1 PCI
- LAN: 1x Ports (1GbE (10/100/1000))
- Video: 1x VGA, 1x DisplayPort, 1x HDMI
- Audio: 7.1 HD Audio
- Ports:

8x USB 2.0 Ports (2 Front, 2 Rear, 4 Internal Headers) 2x USB 3.2 Gen 1 Ports (2 Internal Headers) 2x USB 3.2 Gen 2 Ports (2 Rear) 2x COM Ports (1 RS232 Rear, 1 RS232 Internal Headers) 1x Parallel Port (Headers) See specifications for more ports

• Operating Temperature: 0°C to 40°C (32°F to 104°F)

Configuration summary:

- **Processor:** G7400 3.70GHz Intel Pentium Gold CPU - Dual Core, 6MB Cache, UHD Graphics 710 (Base 46W) (ERM)
- Memory: 8GB DDR4 3200MHz RAM
- Hard Drive: 250GB NVMe SSD M.2 2.9GB/1.3GB - Samsung 980

- Power Supply: 400W Power Supply
- Operating System: Not Included -
- Warranty: One-Year Depot Warranty

Technical Specifications

MotherBoard Specifications:

Motherboard Model

- Motherboard Type: MicroATX
- Long Production Cycle

Supported CPU

- Number of Processors: 1
- Processor Type: 13th & 12th Gen Intel Core[™], Pentium Gold and Celeron

Chipset

• Chipset: Intel H610 Chipset

Memory

- Memory Type: DDR4 3200MHz
- Memory Type: Non-ECC
- DIMMS: 2
- Maximum Memory: 64GB

On Board Audio

Audio Type: 7.1 HD Audio

On Board Video

- Video Chipset: Supported by CPU depends on CPU selected
- Video on IO: 1x VGA, 1x DisplayPort, 1x HDMI
- VGA Port Out: 1
- Display Port Out: 1
- HDMI Out: 1

LAN

- LAN Ports: 1
- LAN Type: 1GbE (10/100/1000)
- LAN Chipset: Intel GbE LAN chip
- Wireless LAN: No Integrated WLAN

Drive Interface

SATA III Ports (6GB): 4

Expansion Slots

- PCI Express x16 Slots On Motherboard: 1
- PCI Express x1 Slots On Motherboard: 2
- PCI Slots (Conventional 32-Bit): 1

Chassis Specifications:

General

- Form Factor: 2U Rackmount
- Color: Black
- Material: Metal/Steel
- Material Thickness: 1mm
- Motherboard Compatibility: Micro ATX
- Slide Rails: Optional

Expansion

- Low Profile Slots: 4
- Max Card Depth: 9.00"
- External 5.25" Bays: 1
- Internal 3.5" Bays: 3

Front Ports

• USB 2.0 Ports (Front): 2

Cooling System

- Maximum Fan Count: 2
- Included Fans: 1

Physical

- Depth: 15.35"
- Depth (Inches): 15.35
- Width: 19"
- Height: 3.50"
- Shipping Box Depth: 22"
- Shipping Box Width: 21"
- Shipping Box Height: 7"
- Shipping Weight: 25lbs

Other Features

• Chassis Warranty: 1 Year

Power

• Remote Server Management:

M.2 Slot Specs

- Total M.2 NVMe SSD Slots: 1
- M.2 Slot #1 Specs
- PCle Signal
- 2242 22 mm x 42 mm.
- 2260 22 mm x 60 mm.
- 2280 22 mm x 80 mm.

Rear IO

- PS/2 Mouse on IO
- PS/2 Keyboard on IO
- USB 2.0 Ports (on IO): 2
- USB 3.2 Gen 2 Type A Ports (on IO): 2
- Serial (Rear IO): 1

Headers

- USB 2.0 Ports (on Headers): 6
- USB 3.2 Gen 1 Ports (on Headers): 2
- Serial (via Headers): 1
- Parallel Ports: 1
- FAN Connectors: 2
- Audio on Headers
- Chassis Intrusion
- TPM Support: 2.0 Module Included

Environmental

- Operating Temperature: 0°C to 40°C (32°F to 104°F)
- High Humidity: 90%
- Low Humidity: 5%

Operating System Support

- Windows 10 Pro (64-Bit)
- SL-Windows 11PRO to 10PRO 64bit
- Windows 10 IoT 2021 LTSC Value
- Windows 10 IoT 2021 LTSC High End
- Windows 11 Home (64 Bit)
- Windows 11 Pro (64 Bit)
- Windows 11 Pro for WS (64 Bit)
- Windows 11 IoT 2024 LTSC Value
- Windows 11 IoT 2024 LTSC High End
- LINUX Ubuntu Desktop
- Ubuntu Server Edition

Compliance of Component

- RoHS
- FCC

Other Features

Features:	
TPM IC	Intel 1
Onboard	3 th &

Expansion	12 th G
Slots	
51015	en
	Proce
	ssors
	1 x
	PCIe
	4.0
	x16
	slot
	Intel
	H610
	Chips
	et
	2 x
	PCIe
	3.0 x1
	slots
	1 x
	PCI
	slot
	* Acc
	ess to
	PCI
	Expre
	ss slot
	requir
	es
	expan
	sion
	slot
	and a
	riser
	in
	some
	chassi
	S
	model
	S.
	Pleas
	e
	check
	Chass
	is
	Speci
	ficatio
	n
	sectio

n for more infor matio n. lf you have any questi ons, pleas е discus s with our Sales Engin eers

• Motherboard Warranty: 1 Year



www.superlogics.com Phone: 1-508-650-9500 sales@superlogics.com Fax: 1-508-650-9525