uperLogics

1U Rack Mount Industrial PC Rackmount

Configuration Number: BASE CONFIG SL-1U-AQ670M-LG



Type:

- 1U Rack Mount Industrial PC
- Depth: 14", Max Card Depth: 12.28"

Motherboard:

- Featuring Intel Q670 Chipset and 13th & 12th Gen Intel Core[™], Pentium Gold and Celeron processor
- Long Production Cycle Motherboard (Through Q1 2025)
- LAN: 1x Ports (1GbE (10/100/1000))
- RAID: 0,1,5,10 and NVMe 0,1,5
- Video: 2x DisplayPort, 1x HDMI
- Audio: 7.1 HD Audio
- Ports:
 - 6x USB 2.0 Ports (2 Front, 2 Rear, 2 Internal Headers)

2x USB 3.2 Gen 1 Ports (2 Internal Headers)

4x USB 3.2 Gen 2 Ports (4 Rear) 2x COM Ports (RS232 Internal Headers) 1x Parallel Port (Headers)

- See specifications for more ports
- Operating Temperature: 0°C to 40°C (32°F to 104°F)

Configuration summary:

- **Processor:** G7400 3.70GHz Intel Pentium Gold CPU - Dual Core, 6MB Cache, UHD Graphics 710 (Base 46W) (ERM)
- Memory: 8GB DDR5 4800MHz RAM Non-ECC Unbuffered DIMM
- Hard Drive: 250GB NVMe SSD M.2 2.9GB/1.3GB - Samsung 980
- Power Supply: 200W ATX12V Power

Supply

- Operating System: Not Included -
- Warranty: One-Year Depot Warranty

Technical Specifications

MotherBoard Specifications:

Motherboard Model

- Motherboard Type: MicroATX
- Long Production Cycle
- Long Life: YES
- EOL Date: Q1 2025

Supported CPU

- Number of Processors: 1
- Processor Type: 13th & 12th Gen Intel Core[™], Pentium Gold and Celeron

Chipset

• Chipset: Intel Q670 Chipset

Memory

- Memory Type: DDR5 4800MHz
- Memory Type: Non-ECC
- DIMMS: 4
- Maximum Memory: 128GB

On Board Audio

• Audio Type: 7.1 HD Audio

On Board Video

- Video Chipset: Supported by CPU depends on CPU selected
- Video on IO: 2x DisplayPort, 1x HDMI
- Display Port Out: 2
- HDMI Out: 1

LAN

- LAN Ports: 1
- LAN Type: 1GbE (10/100/1000)
- LAN Chipset: Intel GbE LAN chip
- Wireless LAN: No Integrated WLAN

Drive Interface

- SATA III Ports (6GB): 6
- RAID
- RAID Type: Software RAID
- RAID Levels Supported on Motherboard: 0, 1, 5,

Chassis Specifications:

General

- Form Factor: 1U Rackmount
- Color: Black & Silver
- Material: Metal/Steel
- Material Thickness: 1mm
- Motherboard Compatibility: ATX
- Slide Rails: Optional

Expansion

- Full Height Slots: 1
- Max Card Depth: 12.28"
- Internal 3.5" Bays: 1

Front Ports

• USB 2.0 Ports (Front): 2

Cooling System

- Maximum Fan Count: 1
- Included Fans: 1

Physical

- Depth: 14"
- Depth (Inches): 14
- Width: 16.80"
- Height: 1.70"
- Shipping Box Depth: 22"
- Shipping Box Width: 21"
- Shipping Box Height: 7"
- Shipping Weight: 20lbs

Compliance of Component

- UL
- CE
- FCC

Other Features

Chassis Warranty: 1 Year

Power

• Built-in Chassis Power Supply: 200W ATX12V Power Supply

• Remote Server Management:

M.2 Slot Specs

- Total M.2 NVMe SSD Slots: 2
- M.2 Slot #1 Specs
- PCle Signal
- 2242 22 mm x 42 mm.
- 2260 22 mm x 60 mm.
- 2280 22 mm x 80 mm.
- M.2 Slot #2 Specs
- PCle Signal
- 2242 22 mm x 42 mm.
- 2260 22 mm x 60 mm.
- 2280 22 mm x 80 mm.

Rear IO

- PS/2 Mouse on IO
- PS/2 Keyboard on IO
- USB 2.0 Ports (on IO): 2
- USB 3.2 Gen 2 Type A Ports (on IO): 4
- Audio on IO

Headers

- USB 2.0 Ports (on Headers): 4
- USB 3.2 Gen 1 Ports (on Headers): 2
- Serial (via Headers): 2
- Parallel Ports: 1
- FAN Connectors: 3
- Audio on Headers
- Chassis Intrusion

Environmental

- Operating Temperature: 0°C to 40°C (32°F to 104°F)
- High Humidity: 95%
- Low Humidity: 20%

Operating System Support

- Windows 10 Home (64 Bit)
- Windows 10 Pro (64-Bit)
- Windows 10 Pro WS (64-Bit)
- SL-Windows 11PRO to 10PRO 64bit
- Windows 10 IoT 2021 LTSC Value
- Windows 10 IoT 2021 LTSC High End
- Windows 11 Home (64 Bit)
- Windows 11 Pro (64 Bit)
- Windows 11 Pro for WS (64 Bit)
- Windows 11 IoT 2024 LTSC Value
- Windows 11 IoT 2024 LTSC High End
- LINUX Ubuntu Desktop
- Ubuntu Server Edition

Compliance of Component

10

- RoHS
- FCC

Other Features

 Features: Expansion Slots

Intel 13th & 12th Gen Processors

1 x PCle 4.0/3.0 x16 slot

Intel Q670 Chipset

2 x PCIe 3.0 x1 slots

Storage

Supports 2 x M.2 slots and 6 x SATA 6Gb/s ports

Intel 13th & 12th Gen Processors

M.2_1 slot (Key M), type 2242/2260/2280

- Intel 12th Gen processors support PCIe 4.0 x4 mode

Intel Q670 Chipset**

M.2_2 slot (Key M), type 2242/2260/2280(supports PCIe 4.0 x4 mode)

6 x SATA 6Gb/s ports

* Intel Rapid Storage Technology supports NVMe RAID 0/1/5, SATA RAID 0/1/5/10.

** Intel Rapid Storage Technology supports Intel Optane Memory H Series on PCH attached M.2 slots.

* Access to PCI Express slot requires expansion slot and a riser in some chassis models. Please check Chassis Specification section for more information.

If you have any questions, please discuss with our Sales Engineers.

Motherboard Warranty: 1 Year



www.superlogics.com Phone: 1-508-650-9500 sales@superlogics.com Fax: 1-508-650-9525