

## Microbox PC Embedded PC

Configuration Number: BASE CONFIG  
SL-EB-J6412-H-2LAN



(Full size images available on web site)

### Type:

- Microbox PC
- Dimension: 109mm x 125mm x 44mm

### Motherboard:

- Featuring Intel Celeron SoC and Intel Celeron J6412 Elkhart Lake Platform (Quad Core 2.0GHz/10W, Turbo 2.6GHz)
- **Long Production Cycle Motherboard (Through Q1 2036)**
- **LAN:** 2x Ports (2.5GbE (10/100/1000/2500))
- **WiFi:** Wireless AC
- **Video:** 1x DisplayPort + HDMI
- **Audio:** Realtek ALC888S HD Audio
- **Ports:**
  - 1x USB 2.0 Port( 1 Front )
  - 1x USB 3.2 Gen 1 Port( 1 Front )
  - 1x USB 3.2 Gen 2 Port ( 1 Rear )
  - See specifications for more ports
- **Operating Temperature:** -20°C to 60°C (-4°F to 140°F)

### Configuration summary:

- **Memory:** 8GB DDR4 3200MHz SODIMM RAM
- **Hard Drive:** 500GB M.2 2280 NVMe SSD or greater 5,000/3,000MB/s
- **Power Supply:** Adapter : AC\_90~240V / DC\_12V/40W
- **Operating System:** Not Included -
- **Warranty:** One-Year Depot Warranty

# Technical Specifications

## MotherBoard Specifications:

### Motherboard Model

- Motherboard Type: NUC (101x101 mm)
- Long Production Cycle
- Long Life: YES
- EOL Date: Q1 2036
- Fanless

### Supported CPU

- Number of Processors: 1
- Processor Type: Embedded CPUs (ultra-low power, soldered down)
- Embedded CPU: Intel Celeron J6412 Elkhart Lake Platform (Quad Core 2.0GHz/10W, Turbo 2.6GHz)

### Chipset

- Chipset: Intel Celeron SoC

### Memory

- Memory Type: SO DIMM DDR4 3200MHz
- Memory Type: Non-ECC
- DIMMS: 1
- Maximum Memory: 32GB

### On Board Audio

- Audio Type: Realtek ALC888S HD Audio

### On Board Video

- Video Chipset: Intel UHD Graphics for 10th Gen Intel Processors
- Video on IO: 1x DisplayPort + HDMI
- Display Port Out: 1
- HDMI Out: 2

### LAN

- LAN Ports: 2
- LAN Type and IPMI: 2.5GbE (10/100/1000/2500)
- LAN Chipset: Intel I225-V 2.5GbE Ethernet
- Second LAN Chipset: Intel i225-V 2.5GbE Ethernet
- Wireless LAN: Wireless AC

### M.2 Slot Specs

- Total M.2 NVMe SSD Slots: 1
- M.2 Slot #1 Specs
- M.2 SATA SSD
- PCIe Signal
- 2260 - 22 mm x 60 mm.
- 2280 - 22 mm x 80 mm.

## Chassis Specifications:

### General

- Form Factor: NUC Box
- Front Facing I/O
- Color: Black
- Material: Steel & Plastic
- Material Thickness: 1mm

### Front Ports

- USB 2.0 Ports (Front): 1
- USB 3.2 Ports (Front): 1
- USB 3.2 Gen 2 Type-C (Front): 2
- Front Audio Ports: 1

### Physical

- Depth: 109.20mm
- Depth (Inches): [Click Available Downloads Tab > Mechanical Drawings.](#)
- Width: 125mm
- Height: 44.50mm
- Shipping Box - Depth:
- Shipping Box - Width:
- Shipping Box - Height:
- Shipping Weight: 2lbs

### Power

- Built-in Chassis Power Supply: Adapter : AC\_90~240V / DC\_12V/40W

**Rear IO**

- USB 3.2 Gen 2 Type A Ports (on IO): 1

**Headers**

- USB 2.0 Ports (on Headers): 1
- USB 3.2 Gen 1 Ports (on Headers): 1
- FAN Connectors: 1

**Management Features**

- TPM Support: TPM via Intel Platform Trust Technology

**Environmental**

- Operating Temperature: -20°C to 60°C (-4°F to 140°F )
- High Humidity: 95%
- Low Humidity: 10%

**Operating System Support**

- Windows 10 Home (64 Bit)
- Windows 10 Pro (64-Bit)
- Windows 10 IoT 2021 LTSC Entry
- Windows 11 Home (64 Bit)
- Windows 11 Pro (64 Bit)
- SL-Windows 11PRO to 10PRO 64bit
- Windows 11 IoT 2024 LTSC Entry
- LINUX Ubuntu Desktop

**Compliance of Component**

- UL
- CE
- RoHS
- FCC
- CB
- CCC

**Warranty of Component**

- Motherboard Warranty: 1 Year



www.superlogics.com  
Phone: 1-508-650-9500

sales@superlogics.com  
Fax: 1-508-650-9525