

4U Rack Mount Server Rackmount

Configuration Number: BASE CONFIG
SL-4U-W790ACE-SA



(Not all images available on web site)

Type:

- 4U Rack Mount Server
- Depth: 18.43", Max Card Depth: Length w/o expansion card retainer: 426mm, Length w/ expansion card retainer: 337mm", Locking Front Bezel

Motherboard:

- Featuring Intel W790 Chipset and Intel Xeon W-3400 Series, LGA4677 processor
- **Full Height Slots:**
 - 5 - PCIe x16
- **LAN:** 2x Ports (2.5GbE + 10GbE)
- **RAID:** 0,1,5,10 and NVMe 0,1 RAID Intel VROC
- **Video:** None
- **Audio:** 8-Channel High Definition Audio CODEC Realtek ALC S1220A
- **Ports:**
 - 12x USB 2.0 Ports (8 Rear, 4 Internal Headers)
 - 2x USB 3.2 Gen 1 Ports (2 Front)
 - 4x USB 3.2 Gen 2 Ports (4 Rear)
 - 1x USB 3.2 Gen 2 Type-C Port (1 Internal Headers)
 - 1x COM Port (RS232 Internal Headers)
 - See specifications for more ports
- **Operating Temperature:** 0°C to 40°C (32°F to 104°F)

Configuration summary:

- **Processor:** Intel Xeon W3-2425 W-2400 Series CPU (6 Core) - 3.0 GHz (Up to 4.4GHz) - 15MB Cache (156W)
- **Memory:** 4 x 16GB DDR5 5600MHz ECC Registered RAM

- **Hard Drive:** 500GB M.2 2280 NVMe SSD or greater 5,000/3,000MB/s
- **Add-In Graphic Card:** NVIDIA RTX A400 4GB GDDR6, PCI Express 4.0 x16 - 4x Mini DisplayPort - Low Profile and Full Height Compatible
- **Power Supply:** 850W ATX12V / EPS12V Full Modular Power Supply - 80+ Gold Certified
- **Operating System:** Not Included -
- **Warranty:** One-Year Depot Warranty

Technical Specifications

MotherBoard Specifications:

Motherboard Model

- Motherboard Type: SSI CEB

Supported CPU

- Number of Processors: 1
- Processor Type: Intel Xeon W-3400 Series, LGA4677

Chipset

- Chipset: Intel W790 Chipset

Memory

- Memory Type: DDR5 4800MHz ECCR
- Memory Type: ECC Registered
- DIMMS: 8
- Maximum Memory: 2048GB

On Board Audio

- Audio Type: 8-Channel High Definition Audio CODEC Realtek ALC S1220A

On Board Video

- Video Chipset: None
- Video on IO: None

LAN

- LAN Ports: 2
- LAN Type and IPMI: 2.5GbE + 10GbE
- LAN Chipset: Intel 2.5Gb Ethernet
- Second LAN Chipset: Marvell AQtion 10Gb Ethernet
- Wireless LAN: No Integrated WLAN

Chassis Specifications:

General

- Form Factor: 4U Rackmount
- Color: Black
- Material: Metal/Steel
- Material Thickness: 1mm
- Motherboard Compatibility: SSI EEB
- Redundant Power Supply Capable
- Slide Rails: Optional

Expansion

- Full Height Slots: 7
- Max Card Depth: Length w/o expansion card retainer: 426mm, Length w/ expansion card retainer: 337mm"
- External 5.25" Bays: 2
- Internal 3.5" Bays: 4
- Internal 2.5" Bays: 2

Front Ports

- USB 3.2 Ports (Front): 2
- USB Type-C (Front): 1
- Front Audio Ports: 1

Cooling System

- Maximum Fan Count: 4
- Included Fans: 2

Physical

- Depth: 18.43"
- Width: 16.93"
- Height: 6.93"
- Shipping Box - Depth:

Drive Interface

- SATA III Ports (6GB): 4
- RAID
- RAID Type: Hardware RAID
- RAID Levels Supported on Motherboard: 0, 1, 5, 10

Expansion Slots

- PCI Express x16 Slots On Motherboard: 5

M.2 Slot Specs

- Total M.2 NVMe SSD Slots: 2
- M.2 Slot #1 Specs
- PCIe Signal
- 2242 - 22 mm x 42 mm.
- 2260 - 22 mm x 60 mm.
- 2280 - 22 mm x 80 mm.
- 22110 - 22 mm x 110 mm.
- M.2 Slot #2 Specs
- PCIe Signal
- 2280 - 22 mm x 80 mm.

Rear IO

- USB 2.0 Ports (on IO): 8
- USB 3.2 Gen 2 Type A Ports (on IO): 4
- USB 3.2 Gen 2x2 Type C Ports (on I/O): 1
- SPDIF Connector: 1
- Audio on IO

Headers

- USB 2.0 Ports (on Headers): 4
- USB 3.2 Gen 1 Ports (on Headers): 2
- USB 3.2 Gen 2 Type-C (on Headers): 1
- Serial (via Headers): 1
- FAN Connectors: 7
- Audio on Headers
- TPM Support: Via 2.0 Header

Environmental

- Operating Temperature: 0°C to 40°C (32°F to 104°F)
- High Humidity: 90%
- Low Humidity: 20%

Operating System Support

- Windows 10 Pro (64-Bit)
- Windows 10 Pro WS (64-Bit)
- SL-Windows 11PRO to 10PRO 64bit
- Windows 11 Pro (64 Bit)
- Windows 11 Pro for WS (64 Bit)
- Windows 11 IoT 2024 LTSC High End

Compliance of Component

- Shipping Box - Width:
- Shipping Box - Height:
- Shipping Weight: 25lbs

Other Features

- Features:

Expansion card

- Length w/ expansion card retainer: 337mm
- Length w/o expansion card retainer: 426mm
- Width w/ GPU holder: 116mm
- Width w/o GPU holder: 154mm

Limitation of CPU cooler

- w/ GPU holder: 130mm
- w/o GPU holder: 148mm

Drive Bays

- External - 5.25" x 2 OR Internal 2.5" x 4 OR Internal 3.5" x 2
- Internal - 2.5" x 1
- Chassis Warranty: 1 Year

- RoHS
- FCC

Other Features

- Features:

Intel Xeon™ W-3400 and W-2400

Series Processors

5 x PCIe 5.0 x16 slot(s) (supports x16, x16, x16,
x0/x8, x16/x8 modes)

Total supports 2 x M.2 slots, 4 x SATA 6Gb/s ports
and 3 x SlimSAS ports*

Intel W790 Chipset**

M.2_1 slot (Key M), type 2242/2260/2280/22110
(supports PCIe 4.0 x4 mode)

M.2_2 slot (Key M), type 2280 (supports PCIe 4.0
x4 mode)

SlimSAS_1 slot supports PCIe 3.0 x4 mode NVMe
device

SlimSAS_2 slot supports PCIe 4.0 x4 mode or up
to 4 SATA devices via a transfer cable. The cable
is purchased separately.

SlimSAS_3 slot supports PCIe 4.0 x4 mode NVMe
device

4 x SATA 6Gb/s ports*

* Supports Intel Virtual RAID on CPU (Intel VROC)
and Intel Volume Management Device (IntelVMD)

** Intel VROC Technology supports PCIe RAID
0/1/5/10, SATA RAID 0/1/5/10. VROC HW_Key is
purchased separately.

- Motherboard Warranty: 1 Year



www.superlogics.com
Phone: 1-508-650-9500

sales@superlogics.com
Fax: 1-508-650-9525