

HMI Panel PC Panel PC

Configuration Number: BASE CONFIG
SL-PPC-19A-LLH610I-S19-NF



FANLESS High Performance Panel PC

Type:

- Fanless Panel PC
- **Screen:**
 - 19" 5-Wire Resistive, Native
Resolution: 1280 x 1024, Front Panel
Rating: IP65 / NEMA4
- **Mounting:** Bezel Mounting Hardware Included, Suitable for Mounting in Cut-Out

Motherboard:

- Featuring Intel H610 Chipset and 12th Gen Core, Pentium Gold and Celeron, LGA1700 processor
- **Long Production Cycle Motherboard (Through Q2 2030)**
- **Low Profile Slots:**
 - 1 - PCIe x16
- **LAN:** 2x Ports (1GbE + 1GbE)
- **Video:** 1x DisplayPort, 2x HDMI
- **Audio:** Realtek ALC897
- **Ports:**
 - 2x USB 2.0 Ports (2 Front)
 - 4x USB 3.2 Gen 1 Ports (4 Rear)
 - 2x COM Port (RS232/422/485 Rear)
 - See specifications for more ports
- **Operating Temperature:** 0°C to 60°C (32°F to 140°F)

Configuration summary:

- **Processor:** i3-12100 - 3.30GHz (up to 4.30GHz) Intel Core CPU - 4 Core, 12MB Cache, UHD Graphics 730 (Base 60W, Max 89W) (ERM)
- **Memory:** 8GB DDR5 5600MHz RAM Non-

ECC Unbuffered SODIMM

- **Hard Drive:** 500GB M.2 2280 NVMe SSD or greater 5,000/3,000MB/s
- **Power Supply:** 160w output, 12v input DC-DC Power Supply - AC Adapter Included
- **Operating System:** Not Included -
- **Warranty:** One-Year Depot Warranty

Technical Specifications

MotherBoard Specifications:

Motherboard Model

- Motherboard Type: MiniITX
- Fanless
- Long Production Cycle
- Long Life: YES
- EOL Date: Q2 2030

Supported CPU

- Number of Processors: 1
- Processor Type: 12th Gen Core, Pentium Gold and Celeron, LGA1700

Chipset

- Chipset: Intel H610 Chipset

Memory

- Memory Type: SO DIMM DDR4 2400MHz
- Memory Type: Non-ECC
- DIMMS: 2
- Maximum Memory: 64GB

On Board Audio

- Audio Type: Realtek ALC897

On Board Video

- Video Chipset: Supported by CPU - depends on CPU selected
- Video on IO: 1x DisplayPort, 2x HDMI
- Display Port Out: 1
- HDMI Out: 2

LAN

- LAN Ports: 2
- LAN Type and IPMI: 1GbE + 1GbE
- LAN Chipset: Intel i219V
- Second LAN Chipset: Intel i210AT

Display Specifications

Display

- Screen Size (inches): 19
- Touch Type: 5-Wire Resistive
- Front Panel Rating: IP65 / NEMA4
- Aspect Ratio: 5 : 4
- Native Display Resolution: 1280 x 1024
- Brightness (nits): 350
- Screen Refresh Rate: 60Hz
- Display Area (H): 376.32mm
- Display Area (V): 301.07mm
- Aspect Ratio: 5 : 4
- DisplayColors: 16.7 M
- Contrast Ratio: 1000:1
- Backlight: LED
- Viewing Angle(U) : 80
- Viewing Angle(D) : 80
- Viewing Angle(L) : 80
- Viewing Angle(R) : 80

Connectivity

- HDMI In: 1
- Display Port In: 1
- Touchscreen Interface USB Port (Front): 1

Mounting Options

- Mounting Options: VESA 75mm x 75mm, VESA 100mm x 100mm, Bezel Mounting Hardware Included, Other options sold separately
- Suggested Cut-Out Dimension (Width):
- Suggested Cut-Out Dimension (Height):

Physical

- Width:
- Height:

- Wireless LAN: No Integrated WLAN

Drive Interface

- SATA III Ports (6GB): 3

Expansion Slots

- PCI Express x16 Slots On Motherboard: 1

M.2 Slot Specs

- Total M.2 NVMe SSD Slots: 1
- M.2 Slot #1 Specs
- M.2 SATA SSD
- PCIe Signal
- 2242 - 22 mm x 42 mm.
- 2260 - 22 mm x 60 mm.
- 2280 - 22 mm x 80 mm.

Rear IO

- USB 3.2 Gen 1 Type A Ports (on IO): 4
- Serial 232/422/485 Ports: 2
- Audio on IO

Headers

- USB 2.0 Ports (on Headers): 2
- FAN Connectors: 2
- Audio on Headers
- LVDS
- Chassis Intrusion
- TPM Support: Via 2.0 Header

Environmental

- Operating Temperature: 0°C to 60°C (32°F to 140°F)
- High Humidity: 95%
- Low Humidity: 10%

Operating System Support

- Windows 10 Home (64 Bit)
- Windows 10 Pro (64-Bit)
- SL-Windows 11PRO to 10PRO 64bit
- Windows 10 IoT 2021 LTSC Value
- Windows 10 IoT 2021 LTSC High End
- Windows 11 Home (64 Bit)
- Windows 11 Pro (64 Bit)
- Windows 11 IoT 2024 LTSC Value
- Windows 11 IoT 2024 LTSC High End
- LINUX Ubuntu Desktop

Compliance of Component

- CE
- FCC

Other Features

- Features:

- Depth:

- Depth (Inches): Click Available Downloads Tab > Mechanical Drawings.
- Unboxed Weight: 14lbs
- Shipping Weight: 40lbs

Environmental

- MTBF: 30000hours
- Maximum Operating Temperature: 50C
- High Humidity: 90%
- Low Humidity: 8%
- Storage Temp (High): 60C
- Storage Temp (Low): -10C
- Storage Humidity (High): 90%
- Storage Humidity (Low): 8%

Power

- Power Supply: AC 100~240V/12V DC
- Power Consumption (on): 18Watts

Compliance of Component

- CE
- RoHS
- CCC

Warranty

- Warranty: 1 year

Other

- Features:

Industrial Display

- Screen Size: 19"
- Touch Type: 5-Wire Resistive
- Front Panel Rating: IP65 / NEMA4
- Native Display Resolution: 1280 x 1024
- Brightness (nits): 350
- Wide Voltage 9-36VDC

1x PCIe 4.0 x16 slot

1x M.2 Socket 3 with key M, type
2242/2260/2280 (SATA/PCIe x4 mode)

1x M.2 Socket 1 with Key E, type 2230 for WIFI/BT
device (PCIe & CNVi)

* Access to PCI Express slot requires expansion
slot and a riser in some chassis models. Please
check Chassis Specification section for more
information.

If you have any questions, please discuss with our
Sales Engineers

- Motherboard Warranty: 1 Year

Chassis Specifications:

General

- Form Factor: Embedded PC
- Color: Black
- Material: Metal/Steel
- Material Thickness: 1mm
- Motherboard Compatibility: Mini ITX

Expansion

- Low Profile Slots: 1
- Max Card Depth: 7.5"
- Internal 2.5" Bays: 2
- Serial Port Punchouts: 2
- Parallel Port Punchouts: 1

Front Ports

- USB 2.0 Ports (Front): 2

Cooling System

- Maximum Fan Count: 2

Physical

- Depth: 8.30"
- Depth (Inches): 8.27
- Width: 8"
- Height: 3.50"
- Shipping Box - Depth: 150mm
- Shipping Box - Width: 380mm
- Shipping Box - Height: 27mm
- Shipping Weight: 13lbs

Other Features

- Chassis Warranty: 1 Year

Power

- Built-in Chassis Power Supply: Power Adapter Included



Simplifying Computing™

www.superlogics.com
Phone: 1-508-650-9500

sales@superlogics.com
Fax: 1-508-650-9525