

Tower Server Desktop

Configuration Number: BASE CONFIG

SL-DK-W790ACE-FW













Type:

- Tower Server
- Dimension: 547mm x 240mm x 475mm

Motherboard:

- Featuring Intel W790 Chipset and Intel Socket LGA4677 for Xeon W-3400 Series processor
- Full Height Slots:
 - 5 PCle x16
- **LAN:** 2x Ports (2.5GbE + 10GbE)
- RAID: 0,1,5,10 and NVMe 0,1 RAID Intel VROC
- Video: None
- Audio: 8-Channel High Definition Audio CODEC Realtek ALC S1220A
- Ports:
 - 12x USB 2.0 Ports (8 Rear, 4 Internal Headers)
 - 2x USB 3.2 Gen 1 Ports (2 Front)
 - 4x USB 3.2 Gen 2 Ports (4 Rear)
 - 1x USB 3.2 Gen 2 Type-C Port (1 Internal Headers)
 - 1x COM Port (RS232 Internal Headers)
 - 1x Front Audio Port
 - See specifications for more ports
- Operating Temperature: 0°C to 40°C (32°F to 104°F)

Configuration summary:

- Processor: Intel Xeon W3-2425 W-2400
 Series CPU (6 Core) 3.0 GHz (Up to 4.4GHz) - 15MB Cache (156W)
- Memory: 4 x 16GB DDR5 4800MHz ECC Registered RAM
- Hard Drive: 500GB M.2 2280 NVMe SSD

or greater

- Add-In Graphic Card: NVIDIA Quadro T400 4GB 64-bit GDDR5 PCIe 3.0 x16 Workstation Video Card - 3 x Mini DisplayPort 1.4 - No Win 7 Support!
- Power Supply: 850W ATX12V / EPS12V
 Full Modular Power Supply 80+ Gold
 Certified
- Operating System: Not Included -Warranty: One-Year Depot Warranty

Technical Specifications

MotherBoard Specifications:

Motherboard Model

Motherboard Type: SSI CEB

Supported CPU

- Number of Processors: 1
- Processor Type: Intel Socket LGA4677 for Xeon W-3400 Series

Chipset

• Chipset: Intel W790 Chipset

Memory

- Memory Type: DDR5 4800MHz ECCR
- Memory Type: ECC Registered
- DIMMS: 8
- Maximum Memory: 2048GB

On Board Audio

 Audio Type: 8-Channel High Definition Audio CODEC Realtek ALC S1220A

On Board Video

- Video Chipset: None
- Video on IO: None

LAN

- LAN Ports: 2
- LAN Type: 2.5GbE + 10GbE
- LAN Chipset: Intel 2.5Gb Ethernet
- Second LAN Chipset: Marvell AQtion 10Gb Ethernet
- Wireless LAN: No Integrated WLAN

Drive Interface

Chassis Specifications:

General

- Form Factor: Full Tower
- Front Facing I/O
- Front Changeable Air Filter
- Color: Black
- Material: Metal/Steel
- Material Thickness: 1mm
- Motherboard Compatibility: E-ATX

Expansion

- Full Height Slots: 7
- Max Card Depth: Storage layout: 315 mm Open layout: 491 mm (467 mm w/ front fan)"
- External 5.25" Bays: 1
- Internal 3.5" Bays: 6
- Internal 2.5" Bays: 2

Front Ports

- USB 3.2 Ports (Front): 5
- Front Audio Ports: 1

Cooling System

- Maximum Fan Count: 9
- Included Fans: 4

Physical

- Depth: 547mm
- Depth (Inches): 21.5
- Width: 240mm
- Height: 475mm
- Shipping Box Depth: 558mm
- Shipping Box Width: 363mm
- Shipping Box Height: 641mm

• SATA III Ports (6GB): 4

RAID

• RAID Type: Hardware RAID

• RAID Levels Supported on Motherboard: 0, 1, 5,

Expansion Slots

• PCI Express x16 Slots On Motherboard: 5

M.2 Slot Specs

Total M.2 NVMe SSD Slots: 2

• M.2 Slot #1 Specs

• PCle Signal

• 2242 - 22 mm x 42 mm.

• 2260 - 22 mm x 60 mm.

• 2280 - 22 mm x 80 mm.

• 22110 - 22 mm x 110 mm.

• M.2 Slot #2 Specs

• PCle Signal

• 2280 - 22 mm x 80 mm.

Rear IO

• USB 2.0 Ports (on IO): 8

• USB 3.2 Gen 2 Type A Ports (on IO): 4

• USB 3.2 Gen 2x2 Type C Ports (on I/O): 1

• SPDIF Connector: 1

• Audio on IO

Headers

• USB 2.0 Ports (on Headers): 4

• USB 3.2 Gen 1 Ports (on Headers): 2

• USB 3.2 Gen 2 Type-C (on Headers): 1

• Serial (via Headers): 1

• FAN Connectors: 7

· Audio on Headers

• TPM Support: Via 2.0 Header

Environmental

• Operating Temperature: 0°C to 40°C (32°F to

104ºF)

• High Humidity: 90%

• Low Humidity: 20%

Operating System Support

• Windows 10 Pro (64-Bit)

• Windows 10 Pro WS (64-Bit)

• SL-Windows 11PRO to 10PRO 64bit

• Windows 11 Pro (64 Bit)

• Windows 11 Pro for WS (64 Bit)

• Windows 11 IoT 2024 LTSC High End

Compliance of Component

RoHS

• Shipping Weight: 36lbs

Other Features

Chassis Warranty: 1 Year

• FCC

Other Features

• Features:

Intel Xeon™ W-3400 and W-2400
Series Processors
5 x PCle 5.0 x16 slot(s) (supports x16, x16, x16, x0/x8, x16/x8 modes)

Total supports 2 x M.2 slots, 4 x SATA 6Gb/s ports and 3 x SlimSAS ports*
Intel W790 Chipset**
M.2_1 slot (Key M), type 2242/2260/2280/22110 (supports PCle 4.0 x4 mode)
M.2_2 slot (Key M), type 2280 (supports PCle 4.0 x4 mode)
SlimSAS_1 slot supports PCle 3.0 x4 mode NVMe device
SlimSAS_2 slot supports PCle 4.0 x4 mode or up to 4 SATA devices via a transfer cable. The cable is perchased seperately.
SlimSAS_3 slot supports PCle 4.0 x4 mode NVMe

4 x SATA 6Gb/s ports*

device

- * Supports Intel Virtual RAID on CPU (Intel VROC) and Intel Volume Management Device (IntelVMD) ** Intel VROC Technology supports PCIe RAID 0/1/5/10, SATA RAID 0/1/5/10. VROC HW_Key is purchased separately.
- Motherboard Warranty: 1 Year



www.superlogics.com Phone: 1-508-650-9500 sales@superlogics.com Fax: 1-508-650-9525