


## 4U Rack Mount Industrial PC Rackmount

Configuration Number: BASE CONFIG  
SL-4U-TRX50-SG-ST



### Liquid Cooled Rack Mount

#### Type:

- 4U Rack Mount Industrial PC
- Depth: 16.89", Max Card Depth: 375mm"

#### Motherboard:

- Featuring AMD TRX50 and AMD Socket sTR5 for Ryzen™ Threadripper™ PRO 7000 WX-Series processor
- **Full Height Slots:**  
5 - PCIe x16
- **LAN:** 2x Ports (2.5GbE + 10GbE )
- **WiFi:** Wi-Fi 7 + BT
- **RAID:** 0,1,5,10 and NVMe 0,1,5
- **Video:** None
- **Audio:** Realtek ALC1220P Surround Sound High Definition Audio CODEC
- **Ports:**  
6x USB 2.0 Ports ( 2 Rear, 4 Internal Headers )  
2x USB 3.2 Gen 1 Ports ( 2 Front )  
6x USB 3.2 Gen 2 Ports ( 6 Rear )  
1x USB 3.2 Gen 2 Type-C Port ( 1 Internal Headers )  
See specifications for more ports
- **Operating Temperature:** 10°C to 35°C (50°F to 95°F)

#### Configuration summary:

- **Processor:** i7-9800X - 3.8GHz (up to 4.4GHz) Intel Octa (8) Core CPU - 16.5MB Cache, No Onboard Graphics (165W)
- **Memory:** 2 x 16GB DDR5 6000MHz ECC RAM..
- **Hard Drive:** 1TB PCIe 4.0 NVMe SSD M.2

- 7,450/6,900MB/s - Samsung 990 PRO
- **Add-In Graphic Card:** NVIDIA Quadro T400 4GB 64-bit GDDR5 PCIe 3.0 x16 Workstation Video Card - 3 x Mini DisplayPort 1.4 - No Win 7 Support!
- **Power Supply:** 850W ATX12V / EPS12V Full Modular Power Supply - 80+ Gold Certified
- **Operating System:** Not Included -
- **Warranty:** One-Year Depot Warranty

## Technical Specifications

### MotherBoard Specifications:

#### Motherboard Model

- Motherboard Type: SSI CEB

#### Supported CPU

- Number of Processors: 1
- Processor Type: AMD Socket sTR5 for Ryzen™ Threadripper™ PRO 7000 WX-Series

#### Chipset

- Chipset: AMD TRX50

#### Memory

- Memory Type: DDR5 4800MHz ECCR
- Memory Type: ECC Registered
- DIMMS: 4

#### On Board Audio

- Audio Type: Realtek ALC1220P Surround Sound High Definition Audio CODEC

#### On Board Video

- Video Chipset: None
- Video on IO: None

#### LAN

- LAN Ports: 2
- LAN Type: 2.5GbE + 10GbE
- LAN Chipset: Marvell AQtion 10Gb Ethernet
- Second LAN Chipset: Intel i226-LM 2.5GbE Ethernet
- Wireless LAN: Wi-Fi 7 + BT

#### Drive Interface

- SATA III Ports (6GB): 4

### Chassis Specifications:

#### General

- Form Factor: 4U Rackmount
- Front Changeable Air Filter
- Color: Black
- Material: Metal/Steel
- Material Thickness: 1mm
- Motherboard Compatibility: SSI CEB
- Redundant Power Supply Capable
- Slide Rails: Optional

#### Expansion

- Full Height Slots: 8
- Max Card Depth: 375mm"
- Internal 3.5" Bays: 3
- Internal 2.5" Bays: 8

#### Front Ports

- USB 3.2 Ports (Front): 2
- USB Type-C (Front): 1

#### Cooling System

- Maximum Fan Count: 3

#### Physical

- Depth: 16.89"
- Depth (Inches): Click Available Downloads Tab > Mechanical Drawings.
- Width: 17"
- Height: 6.96"
- Shipping Box - Depth: 21"
- Shipping Box - Width: 21"
- Shipping Box - Height: 11"
- Shipping Weight: 30lbs

- RAID
- RAID Type: Software RAID
- RAID Levels Supported on Motherboard: 0, 1, 5, 10

#### **Expansion Slots**

- PCI Express x16 Slots On Motherboard: 5

#### **M.2 Slot Specs**

- Total M.2 NVMe SSD Slots: 3
- M.2 Slot #1 Specs
  - PCIe Signal
  - 2242 - 22 mm x 42 mm.
  - 2260 - 22 mm x 60 mm.
  - 2280 - 22 mm x 80 mm.
- M.2 Slot #2 Specs
  - PCIe Signal
  - 2242 - 22 mm x 42 mm.
  - 2260 - 22 mm x 60 mm.
  - 2280 - 22 mm x 80 mm.
- M.2 Slot #3 Specs
  - PCIe Signal
  - 2280 - 22 mm x 80 mm.

#### **Rear IO**

- USB 2.0 Ports (on IO): 2
- USB 3.2 Gen 2 Type A Ports (on IO): 6
- USB 3.2 Gen 2x2 Type C Ports (on I/O): 1
- SPDIF Connector: 1
- Audio on IO

#### **Headers**

- USB 2.0 Ports (on Headers): 4
- USB 3.2 Gen 1 Ports (on Headers): 2
- USB 3.2 Gen 2 Type-C (on Headers): 1
- SPDIF Connector: 1
- FAN Connectors: 6
- Audio on Headers
- Chassis Intrusion
- TPM Support: Via 2.0 Header

#### **Environmental**

- Operating Temperature: 10°C to 35°C (50°F to 95°F )
- High Humidity: 90%
- Low Humidity: 20%

#### **Operating System Support**

- Windows 11 Pro (64 Bit)
- Windows 11 Pro for WS (64 Bit)

#### **Compliance of Component**

- CE

#### **Other Features**

- Features:
  - 8x full height PCIe card slot cutouts
  - Maximum card height: 158mm (card and power connector must be ≤158mm tall)
  - Maximum card length: 375mm (with 25mm thick front fans)
  - 
  - LIQUID COOLING NOTE: radiators reduce the available depth inside the case for long GPUs
  - Inside of case is 399mm deep
  - Thickness of radiator + thickness of case fans + GPU length must equal less than 399mm total.
- Chassis Warranty: 1 Year

- RoHS
- FCC

#### **Other Features**

- Features:

AMD Ryzen™ Threadripper™ PRO 7000 WX-Series and Ryzen™ Threadripper™ 7000 Series Processors

2 x PCIe 5.0 x16 slots

1 x PCIe 5.0 x16 slot(x8 mode)

1 x PCIe 4.0 x16 slot

1 x PCIe 4.0 x16 slot(x4 mode)

Total supports 3 x M.2 slots, 4 x SATA 6Gb/s ports

AMD Ryzen™ Threadripper™ PRO 7000 WX-Series and Ryzen™ Threadripper™ 7000 Series Processors

M.2\_1 slot (Key M), type 2242/2260/2280 (supports PCIe 5.0 x4 mode)

M.2\_2 slot (Key M), type 2242/2260/2280 (supports PCIe 5.0 x4 mode)AMD TRX50 Chipset

M.2\_3 slot (Key M), type 2280(supports PCIe 4.0 x4 mode)

4 x SATA 6Gb/s ports

1 x SlimSAS slot supports PCIe 4.0 x4 mode NVMe device

\* AMD RAIDXpert2 Technology supports both PCIe RAID 0/1/5/10 and SATA RAID 0/1/5/10.

\* Access to PCI Express slot requires expansion slot and a riser in some chassis models. Please check Chassis Specification section for more information.

If you have any questions, please discuss with our Sales Engineers.

- Motherboard Warranty: 1 Year



www.superlogics.com  
Phone: 1-508-650-9500

sales@superlogics.com  
Fax: 1-508-650-9525