

1U Rack Mount Server Rackmount

Configuration Number: BASE CONFIG

SL-1U-C262-RS300-PS4





Type:

- 1U Rack Mount Server
- Depth: 19.57"

Motherboard:

- Featuring Intel C262 Chipset and Intel Xeon E-2400 Processor processor
- Full Height Slots:
 - 1 PCle x16
- LAN: 2x Ports (1GbE + 1GbE + IPMI)
- RAID: 0,1,5,10 Intel VROC
- Video: 1x VGA
- Audio: No Onboard Audio
- Ports:
 - 2x USB 3.2 Gen 1 Ports (2 Front) 3x USB 3.2 Gen 2 Ports (3 Rear) 1x COM Port (RS232 Rear) See specifications for more ports
- Operating Temperature: 10°C to 35°C (50°F to 95°F)

Configuration summary:

- Processor: Intel Xeon E-2414 2.6 GHz -4 cores - 4 threads - 12 MB cache -E-2400 Series (55W)
- Memory: 2 x 16GB DDR5 5600MHz ECC Unbuffered RAM (Requires Intel Core i7/i9 or Xeon Processors)
- Hard Drive: 500GB M.2 2280 NVMe SSD or greater 5,000/3,000MB/s
- Power Supply: Single 350W 80 PLUS Gold Power Supply
- Operating System: Not Included -Warranty: One-Year Depot Warranty

Technical Specifications

MotherBoard Specifications:

Motherboard Model

• Motherboard Type: Proprietary

Supported CPU

• Number of Processors: 1

Processor Type: Intel Xeon E-2400 Processor

Chipset

• Chipset: Intel C262 Chipset

Memory

Memory Type: DDR5 4400MHzMemory Type: ECC Unbuffered

• DIMMS: 4

• Maximum Memory: 128GB

On Board Audio

• Audio Type: No Onboard Audio

On Board Video

• Video Chipset: ASPEED AST2600 BMC

Video on IO: 1x VGAVGA Port Out: 1

LAN

• LAN Ports: 2

• LAN Type: 1GbE + 1GbE + IPMI

• LAN Chipset: Intel i210AT

• Second LAN Chipset: Intel i210AT

• Third LAN Chipset: Dedicated IPMI

• Wireless LAN: No Integrated WLAN

Drive Interface

• SATA III Ports (6GB): 8

RAID

• RAID Type: Hardware RAID

• RAID Levels Supported on Motherboard: 0, 1, 5,

Expansion Slots

• PCI Express x16 Slots On Motherboard: 1

M.2 Slot Specs

• Total M.2 NVMe SSD Slots: 1

M.2 Slot #1 Specs

• PCle Signal

• 2280 - 22 mm x 80 mm.

Chassis Specifications:

General

• Form Factor: 1U Rackmount

• Color: Black & Silver

Material: Metal/Aluminum

• Material Thickness: 1mm

• Redundant Power Supply Capable

Expansion

Full Height Slots: 1Low Profile Slots: 1

• 3.5" or 2.5" Hot Swap Bays: 4

Front Ports

• USB 3.2 Ports (Front): 2

Cooling System

• Maximum Fan Count: 6

• Included Fans: 6

Physical

• Depth: 19.57"

• Depth (Inches): 19.57

Width: 17.31"Height: 1.74"

• Shipping Box - Depth:

• Shipping Box - Width:

• Shipping Box - Height:

• Shipping Weight: 40lbs

Power

Built-in Chassis Power Supply: Single 350W 80
PLUS Gold Power Supply

Rear IO

- USB 3.2 Gen 2 Type A Ports (on IO): 3
- Serial (Rear IO): 1

Headers

• USB 3.2 Gen 1 Ports (on Headers): 2

Management Features

• TPM Support: 2.0 Module Included

Environmental

- Operating Temperature: 10°C to 35°C (50°F to 95ºF)
- High Humidity: 90% • Low Humidity: 20%

Operating System Support

- Windows 11 Pro (64 Bit)
- Windows 11 Pro for WS (64 Bit)
- LINUX Ubuntu Desktop
- Ubuntu Server Edition
- Windows Server 2022 STD

Compliance of Component

- CE
- FCC

Warranty of Component

• Motherboard Warranty: 1 Year

Other Features

• Other Features:

Expansion Slots

Total PCI-E Slots: 3

1 x PCI-E x 16 (Gen5 x16 Link, switch to x8 link when x8 Low Profile Slot is occupied), Full Height

Slot

1 x PCI-E x 8 (Gen5 x8 Link), HH/HL* Low Profile

Slot

Networking

2 x Intel I210AT + 1 x Mgmt LAN

