

## 2U Rack Mount Server Rackmount

Configuration Number: BASE CONFIG  
SL-2U-C256P12-10GB-SG



### Type:

- 2U Rack Mount Server
- Depth: 13.13"

### Motherboard:

- Featuring Intel C256 Chipset and Intel Xeon E-2300 Processor processor
- **Low Profile Slots:**
  - 1 - PCIe x16
  - 3 - PCIe x8
- **LAN:** 2x Ports (10GbE + 10GbE + IPMI)
- **RAID:** 0,1,5,10
- **Video:** 1x VGA
- **Audio:** No Onboard Audio
- **Ports:**
  - 2x USB 2.0 Ports ( 2 Internal Headers )
  - 4x USB 3.2 Gen 1 Ports ( 2 Front, 2 Rear )
  - 2x USB 3.2 Gen 2 Ports ( 2 Rear )
  - 1x COM Port (RS232 Internal Headers)

See specifications for more ports
- **Operating Temperature:** 10°C to 50°C (50°F to 122°F)

### Configuration summary:

- **Processor:** Intel Xeon E-2314 (Up to 4.5 GHz) - 2.8 GHz - 4 core - 4 threads - 8MB Cache - E-2300 Series (65W)
- **Memory:** 2 x 32GB DDR4 3200MHz ECCU RAM
- **Hard Drive:** 500GB M.2 2280 NVMe SSD or greater 5,000/3,000MB/s
- **Power Supply:** 400W 1U FLEX ATX Power Supply - 80+ Gold Efficient
- **Operating System:** Not Included -
- **Warranty:** One-Year Depot Warranty

# Technical Specifications

## MotherBoard Specifications:

### Motherboard Model

- Motherboard Type: ATX

### Supported CPU

- Number of Processors: 1
- Processor Type: Intel Xeon E-2300 Processor

### Chipset

- Chipset: Intel C256 Chipset

### Memory

- Memory Type: DDR4 3200MHz
- Memory Type: ECC Unbuffered
- DIMMS: 4
- Maximum Memory: 128GB

### On Board Audio

- Audio Type: No Onboard Audio

### On Board Video

- Video Chipset: ASPEED AST2600 BMC
- Video on IO: 1x VGA
- VGA Port Out: 1
- HDMI Out: 1

### LAN

- LAN Ports: 2
- LAN Type and IPMI: 10GbE + 10GbE + IPMI
- LAN Chipset: Intel X710-AT2
- Second LAN Chipset: Intel X710-AT2
- Third LAN Chipset: Dedicated IPMI
- Wireless LAN: No Integrated WLAN

### Drive Interface

- SATA III Ports (6GB): 8
- RAID
- RAID Type: Software RAID
- RAID Levels Supported on Motherboard: 0, 1, 5, 10

### Expansion Slots

- PCI Express x16 Slots On Motherboard: 1
- PCI Express x8 Slots On Motherboard: 3

### M.2 Slot Specs

- Total M.2 NVMe SSD Slots: 2
- M.2 Slot #1 Specs

## Chassis Specifications:

### General

- Form Factor: 2U Rackmount
- Front Changeable Air Filter
- Color: Black
- Material: Metal/Steel
- Material Thickness: 1mm
- Motherboard Compatibility: ATX
- Slide Rails: Optional

### Expansion

- Low Profile Slots: 7
- Internal 3.5" Bays: 2
- Internal 2.5" Bays: 4

### Front Ports

- USB 3.2 Ports (Front): 2

### Cooling System

- Maximum Fan Count: 3

### Physical

- Depth: 13.13"
- Width: 17"
- Height: 3.50"
- Shipping Box - Depth: 20"
- Shipping Box - Width: 17"
- Shipping Box - Height: 9"
- Shipping Weight: 12lbs

### Other Features

- Chassis Warranty: 1 Year

### Power

- Remote Server Management:

- M.2 SATA SSD
- PCIe Signal
- 2242 - 22 mm x 42 mm.
- 2260 - 22 mm x 60 mm.
- 2280 - 22 mm x 80 mm.
- 22110 - 22 mm x 110 mm.
- M.2 Slot #2 Specs
- M.2 SATA SSD
- PCIe Signal
- 2242 - 22 mm x 42 mm.
- 2260 - 22 mm x 60 mm.
- 2280 - 22 mm x 80 mm.
- 22110 - 22 mm x 110 mm.

#### **Rear IO**

- PS/2 Combo (Mouse/Keyboard)
- USB 3.2 Gen 1 Type A Ports (on IO): 2
- USB 3.2 Gen 2 Type A Ports (on IO): 2

#### **Headers**

- USB 2.0 Ports (on Headers): 2
- USB 3.2 Gen 1 Ports (on Headers): 2
- USB 3.0 Type A Internal: 1
- Serial (via Headers): 1
- FAN Connectors: 6
- Chassis Intrusion
- TPM Support: Via 2.0 Header

#### **Environmental**

- Operating Temperature: 10°C to 50°C (50°F to 122°F )
- High Humidity: 90%
- Low Humidity: 20%

#### **Operating System Support**

- Windows 11 Pro (64 Bit)
- Windows 11 Pro for WS (64 Bit)
- Windows 11 IoT 2024 LTSC High End
- Windows Server 2019 Std
- Windows Server 2022 STD
- RED HAT Enterprise LINUX SERVER BASIC
- RED HAT Enterprise LINUX WORKSTATION STANDARD
- RED HAT Enterprise LINUX SERVER STANDARD
- LINUX Ubuntu Desktop
- Ubuntu Server Edition

#### **Compliance of Component**

- RoHS
- FCC

#### **Other Features**

- Features:

Expansion Slots

Total Slot : 4  
Slot Location 1 : PCI-E x8  
(Gen3 X4 Link)  
Slot Location 2 : PCI-E x8  
(Gen3 X4 Link)  
Slot Location 4 : PCI-E x8  
(Gen4 X8 Link)  
Slot Location 6 : PCI-E  
x16 (Gen4 X16 Link),  
Auto switch to x8 link if  
slot 4 is occupied

Storage      Stora  
ge  
Contr  
oller :  
8 x  
SATA  
3  
6Gb/s  
ports  
by 4  
Mini-  
SAS  
HD  
conne  
ctors  
2 x  
M.2  
conne  
ctor(2  
242/2  
260/2  
280/2  
2110)  
both  
SATA  
&  
PCIe  
mode  
\*  
\*Gen4  
x4  
Link &  
Gen3  
x2  
Link,g  
ray  
SATA  
port  
will

disabl  
e  
when  
M.2 is  
SATA  
signal

- Motherboard Warranty: 1 Year

*SuperLogics*<sup>®</sup>  
Simplifying Computing<sup>™</sup>

[www.superlogics.com](http://www.superlogics.com)  
Phone: 1-508-650-9500

[sales@superlogics.com](mailto:sales@superlogics.com)  
Fax: 1-508-650-9525