2U Rack Mount Industrial PC Rackmount

Configuration Number: BASE CONFIG
SL-2U-AH810M-GD

Type:

- 2U Rack Mount Industrial PC
- Depth: 15.35", Max Card Depth: 9.00"

Motherboard:

- Featuring Intel H810 Chipset and Intel Core™ Ultra Processors (Series 2), LGA1851 processor
- **Low Profile Slots:**
  1 - PCIe x16
  1 - PCIe x1
- **LAN:** 1x Ports (1GbE (10/100/1000))
- **WiFi:** Wi-Fi 6 + BT 5.2
- **Video:** 1x DisplayPort + HDMI
- **Audio:** Realtek Audio CODEC
- **Ports:**
  6x USB 2.0 Ports (2 Front, 4 Rear)
  2x USB 3.2 Gen 1 Ports (2 Internal Headers)
  2x USB 3.2 Gen 2 Ports (2 Rear)
  1x USB 3.2 Gen 2 Type-C Port (1 Internal Headers)
  1x COM Port (RS232 Internal Headers)
  See specifications for more ports
- **Operating Temperature:** 10ºC to 35ºC (50ºF to 95ºF)

Configuration summary:

- **Processor:** Intel Core Ultra 5 225 Processor - 10 Cores (6P + 4E), 20MB Cache, 121W (PL2)
- **Memory:** 16GB DDR5 5600MHz RAM Non-ECC Unbuffered DIMM
- **Hard Drive:** 500GB M.2 2280 NVMe SSD or greater 5,000/3,000MB/s
- **Power Supply:** 400W ATX Power Supply

- Auto-Switching, 80+ Bronze.
- **Operating System:** Not Included -
- **Warranty:** One-Year Depot Warranty

Technical Specifications

MotherBoard Specifications:

Motherboard Model
- Motherboard Type: MicroATX

Supported CPU
- Number of Processors: 1
- Processor Type: Intel Core™ Ultra Processors (Series 2), LGA1851

Chipset
- Chipset: Intel H810 Chipset

Memory
- Memory Type: DDR5 4800MHz
- Memory Type: Non-ECC
- DIMMS: 2
- Maximum Memory: 128GB

On Board Audio
- Audio Type: Realtek Audio CODEC

On Board Video
- Video Chipset: Supported by CPU - depends on CPU selected
- Video on IO: 1x DisplayPort + HDMI
- Display Port Out: 1
- HDMI Out: 1

LAN
- LAN Ports: 1
- LAN Type and IPMI: 1GbE (10/100/1000)
- LAN Chipset: Intel GbE LAN chip
- Wireless LAN: Wi-Fi 6 + BT 5.2

Drive Interface
- SATA III Ports (6GB): 4

Expansion Slots
- PCI Express x16 Slots On Motherboard: 1
- PCI Express x1 Slots On Motherboard: 1

M.2 Slot Specs
- Total M.2 NVMe SSD Slots: 2

Chassis Specifications:

General
- Form Factor: 2U Rackmount
- Color: Black
- Material: Metal/Steel
- Material Thickness: 1mm
- Motherboard Compatibility: Micro ATX
- Slide Rails: Optional

Expansion
- Low Profile Slots: 4
- Max Card Depth: 9.00"
- External 5.25" Bays: 1
- Internal 3.5" Bays: 3

Front Ports
- USB 2.0 Ports (Front): 2

Cooling System
- Maximum Fan Count: 2
- Included Fans: 1

Physical
- Depth: 15.35"
- Depth (Inches): 15.35
- Width: 19"
- Height: 3.50"
- Shipping Box - Depth: 22"
- Shipping Box - Width: 21"
- Shipping Box - Height: 7"
- Shipping Weight: 25lbs

Other Features
- Chassis Warranty: 1 Year

Power
- Remote Server Management:

- M.2 Slot #1 Specs
- 2280 - 22 mm x 80 mm.
- M.2 Slot #2 Specs
- 2242 - 22 mm x 42 mm.
- 2260 - 22 mm x 60 mm.
- 2280 - 22 mm x 80 mm.

Rear IO

- PS/2 Combo (Mouse/Keyboard)
- USB 2.0 Ports (on IO): 4
- USB 3.2 Gen 2 Type A Ports (on IO): 2
- Audio on IO

Headers

- USB 2.0 Ports (on Headers): 2
- USB 3.2 Gen 1 Ports (on Headers): 2
- USB 3.2 Gen 2 Type-C (on Headers): 1
- Serial (via Headers): 1
- FAN Connectors: 3
- Audio on Headers
- TPM Support: Via 2.0 Header

Environmental

- Operating Temperature: 10ºC to 35ºC (50ºF to 95ºF)
- High Humidity: 95%
- Low Humidity: 5%

Operating System Support

- Windows 11 Home (64 Bit)
- Windows 11 Pro (64 Bit)
- Windows 11 Pro for WS (64 Bit)
- Windows 11 IoT 2024 LTSC Value
- Windows 11 IoT 2024 LTSC High End

Compliance of Component

- CE
- RoHS
- FCC

Other Features

- Features:
  Expansion Slots

  Intel Core™ Ultra Processors (Series 2)
  1 x PCIe 4.0 x16 slot
  Intel H810 Chipset
  1 x PCIe 4.0 x1 slot

  Storage

  Total supports 2 x M.2 slots and 4 x SATA 6Gb/s ports
  Intel H810 Chipset

M.2_1 slot (Key M), type 2280 (supports PCIe 4.0 x4 mode)
M.2_2 slot (Key M), type 2242/2260/2280 (supports PCIe 4.0 x2 mode)
4 x SATA 6Gb/s ports

* Access to PCI Express slot requires expansion slot and a riser in some chassis models. Please check Chassis Specification section for more information.

If you have any questions, please discuss with our Sales Engineers

- Motherboard Warranty: 1 Year

SuperLogics®
Simplifying Computing™

www.superlogics.com
Phone: 1-508-650-9500

sales@superlogics.com
Fax: 1-508-650-9525