uperLogics

Desktop PC Desktop

Configuration Number: BASE CONFIG SL-DK-AH810M-ID





Type:

- Desktop PC
- Dimension: 10.80" x 5.50" x 12.70"

Motherboard:

- Featuring Intel H810 Chipset and Intel Core[™] Ultra Processors (Series 2), LGA1851 processor
- Full Height Slots: 1 - PCle x16
 - 1 PCIe x1
- LAN: 1x Ports (1GbE (10/100/1000))
- **WiFi:** Wi-Fi 6 + BT 5.2
- Video: 1x DisplayPort + HDMI
- Audio: Realtek Audio CODEC
- Ports:
 - 6x USB 2.0 Ports (2 Front, 4 Rear) 2x USB 3.2 Gen 1 Ports (2 Internal Headers)

5x USB 3.2 Gen 2 Ports (5 Rear) 1x USB 3.2 Gen 2 Type-C Port (1 Internal

Headers)

1x COM Port (RS232 Internal Headers) 1x Front Audio Port

See specifications for more ports

• Operating Temperature: 10°C to 35°C (50°F to 95°F)

Configuration summary:

- **Processor:** Intel Core[™] Ultra 5 Processor 225 Processor - 10 Cores (6P + 4E), 20MB Intel Smart Cache, 121W (PL2)
- Memory: 8GB DDR5 4800MHz RAM Non-ECC Unbuffered DIMM
- Hard Drive: 250GB NVMe SSD M.2 2.9GB/1.3GB - Samsung 980

- Power Supply: 300 Watt Power Supply
- Operating System: Not Included -
- Warranty: One-Year Depot Warranty

Technical Specifications

MotherBoard Specifications:

Motherboard Model

• Motherboard Type: MicroATX

Supported CPU

- Number of Processors: 1
- Processor Type: Intel Core[™] Ultra Processors (Series 2), LGA1851

Chipset

• Chipset: Intel H810 Chipset

Memory

- Memory Type: DDR5 4800MHz
- Memory Type: Non-ECC
- DIMMS: 2
- Maximum Memory: 128GB

On Board Audio

• Audio Type: Realtek Audio CODEC

On Board Video

- Video Chipset: Supported by CPU depends on CPU selected
- Video on IO: 1x DisplayPort + HDMI
- Display Port Out: 1
- HDMI Out: 1

LAN

- LAN Ports: 1
- LAN Type: 1GbE (10/100/1000)
- LAN Chipset: Intel GbE LAN chip
- Wireless LAN: Wi-Fi 6 + BT 5.2

Drive Interface

• SATA III Ports (6GB): 4

Expansion Slots

- PCI Express x16 Slots On Motherboard: 1
- PCI Express x1 Slots On Motherboard: 1

M.2 Slot Specs

• Total M.2 NVMe SSD Slots: 2

Chassis Specifications:

General

- Form Factor: Mini Tower
- Color: Black
- Material: Metal/Steel
- Material Thickness: 1mm
- Motherboard Compatibility: Micro ATX

Expansion

- Full Height Slots: 4
- Max Card Depth: 9.5 inches"
- External 5.25" Bays: 1
- Internal 3.5" Bays: 1
- External 3.5" Bays: 1

Front Ports

- USB 2.0 Ports (Front): 4
- Front Audio Ports: 1

Physical

- Depth: 10.80"
- Depth (Inches): 10.8
- Width: 5.50"
- Height: 12.70"
- Shipping Box Depth: 23"
- Shipping Box Width: 23"
- Shipping Box Height: 15"
- Shipping Weight: 24lbs

Compliance of Component

- CE
- RoHS
- FCC

Other Features

• Chassis Warranty: 1 Year

Power

• Built-in Chassis Power Supply: 300 Watt Power Supply

- M.2 Slot #1 Specs
- 2280 22 mm x 80 mm.
- M.2 Slot #2 Specs
- 2242 22 mm x 42 mm.
- 2260 22 mm x 60 mm.
- 2280 22 mm x 80 mm.

Rear IO

- PS/2 Combo (Mouse/Keyboard)
- USB 2.0 Ports (on IO): 4
- USB 3.2 Gen 2 Type A Ports (on IO): 5
- Audio on IO

Headers

- USB 2.0 Ports (on Headers): 2
- USB 3.2 Gen 1 Ports (on Headers): 2
- USB 3.2 Gen 2 Type-C (on Headers): 1
- Serial (via Headers): 1
- FAN Connectors: 3
- Audio on Headers
- TPM Support: Via 2.0 Header

Environmental

- Operating Temperature: 10°C to 35°C (50°F to 95°F)
- High Humidity: 95%
- Low Humidity: 5%

Operating System Support

- Windows 11 Home (64 Bit)
- Windows 11 Pro (64 Bit)
- Windows 11 Pro for WS (64 Bit)
- Windows 11 IoT 2024 LTSC Value
- Windows 11 IoT 2024 LTSC High End

Compliance of Component

- CE
- RoHS
- FCC

Other Features

• Features: Expansion Slots

> Intel Core[™] Ultra Processors (Series 2) 1 x PCle 4.0 x16 slot Intel H810 Chipset 1 x PCle 4.0 x1 slot

Storage

Total supports 2 x M.2 slots and 4 x SATA 6Gb/s ports Intel H810 Chipset M.2_1 slot (Key M), type 2280 (supports PCIe 4.0 x4 mode) M.2_2 slot (Key M), type 2242/2260/2280 (supports PCIe 4.0 x2 mode) 4 x SATA 6Gb/s ports

* Access to PCI Express slot requires expansion slot and a riser in some chassis models. Please check Chassis Specification section for more information.

If you have any questions, please discuss with our Sales Engineers

• Motherboard Warranty: 1 Year



www.superlogics.com Phone: 1-508-650-9500 sales@superlogics.com Fax: 1-508-650-9525