

# 3U Liquid Cooled Rack Mount Industrial PC Rackmount

Configuration Number: BASE CONFIG

SL-3U-GZ890AE-SE





# 1 x Intel Thunderbolt™ 4 (USB Type-C) ports

# Type:

- 3U Liquid Cooled Rack Mount Industrial PC
- Depth: 16.89", Max Card Depth: 375mm"

# Motherboard:

- Featuring Intel Z890 Chipset and Intel Core™ Ultra Processors (Series 2), LGA1851 processor
- Full Height Slots:
  - 3 PCle x16
- LAN: 1x Ports (2.5GbE (10/100/1000/2500))
- **WiFi:** Wi-Fi 7 + BT 5.4
- **RAID:** NVMe 0,1,5,10
- Video: 1x HDMI, 1x DisplayPort, 1x Intel Thunderbolt™ 4
- Audio: Realtek ALC1200 Audio Codec
- Ports:
  - 7x USB 2.0 Ports ( 3 Rear, 4 Internal Headers )
  - 5x USB 3.2 Gen 1 Ports ( 2 Front, 3 Rear )
  - 2x USB 3.2 Gen 2 Ports ( 2 Rear )
  - 1x USB 3.2 Gen 2 Type-C Port ( 1 Internal Headers )
  - 1x Thunderbolt<sup>™</sup> 4 (supports USB 4.0)
  - Type-C Port (Rear)
  - See specifications for more ports
- Operating Temperature: 5°C to 35°C (41°F to 95°F)

# Configuration summary:

• **Processor:** Intel Core™ Ultra 5 Processor

- 225 Processor 10 Cores (6P + 4E), 20MB Intel Smart Cache, 121W (PL2)
- Memory: 2 x 8GB DDR5 4800MHz RAM Non-ECC Unbuffered DIMM
- Hard Drive: 500GB M.2 2280 NVMe SSD or greater 5,000/3,000MB/s
- Power Supply: 700W SFX Form Factor Auto-Switching Power Supply, Fully Modular, 80+ Platinum
- Operating System: Not Included Warranty: One-Year Depot Warranty

# **Technical Specifications**

## MotherBoard Specifications:

#### **Motherboard Model**

• Motherboard Type: ATX

#### **Supported CPU**

- Number of Processors: 1
- Processor Type: Intel Core™ Ultra Processors (Series 2), LGA1851

#### Chipset

• Chipset: Intel Z890 Chipset

#### Memory

- Memory Type: DDR5 4800MHz
- Memory Type: Non-ECC
- DIMMS: 4
- Maximum Memory: 256GB

#### **On Board Audio**

• Audio Type: Realtek ALC1200 Audio Codec

#### **On Board Video**

- Video Chipset: Supported by CPU depends on CPU selected
- Video on IO: 1x HDMI, 1x DisplayPort, 1x Intel Thunderbolt™ 4
- Display Port Out: 1
- HDMI Out: 1
- Thunderbolt™ video outputs: 1

#### LAN

- LAN Ports: 1
- LAN Type: 2.5GbE (10/100/1000/2500)LAN Chipset: Realtek 2.5GbE LAN

# **Chassis Specifications:**

#### General

• Form Factor: 3U Rackmount

• Color: Black

Material: Metal/SteelMaterial Thickness: 1mm

• Motherboard Compatibility: E-ATX

• Slide Rails: Optional

## **Expansion**

• Full Height Slots: 8

• Max Card Depth: 375mm"

• Internal 2.5" Bays: 1

# Front Ports

• USB 3.2 Ports (Front): 2

• USB Type-C (Front): 1

#### **Cooling System**

• Maximum Fan Count: 3

#### **Physical**

• Depth: 16.89"

• Depth (Inches): 17

• Width: 17"

• Height: 5.22"

• Shipping Box - Depth: 21"

• Shipping Box - Width: 21"

• Shipping Box - Height: 10"

Shipping Weight: 28lbs

#### **Other Features**

• Features:

• Wireless LAN: Wi-Fi 7 + BT 5.4

#### **Drive Interface**

- SATA III Ports (6GB): 4
- RAID
- RAID Type: Software RAID
- RAID Levels Supported on Motherboard: 0, 1, 5, 10

#### **Expansion Slots**

PCI Express x16 Slots On Motherboard: 3

#### M.2 Slot Specs

- Total M.2 NVMe SSD Slots: 4
- M.2 Slot #1 Specs
- 2280 22 mm x 80 mm.
- 22110 22 mm x 110 mm.
- M.2 Slot #2 Specs
- 2280 22 mm x 80 mm.
- 22110 22 mm x 110 mm.
- M.2 Slot #3 Specs
- 2280 22 mm x 80 mm.
- 22110 22 mm x 110 mm.
- M.2 Slot #4 Specs
- 2280 22 mm x 80 mm.
- 22110 22 mm x 110 mm.

#### Rear IO

- USB 2.0 Ports (on IO): 3
- USB 3.2 Gen 1 Type A Ports (on IO): 3
- USB 3.2 Gen 2 Type A Ports (on IO): 2
- Thunderbolt™ 4 (supports USB 4.0) Type-C Port: 1

#### **Headers**

- USB 2.0 Ports (on Headers): 4
- USB 3.2 Gen 1 Ports (on Headers): 2
- USB 3.2 Gen 2 Type-C (on Headers): 1
- FAN Connectors: 6
- Audio on Headers
- TPM Support: Via 2.0 Header

#### **Environmental**

- Operating Temperature: 5ºC to 35ºC (41ºF to 95ºF
- High Humidity: 95%
- Low Humidity: 5%

# **Operating System Support**

- Windows 11 Home (64 Bit)
- Windows 11 Pro (64 Bit)
- Windows 11 Pro for WS (64 Bit)
- Windows 11 IoT 2024 LTSC Value
- Windows 11 IoT 2024 LTSC High End

- Eight(8) full height PCIe card slot cutouts
- Maximum card height: 115mm
- Maximum card length with no fans / no AIO cooler: 400mm
- Maximum card length with 3x Noctua A12x25 fans: 375mm
- Maximum card length with Asetek 360mm AlO and Noctua A12x25 fans: 348mm
- Maximum card length with Asetek 360mm AIO and Push/Pull Noctua A12x25 fans: 322mm
- Case includes eight(8) non-vented PCIe slot filler blank brackets (Sliger Part Number: CXSC1020A)
- Chassis Warranty: 1 Year

## **Compliance of Component**

- CE
- RoHS
- FCC

#### **Other Features**

• Features:

**Expansion Slots** 

#### CPU:

- 1 x PCI Express x16 slot, supporting PCIe 5.0 and running at x16 (PCIEX16)
- \* The PCIEX16 slot can only support a graphics card or an NVMe SSD. If only one graphics card is to be installed, be sure to install it in the PCIEX16 slot.

#### Chipset:

- 2 x PCI Express x16 slots, supporting PCIe 4.0 and running at x4 (PCIEX4 1, PCIEX4 2)

#### Graphics

ntegrated Graphics Processor-Intel HD Graphics support:

- 1 x Intel Thunderbolt™ 4 connector (USB4 USB Type-C port), supporting DisplayPort and Thunderbolt™ video outputs
  When a Thunderbolt™ monitor is installed, the maximum resolution supported is 5120x2880@60
  Hz with 24 bpp (single display output).
  When a USB4 USB Type-C monitor is installed, the maximum resolution supported is 3840x2160@240 Hz (single display output).
- \* Because of the limited I/O resources of the PC architecture, the number of Thunderbolt™ devices that can be used is dependent on the number of the PCI Express devices being installed. (Refer to Chapter 2-6, "Back Panel Connectors," for more information.)
- \* Support for DisplayPort 2.1 version and HDCP 2.3
- 1 x front HDMI port, supporting a maximum resolution of 1920x1080@30 Hz
- \* Support for HDMI 1.4 version
- 1 x DisplayPort, supporting a maximum

resolution of 4096x2304@60 Hz

\* Support for DisplayPort 2.1 version and HDCP 2.3

(Graphics specifications may vary depending on CPU support.)

Support for up to triple-display at the same time

#### Storeage

#### CPU:

- 1 x M.2 connector (Socket 3, M key, type
   25110/22110/2580/2280 PCIe 5.0 x4/x2 SSD support) (M2A CPU)
- 1 x M.2 connector (Socket 3, M key, type 22110/2280 PCIe 4.0 x4/x2 SSD support) (M2B CPU)

#### Chipset:

- 1 x M.2 connector (Socket 3, M key, type 25110/22110/2580/2280 PCIe 4.0 x4/x2 SSD support) (M2Q\_SB)
- 1 x M.2 connector (Socket 3, M key, type
   22110/2280 SATA and PCIe 4.0 x4 SSD support)
   (M2M SB)
- 4 x SATA 6Gb/s connectors
   RAID 0, RAID 1, RAID 5, and RAID 10 support for
   NVMe SSD storage devices
   RAID 0, RAID 1, RAID 5, and RAID 10 support for
   SATA storage devices
- \* Access to PCI Express slot requires expansion slot and a riser in some chassis models. Please check Chassis Specification section for more information.

If you have any questions, please discuss with our Sales Engineers

• Motherboard Warranty: 1 Year



www.superlogics.com Phone: 1-508-650-9500 sales@superlogics.com Fax: 1-508-650-9525