

## 5U Rack Mount Workstation Rackmount

Configuration Number: BASE CONFIG  
SL-5U-GZ890AE-SA



### Type:

- 5U Rack Mount Workstation
- Depth: 20.87", Max Card Depth: Length: 455mm (without installing front fans and radiators)"

### Motherboard:

- Featuring Intel Z890 Chipset and Intel Core™ Ultra Processors (Series 2), LGA1851 processor
- **Full Height Slots:**  
3 - PCIe x16
- **LAN:** 1x Ports (2.5GbE (10/100/1000/2500))
- **WiFi:** Wi-Fi 7 + BT 5.4
- **RAID:** 0,1,5,10 and NVMe 0,1,5,10
- **Video:** 1x HDMI, 1x DisplayPort, 1x Intel Thunderbolt™ 4
- **Audio:** Realtek ALC1200 Audio Codec
- **Ports:**  
7x USB 2.0 Ports ( 3 Rear, 4 Internal Headers )  
5x USB 3.2 Gen 1 Ports ( 2 Front, 3 Rear )  
2x USB 3.2 Gen 2 Ports ( 2 Rear )  
1x USB 3.2 Gen 2 Type-C Port ( 1 Internal Headers )  
1x Thunderbolt™ 4 (supports USB 4.0)  
Type-C Port (Rear)  
See specifications for more ports
- **Operating Temperature:** 5°C to 35°C (41°F to 95°F)

### Configuration summary:

- **Processor:** Intel Core™ Ultra 5 Processor 225 Processor - 10 Cores (6P + 4E), 20MB Intel Smart Cache, 121W (PL2)

- **Memory:** 2 x 16GB DDR5 4800MHz RAM Non-ECC Unbuffered DIMM
- **Hard Drive:** 500GB M.2 2280 NVMe SSD or greater 5,000/3,000MB/s
- **Power Supply:** 850W ATX12V / EPS12V Full Modular Power Supply - 80+ Gold Certified
- **Operating System:** Not Included -
- **Warranty:** One-Year Depot Warranty

# Technical Specifications

## MotherBoard Specifications:

### **Motherboard Model**

- Motherboard Type: ATX

### **Supported CPU**

- Number of Processors: 1
- Processor Type: Intel Core™ Ultra Processors (Series 2), LGA1851

### **Chipset**

- Chipset: Intel Z890 Chipset

### **Memory**

- Memory Type: DDR5 4800MHz
- Memory Type: Non-ECC
- DIMMS: 4
- Maximum Memory: 256GB

### **On Board Audio**

- Audio Type: Realtek ALC1200 Audio Codec

### **On Board Video**

- Video Chipset: Supported by CPU - depends on CPU selected
- Video on IO: 1x HDMI, 1x DisplayPort, 1x Intel Thunderbolt™ 4
- Display Port Out: 1
- HDMI Out: 1
- Thunderbolt™ video outputs: 1

### **LAN**

- LAN Ports: 1
- LAN Type: 2.5GbE (10/100/1000/2500)
- LAN Chipset: Realtek 2.5GbE LAN
- Wireless LAN: Wi-Fi 7 + BT 5.4

## Chassis Specifications:

### **General**

- Form Factor: 5U Rackmount
- Color: Black
- Material: Metal/Steel
- Material Thickness: 1mm
- Motherboard Compatibility: SSI EEB
- Redundant Power Supply Capable
- Slide Rails: Optional

### **Expansion**

- Full Height Slots: 8
- Max Card Depth: Length: 455mm (without installing front fans and radiators)"
- Internal 3.5" Bays: 4
- Internal 2.5" Bays: 4

### **Front Ports**

- USB 3.2 Ports (Front): 2
- USB Type-C (Front): 1

### **Cooling System**

- Maximum Fan Count: 6
- Included Fans: 3

### **Physical**

- Depth: 20.87"
- Width: 17.30"
- Height: 8.66"
- Shipping Weight: 71lbs

### **Other Features**

- Features: Expansion card Length: 455mm (without installing front fans and

## Drive Interface

- SATA III Ports (6GB): 4
- RAID
- RAID Type: Software RAID
- RAID Levels Supported on Motherboard: 0, 1, 5, 10

radiators)

Width w/ expansion card

retainer: 157mm

Width w/o expansion

card retainer: 198mm

Limitation of Height w/

CPU cooler expansion

card

retainer:

181mm

Height w/o

expansion

card

retainer:

192mm

Limitation m~19

of 0mm

PSU (Removal)

oval

of

3.5"

drive

cage

eliminates

PSU

depth

limitation)

Dimension

Incl.

rear

fan

cage:

440mm

## Rear IO

- USB 2.0 Ports (on IO): 3
- USB 3.2 Gen 1 Type A Ports (on IO): 3
- USB 3.2 Gen 2 Type A Ports (on IO): 2
- Thunderbolt™ 4 (supports USB 4.0) Type-C Port: 1

## Headers

- USB 2.0 Ports (on Headers): 4
- USB 3.2 Gen 1 Ports (on Headers): 2
- USB 3.2 Gen 2 Type-C (on Headers): 1
- FAN Connectors: 6
- Audio on Headers
- TPM Support: Via 2.0 Header

## Environmental

- Operating Temperature: 5°C to 35°C (41°F to 95°F)
- High Humidity: 95%
- Low Humidity: 5%

## Operating System Support

- Windows 11 Home (64 Bit)
- Windows 11 Pro (64 Bit)
- Windows 11 Pro for WS (64 Bit)
- Windows 11 IoT 2024 LTSC Value
- Windows 11 IoT 2024 LTSC High End

## Compliance of Component

• CE	cage:
• RoHS	440m
• FCC	m
<b>Other Features</b>	(W) x
• Features:	220m
Expansion Slots	m (H)
CPU:	x
- 1 x PCI Express x16 slot, supporting PCIe 5.0 and running at x16 (PCIEX16)	485m
* The PCIEX16 slot can only support a graphics card or an NVMe SSD. If only one graphics card is to be installed, be sure to install it in the PCIEX16 slot.	m (D), 46.95 liters Incl. rear fan cage:
Chipset:	17.3"
- 2 x PCI Express x16 slots, supporting PCIe 4.0 and running at x4 (PCIEX4_1, PCIEX4_2)	(W), 8.66" (H), 20.87 " (D) Excl.
Graphics	fan cage:
Integrated Graphics Processor-Intel HD Graphics support:	17.3" (W), 8.66" (H), 19.1" (D)
- 1 x Intel Thunderbolt™ 4 connector (USB4 USB Type-C port), supporting DisplayPort and Thunderbolt™ video outputs	rear fan cage:
When a Thunderbolt™ monitor is installed, the maximum resolution supported is 5120x2880@60 Hz with 24 bpp (single display output).	17.3" (W), 8.66" fan cage:
When a USB4 USB Type-C monitor is installed, the maximum resolution supported is 3840x2160@240 Hz (single display output).	17.3" (W), 8.66" (H), 19.1" (D)
* Because of the limited I/O resources of the PC architecture, the number of Thunderbolt™ devices that can be used is dependent on the number of the PCI Express devices being installed. (Refer to Chapter 2-6, "Back Panel Connectors," for more information.)	• Chassis Warranty: 1 Year
* Support for DisplayPort 2.1 version and HDCP 2.3	
- 1 x front HDMI port, supporting a maximum resolution of 1920x1080@30 Hz	
* Support for HDMI 1.4 version	
- 1 x DisplayPort, supporting a maximum resolution of 4096x2304@60 Hz	

\* Support for DisplayPort 2.1 version and HDCP

2.3

(Graphics specifications may vary depending on  
CPU support.)

Support for up to triple-display at the same time

Storage

CPU:

- 1 x M.2 connector (Socket 3, M key, type

25110/22110/2580/2280 PCIe 5.0 x4/x2 SSD

support) (M2A\_CPU)

- 1 x M.2 connector (Socket 3, M key, type

22110/2280 PCIe 4.0 x4/x2 SSD support)

(M2B\_CPU)

Chipset:

- 1 x M.2 connector (Socket 3, M key, type

25110/22110/2580/2280 PCIe 4.0 x4/x2 SSD

support) (M2Q\_SB)

- 1 x M.2 connector (Socket 3, M key, type

22110/2280 SATA and PCIe 4.0 x4 SSD support)

(M2M\_SB)

- 4 x SATA 6Gb/s connectors

RAID 0, RAID 1, RAID 5, and RAID 10 support for

NVMe SSD storage devices

RAID 0, RAID 1, RAID 5, and RAID 10 support for

SATA storage devices

\* Access to PCI Express slot requires expansion

slot and a riser in some chassis models. Please

check Chassis Specification section for more

information.

If you have any questions, please discuss with our

Sales Engineers

- Motherboard Warranty: 1 Year