

## 1U Rack Mount Server Rackmount

Configuration Number: BASE CONFIG  
SL-1U-AQ670M-IR1



### Type:

- 1U Rack Mount Server
- Depth: 15.48"

### Motherboard:

- Featuring Intel Q670 Chipset and 13th & 12th Gen Intel Core™, Pentium Gold and Celeron processor
- **Long Production Cycle Motherboard (Through Q1 2025)**
- **LAN:** 1x Ports (1GbE (10/100/1000))
- **RAID:** 0,1 and NVMe 0,1
- **Video:** 2x DisplayPort, 1x HDMI
- **Audio:** 7.1 HD Audio
- **Ports:**
  - 6x USB 2.0 Ports ( 2 Rear, 4 Internal Headers )
  - 2x USB 3.2 Gen 1 Ports ( 2 Front )
  - 4x USB 3.2 Gen 2 Ports ( 4 Rear )
  - 2x COM Ports (RS232 Internal Headers)
  - 1x Parallel Port (Headers)
  - See specifications for more ports
- **Operating Temperature:** 0°C to 40°C (32°F to 104°F)

### Configuration summary:

- **Processor:** i3-12100 - 3.30GHz (up to 4.30GHz) Intel Core CPU - 4 Core, 12MB Cache, UHD Graphics 730 (Base 60W, Max 89W) (ERM)
- **Memory:** 8GB DDR5 4800MHz RAM Non-ECC Unbuffered DIMM
- **Hard Drive:** 500GB M.2 2280 NVMe SSD or greater 5,000/3,000MB/s
- **Power Supply:** 450W
- **Operating System:** Not Included -

- **Warranty:** One-Year Depot Warranty

# Technical Specifications

## MotherBoard Specifications:

### Motherboard Model

- Motherboard Type: MicroATX
- Long Production Cycle
- Long Life: YES
- EOL Date: Q1 2025

### Supported CPU

- Number of Processors: 1
- Processor Type: 13th & 12th Gen Intel Core™, Pentium Gold and Celeron

### Chipset

- Chipset: Intel Q670 Chipset

### Memory

- Memory Type: DDR5 4800MHz
- Memory Type: Non-ECC
- DIMMS: 4
- Maximum Memory: 128GB

### On Board Audio

- Audio Type: 7.1 HD Audio

### On Board Video

- Video Chipset: Supported by CPU - depends on CPU selected
- Video on IO: 2x DisplayPort, 1x HDMI
- Display Port Out: 2
- HDMI Out: 1

### LAN

- LAN Ports: 1
- LAN Type: 1GbE (10/100/1000)
- LAN Chipset: Intel GbE LAN chip
- Wireless LAN: No Integrated WLAN

### Drive Interface

- SATA III Ports (6GB): 6
- RAID
- RAID Type: Software RAID
- RAID Levels Supported on Motherboard: 0, 1, 5, 10

### M.2 Slot Specs

## Chassis Specifications:

### General

- Form Factor: 1U Rackmount
- Color: Black & Silver
- Material: SGCC
- Material Thickness: 1mm
- Motherboard Compatibility: ATX
- Slide Rails: Optional

### Expansion

- Full Height Slots: 1
- Internal 3.5" Bays: 1
- Internal 2.5" Bays: 1

### Front Ports

- USB 3.2 Ports (Front): 2

### Cooling System

- Maximum Fan Count: 3
- Included Fans: 2

### Physical

- Depth: 15.48"
- Depth (Inches): 15.48
- Width: 16.93"
- Height: 1.71"
- Shipping Box - Depth: 592mm
- Shipping Box - Width: 518mm
- Shipping Box - Height: 155mm
- Shipping Weight: 11lbs

### Other Features

- Features:
  - Full height PCIe slot x 1 (via riser card and bracket)
  - External: slim ODD x 1, hot-swap 2.5" x 2
  - Internal: 3.5" HDD x 1
- Chassis Warranty: 1 Year

### Power

- Built-in Chassis Power Supply: 450W
- Remote Server Management:

- Total M.2 NVMe SSD Slots: 2
- M.2 Slot #1 Specs
- PCIe Signal
- 2242 - 22 mm x 42 mm.
- 2260 - 22 mm x 60 mm.
- 2280 - 22 mm x 80 mm.
- M.2 Slot #2 Specs
- PCIe Signal
- 2242 - 22 mm x 42 mm.
- 2260 - 22 mm x 60 mm.
- 2280 - 22 mm x 80 mm.

#### **Rear IO**

- PS/2 Mouse on IO
- PS/2 Keyboard on IO
- USB 2.0 Ports (on IO): 2
- USB 3.2 Gen 2 Type A Ports (on IO): 4
- Audio on IO

#### **Headers**

- USB 2.0 Ports (on Headers): 4
- USB 3.2 Gen 1 Ports (on Headers): 2
- Serial (via Headers): 2
- Parallel Ports: 1
- FAN Connectors: 3
- Audio on Headers
- Chassis Intrusion

#### **Environmental**

- Operating Temperature: 0°C to 40°C (32°F to 104°F )
- High Humidity: 95%
- Low Humidity: 20%

#### **Operating System Support**

- Windows 10 Home (64 Bit)
- Windows 10 Pro (64-Bit)
- Windows 10 Pro WS (64-Bit)
- SL-Windows 11PRO to 10PRO 64bit
- Windows 10 IoT 2021 LTSC Value
- Windows 10 IoT 2021 LTSC High End
- Windows 11 Home (64 Bit)
- Windows 11 Pro (64 Bit)
- Windows 11 Pro for WS (64 Bit)
- Windows 11 IoT 2024 LTSC Value
- Windows 11 IoT 2024 LTSC High End
- LINUX Ubuntu Desktop
- Ubuntu Server Edition

#### **Compliance of Component**

- RoHS
- FCC

## Other Features

- Features:

Expansion Slots

Intel 13<sup>th</sup> & 12<sup>th</sup> Gen Processors

1 x PCIe 4.0/3.0 x16 slot

Intel Q670 Chipset

2 x PCIe 3.0 x1 slots

### Storage

Supports 2 x M.2 slots and 6 x SATA 6Gb/s ports

Intel 13<sup>th</sup> & 12<sup>th</sup> Gen Processors

M.2\_1 slot (Key M), type 2242/2260/2280

- Intel 12th Gen processors support PCIe 4.0 x4 mode

Intel Q670 Chipset\*\*

M.2\_2 slot (Key M), type

2242/2260/2280(supports PCIe 4.0 x4 mode)

6 x SATA 6Gb/s ports

\* Intel Rapid Storage Technology supports NVMe RAID 0/1/5, SATA RAID 0/1/5/10.

\*\* Intel Rapid Storage Technology supports Intel Optane Memory H Series on PCH attached M.2 slots.

\* Access to PCI Express slot requires expansion slot and a riser in some chassis models. Please check Chassis Specification section for more information.

If you have any questions, please discuss with our Sales Engineers.

- Motherboard Warranty: 1 Year



www.superlogics.com  
Phone: 1-508-650-9500

sales@superlogics.com  
Fax: 1-508-650-9525