

1U Rack Mount Server Rackmount

Configuration Number: BASE CONFIG
SL-1U-AQ670M-IR1

Type:

- 1U Rack Mount Server
- Depth: 15.48"



Motherboard:

- Featuring Intel Q670 Chipset and 13th & 12th Gen Intel Core™, Pentium Gold and Celeron processor
- **Long Production Cycle Motherboard (Through Q1 2025)**
- **LAN:** 1x Ports (1GbE (10/100/1000))
- **RAID:** 0,1 and NVMe 0,1
- **Video:** 2x DisplayPort, 1x HDMI
- **Audio:** 7.1 HD Audio
- **Ports:**
 - 6x USB 2.0 Ports (2 Rear, 4 Internal Headers)
 - 2x USB 3.2 Gen 1 Ports (2 Front)
 - 4x USB 3.2 Gen 2 Ports (4 Rear)
 - 2x COM Ports (RS232 Internal Headers)
 - 1x Parallel Port (Headers)
- See specifications for more ports
- **Operating Temperature:** 0°C to 40°C (32°F to 104°F)

Configuration summary:

- **Processor:** i3-12100 - 3.30GHz (up to 4.30GHz) Intel Core CPU - 4 Core, 12MB Cache, UHD Graphics 730 (Base 60W, Max 89W) (ERM)
- **Memory:** 16GB DDR5 5600MHz RAM Non-ECC Unbuffered DIMM
- **Hard Drive:** 500GB M.2 2280 NVMe SSD or greater 5,000/3,000MB/s
- **Power Supply:** 450W
- **Operating System:** Not Included -

- **Warranty:** One-Year Depot Warranty

Technical Specifications

MotherBoard Specifications:

Motherboard Model

- Motherboard Type: MicroATX
- Long Production Cycle
- Long Life: YES
- EOL Date: Q1 2025

Supported CPU

- Number of Processors: 1
- Processor Type: 13th & 12th Gen Intel Core™, Pentium Gold and Celeron

Chipset

- Chipset: Intel Q670 Chipset

Memory

- Memory Type: DDR5 4800MHz
- Memory Type: Non-ECC
- DIMMS: 4
- Maximum Memory: 128GB

On Board Audio

- Audio Type: 7.1 HD Audio

On Board Video

- Video Chipset: Supported by CPU - depends on CPU selected
- Video on IO: 2x DisplayPort, 1x HDMI
- Display Port Out: 2
- HDMI Out: 1

LAN

- LAN Ports: 1
- LAN Type: 1GbE (10/100/1000)
- LAN Chipset: Intel GbE LAN chip
- Wireless LAN: No Integrated WLAN

Drive Interface

- SATA III Ports (6GB): 6
- RAID
- RAID Type: Software RAID
- RAID Levels Supported on Motherboard: 0, 1, 5, 10

M.2 Slot Specs

Chassis Specifications:

General

- Form Factor: 1U Rackmount
- Color: Black & Silver
- Material: SGCC
- Material Thickness: 1mm
- Motherboard Compatibility: ATX
- Slide Rails: Optional

Expansion

- Full Height Slots: 1
- Internal 3.5" Bays: 1
- Internal 2.5" Bays: 1

Front Ports

- USB 3.2 Ports (Front): 2

Cooling System

- Maximum Fan Count: 3
- Included Fans: 2

Physical

- Depth: 15.48"
- Depth (Inches): 15.48
- Width: 16.93"
- Height: 1.71"
- Shipping Box - Depth: 592mm
- Shipping Box - Width: 518mm
- Shipping Box - Height: 155mm
- Shipping Weight: 11lbs

Other Features

- Features:
 - Full height PCIe slot x 1 (via riser card and bracket)
 - External: slim ODD x 1, hot-swap 2.5" x 2
 - Internal: 3.5" HDD x 1
- Chassis Warranty: 1 Year

Power

- Built-in Chassis Power Supply: 450W
- Remote Server Management:

- Total M.2 NVMe SSD Slots: 2

- M.2 Slot #1 Specs

- PCIe Signal

- 2242 - 22 mm x 42 mm.

- 2260 - 22 mm x 60 mm.

- 2280 - 22 mm x 80 mm.

- M.2 Slot #2 Specs

- PCIe Signal

- 2242 - 22 mm x 42 mm.

- 2260 - 22 mm x 60 mm.

- 2280 - 22 mm x 80 mm.

Rear IO

- PS/2 Mouse on IO

- PS/2 Keyboard on IO

- USB 2.0 Ports (on IO): 2

- USB 3.2 Gen 2 Type A Ports (on IO): 4

- Audio on IO

Headers

- USB 2.0 Ports (on Headers): 4

- USB 3.2 Gen 1 Ports (on Headers): 2

- Serial (via Headers): 2

- Parallel Ports: 1

- FAN Connectors: 3

- Audio on Headers

- Chassis Intrusion

Environmental

- Operating Temperature: 0°C to 40°C (32°F to 104°F)

- High Humidity: 95%

- Low Humidity: 20%

Operating System Support

- Windows 10 Home (64 Bit)

- Windows 10 Pro (64-Bit)

- Windows 10 Pro WS (64-Bit)

- SL-Windows 11PRO to 10PRO 64bit

- Windows 10 IoT 2021 LTSC Value

- Windows 10 IoT 2021 LTSC High End

- Windows 11 Home (64 Bit)

- Windows 11 Pro (64 Bit)

- Windows 11 Pro for WS (64 Bit)

- Windows 11 IoT 2024 LTSC Value

- Windows 11 IoT 2024 LTSC High End

- LINUX Ubuntu Desktop

- Ubuntu Server Edition

Compliance of Component

- RoHS

- FCC

Other Features

- Features:

Expansion Slots

Intel 13th & 12th Gen Processors

1 x PCIe 4.0/3.0 x16 slot

Intel Q670 Chipset

2 x PCIe 3.0 x1 slots

Storage

Supports 2 x M.2 slots and 6 x SATA 6Gb/s ports

Intel 13th & 12th Gen Processors

M.2_1 slot (Key M), type 2242/2260/2280

- Intel 12th Gen processors support PCIe 4.0 x4 mode

Intel Q670 Chipset**

M.2_2 slot (Key M), type

2242/2260/2280(supports PCIe 4.0 x4 mode)

6 x SATA 6Gb/s ports

* Intel Rapid Storage Technology supports NVMe RAID 0/1/5, SATA RAID 0/1/5/10.

** Intel Rapid Storage Technology supports Intel Optane Memory H Series on PCH attached M.2 slots.

* Access to PCI Express slot requires expansion slot and a riser in some chassis models. Please check Chassis Specification section for more information.

If you have any questions, please discuss with our Sales Engineers.

- Motherboard Warranty: 1 Year