

5U Rack Mount Workstation Rackmount

Configuration Number: BASE CONFIG
SL-5U-AZ890ACE-SA



Type:

- 5U Rack Mount Workstation
- Depth: 20.87", Max Card Depth: Length: 455mm (without installing front fans and radiators)"

Motherboard:

- Featuring Intel Z890 Chipset and Intel Core™ Ultra Processors (Series 2), LGA1851 processor
- **Full Height Slots:**
3 - PCIe x16
- **LAN:** 3x Ports (10GbE + 2.5GbE + Realtek 1Gb Ethernet dedicated for AST2600)
- **RAID:** 0,1,5,10 and NVMe 0,1,5
- **Video:** 1x HDMI, 1x Intel Thunderbolt™ 4, 1x VGA port from AST2600
- **Audio:** Realtek ALC1220P Surround Sound High Definition Audio CODEC
- **Ports:**
2x USB 2.0 Ports (2 Internal Headers)
2x USB 3.2 Gen 1 Ports (2 Front)
6x USB 3.2 Gen 2 Ports (6 Rear)
1x USB 3.2 Gen 2 Type-C Port (1 Internal Headers)
1x Thunderbolt™ 4 (supports USB 4.0)
Type-C Port (Rear)
1x COM Port (RS232 Internal Headers)
See specifications for more ports
- **Operating Temperature:** 10°C to 35°C (50°F to 95°F)

Configuration summary:

- **Processor:** Intel Core™ Ultra 5 Processor 225 Processor - 10 Cores (6P + 4E), 20MB

- Intel Smart Cache, 121W (PL2)
- Memory:** 2 x 16GB DDR5 5600MHz RAM Non-ECC Unbuffered DIMM
- Hard Drive:** 500GB M.2 2280 NVMe SSD or greater 5,000/3,000MB/s
- Power Supply:** 850W ATX12V / EPS12V Full Modular Power Supply - 80+ Gold Certified
- Operating System:** Not Included -
- Warranty:** One-Year Depot Warranty

Technical Specifications

MotherBoard Specifications:

Motherboard Model

- Motherboard Type: ATX

Supported CPU

- Number of Processors: 1
- Processor Type: Intel Core™ Ultra Processors (Series 2), LGA1851

Chipset

- Chipset: Intel Z890 Chipset

Memory

- Memory Type: DDR5 4800MHz
- Memory Type: Non-ECC
- DIMMS: 4
- Maximum Memory: 256GB

On Board Audio

- Audio Type: Realtek ALC1220P Surround Sound High Definition Audio CODEC

On Board Video

- Video Chipset: Supported by CPU - depends on CPU selected
- Video on IO: 1x HDMI, 1x Intel Thunderbolt™ 4, 1x VGA port from AST2600
- VGA Port Out: 1
- HDMI Out: 1
- Thunderbolt™ video outputs: 1

LAN

- LAN Ports: 3
- LAN Type: 10GbE + 2.5GbE + Realtek 1Gb Ethernet dedicated for AST2600

Chassis Specifications:

General

- Form Factor: 5U Rackmount
- Color: Black
- Material: Metal/Steel
- Material Thickness: 1mm
- Motherboard Compatibility: SSI EEB
- Redundant Power Supply Capable
- Slide Rails: Optional

Expansion

- Full Height Slots: 8
- Max Card Depth: Length: 455mm (without installing front fans and radiators)"
- Internal 3.5" Bays: 4
- Internal 2.5" Bays: 4

Front Ports

- USB 3.2 Ports (Front): 2
- USB Type-C (Front): 1

Cooling System

- Maximum Fan Count: 6
- Included Fans: 3

Physical

- Depth: 20.87"
- Width: 17.30"
- Height: 8.66"
- Shipping Weight: 71lbs

Other Features

- Features: Expansion card Length: 455mm (without

- LAN Chipset: Marvell AQtion 10Gb Ethernet
- Second LAN Chipset: Intel 2.5Gb Ethernet
- Wireless LAN: No Integrated WLAN

installing front fans and radiators)

Width w/ expansion card retainer: 157mm

Width w/o expansion card retainer: 198mm

Limitation of Height w/ CPU cooler expansion card

retainer:

181mm

Height w/o expansion card

retainer:

192mm

Limitation of 160mm

of 0mm

PSU (Removal of

oval

of

3.5"

drive

cage

eliminates

PSU

depth

limitation)

Dimension

Incl.

rear

fan

cage:

440mm

m

(W) x

220mm

m (H)

x

530mm

m

(D),

51.3

liters

Excl.

rear

Drive Interface

- SATA III Ports (6GB): 4
- RAID Type: Software RAID
- RAID Levels Supported on Motherboard: 0, 1, 5, 10

Expansion Slots

- PCI Express x16 Slots On Motherboard: 3

M.2 Slot Specs

- Total M.2 NVMe SSD Slots: 4
- M.2 Slot #1 Specs
- 2260 - 22 mm x 60 mm.
- 2280 - 22 mm x 80 mm.
- M.2 Slot #2 Specs
- 2242 - 22 mm x 42 mm.
- 2260 - 22 mm x 60 mm.
- 2280 - 22 mm x 80 mm.
- M.2 Slot #3 Specs
- 2242 - 22 mm x 42 mm.
- 2260 - 22 mm x 60 mm.
- 2280 - 22 mm x 80 mm.
- M.2 Slot #4 Specs
- 2280 - 22 mm x 80 mm.

Rear IO

- USB 3.2 Gen 2 Type A Ports (on IO): 6
- USB 3.2 Gen 2x2 Type C Ports (on I/O): 1
- Thunderbolt™ 4 (supports USB 4.0) Type-C Port: 1
- Audio on IO

Headers

- USB 2.0 Ports (on Headers): 2
- USB 3.2 Gen 1 Ports (on Headers): 2
- USB 3.2 Gen 2 Type-C (on Headers): 1
- Serial (via Headers): 1
- FAN Connectors: 7
- Audio on Headers

Environmental

- Operating Temperature: 10°C to 35°C (50°F to 95°F)
- High Humidity: 90%

Operating System Support

- Windows 10 Pro (64-Bit)
- SL-Windows 11PRO to 10PRO 64bit
- Windows 11 Home (64 Bit)
- Windows 11 Pro (64 Bit)

• Windows 11 Pro for WS (64 Bit)	fan
• Windows 11 IoT 2024 LTSC Value	cage:
• Windows 11 IoT 2024 LTSC High End	440m
• LINUX Ubuntu Desktop	m
Compliance of Component	(W) x
• CE	220m
• RoHS	m (H)
• FCC	x
	485m
Other Features	m
• Features:	(D),
Expansion Slots	46.95
Intel Core™ Ultra Processors (Series 2)*	liters
2 x PCIe 5.0 x16 slots*** (supports x16 or x8/x8 modes)**	Incl.
Intel Z890 Chipset**	rear
1 x PCIe 4.0 x16 slot (supports x4 mode)***	fan
* Please check the PCIe bifurcation table on the support site (https://www.asus.com/support/FAQ/1037507/).	cage: 17.3"
** To ensure compatibility of the device installed, please refer to https://www.asus.com/support/download-center/ for the list of supported peripherals.	(W), 8.66" (H), 20.87" (D)
Ethernet	Excl. rear
1 x Marvell AQtion 10Gb Ethernet	fan
1 x Intel 2.5Gb Ethernet	cage: 17.3"
1 x Realtek 1Gb Ethernet dedicated for AST2600	(W), 8.66"
Storage	(H), 19.1" (D)
Total supports 4 x M.2 slots and 8 x SATA 6Gb/s ports*	• Chassis Warranty: 1 Year
Intel Core™ Ultra Processors (Series 2)	
M.2_1 slot (Key M), type 2260/2280 (supports PCIe 5.0 x4 mode)	
M.2_2 slot (Key M), type 2242/2260/2280 (supports PCIe4.0 x4 mode)	
Intel Z890 Chipset**	
M.2_3 slot (Key M), type 2242/2260/2280 (supports PCIe 4.0 x4 mode)	
M.2_4 slot (Key M), type 2280 (supports PCIe 4.0 x4 mode)	
SlimSAS_1 slot supports PCIe 4.0 x4 mode or up to 4 SATA devices via a transfer cable. The cable is purchased separately. **	
4 x SATA 6Gb/s ports	
* Intel Rapid Storage Technology supports PCIe RAID 0/1/5/10, SATA RAID 0/1/5/10, M.2 slot from	

CPU only supports RAID 0/1/5.

**SlimSAS port connected to a U.2 device via a transfer cable does not support VMD/RST.

- Motherboard Warranty: 1 Year



www.superlogics.com
Phone: 1-508-650-9500

sales@superlogics.com
Fax: 1-508-650-9525