

## 2U Rack Mount Industrial PC Rackmount

Configuration Number: BASE CONFIG  
SL-2U-MTC741T-SJ



### Type:

- 2U Rack Mount Industrial PC
- Depth: 17", Max Card Depth: 404mm"

### Motherboard:

- Featuring Intel C741 Chipset and Intel Xeon Scalable Processors 5th/4th Gen LGA-4677 (Socket E), CPU TDP supports up to 350W TDP processor

- **Low Profile Slots:**

- 4 - PCIe x16
- 1 - PCIe x8

- **LAN:** 2x Ports (10GbE + 10GbE + IPMI)

- **RAID:** 0,1,5,10 and NVMe 0,1 RAID Intel VROC

- **Video:** 1x VGA

- **Audio:** Realtek ALC888S HD Audio

- **Ports:**

- 2x USB 2.0 Ports ( 2 Rear )
- 3x USB 3.2 Gen 1 Ports ( 1 Front, 2 Rear )
- 1x COM Port (RS232 Rear)

See specifications for more ports

- **Operating Temperature:** 10°C to 35°C (50°F to 95°F)

### Configuration summary:

- **Processor:** 4th GEN Intel Xeon Bronze 3408U Octa-core (8 Core) 1.80 GHz Processor - 22.50 MB L3 Cache - 64-bit Processing - 1.90 GHz Overclocking Speed - Socket LGA-4677 - 125 W - 8 Threads
- **Memory:** 2 x 16GB DDR5 5600MHz ECC Registered RAM
- **Hard Drive:** 1TB PCIe GEN 5.0 NVMe SSD M.2 Read/write speeds up to

11,000/9,500MB/s

- **Power Supply:** 600W 1U FLEX ATX Power Supply - 80+ Platinum Efficient
- **Operating System:** Not Included -
- **Warranty:** One-Year Depot Warranty

# Technical Specifications

## MotherBoard Specifications:

### **Motherboard Model**

- Motherboard Type: SSI CEB

### **Supported CPU**

- Number of Processors: 1
- Processor Type: Intel Xeon Scalable Processors 5th/4th Gen LGA-4677 (Socket E), CPU TDP supports up to 350W TDP

### **Chipset**

- Chipset: Intel C741 Chipset

### **Memory**

- Memory Type: DDR5 5600MHz ECCR
- Memory Type: ECC Registered
- DIMMS: 8
- Maximum Memory: 2048GB

### **On Board Audio**

- Audio Type: Realtek ALC888S HD Audio

### **On Board Video**

- Video Chipset: ASPEED AST2600 BMC
- Video on IO: 1x VGA
- VGA Port Out: 1

### **LAN**

- LAN Ports: 2
- LAN Type: 10GbE + 10GbE + IPMI
- LAN Chipset: Intel X550 10GBase-T
- Second LAN Chipset: Intel X550 10GBase-T
- Wireless LAN: No Integrated WLAN

### **Drive Interface**

- SATA III Ports (6GB): 6
- RAID
- RAID Type: Software RAID
- RAID Levels Supported on Motherboard: 0, 1, 5,

10

## Chassis Specifications:

### **General**

- Form Factor: 2U Rackmount
- Front Changeable Air Filter
- Color: Black
- Material: Metal/Steel
- Material Thickness: 1mm
- Motherboard Compatibility: SSI EEB
- Slide Rails: Optional

### **Expansion**

- Low Profile Slots: 7
- Max Card Depth: 404mm"
- Internal 2.5" Bays: 5

### **Front Ports**

- USB 3.2 Ports (Front): 2

### **Cooling System**

- Maximum Fan Count: 4

### **Physical**

- Depth: 17"
- Depth (Inches): 17
- Width: 17"
- Height: 3.46"
- Shipping Box - Depth: 20.50"
- Shipping Box - Width: 20.50"
- Shipping Box - Height: 7.50"
- Shipping Weight: 16lbs

### **Other Features**

- Features:
  - Storage

Five (5) 2.5" drives up to 7mm thick  
Up to five(5) 7mm 2.5" SSDs in the rear drive cage when not using 3.5" HDD mounts  
Two (2) 3.5" drives up to 20mm thick  
Up to two(2) 3.5" Hard Disk Drives [HDDs]

### **Expansion Slots**

- PCI Express x16 Slots On Motherboard: 4
- PCI Express x8 Slots On Motherboard: 1

### **M.2 Slot Specs**

- Total M.2 NVMe SSD Slots: 1
- M.2 Slot #1 Specs
- 2280 - 22 mm x 80 mm.

### **Rear IO**

- USB 2.0 Ports (on IO): 2
- USB 3.2 Gen 1 Type A Ports (on IO): 2
- Serial (Rear IO): 1
- Audio on IO

### **Headers**

- USB 3.2 Gen 1 Ports (on Headers): 1
- USB 2.0 Ports (Type A): 1
- FAN Connectors: 6
- TPM Support: Via 2.0 Header

### **Environmental**

- Operating Temperature: 10°C to 35°C (50°F to 95°F )
- High Humidity: 90%
- Low Humidity: 0%

### **Operating System Support**

- Windows 11 Pro (64 Bit)
- Windows 11 Pro for WS (64 Bit)
- Windows Server 2022 STD
- RED HAT Enterprise LINUX WORKSTATION STANDARD
- RED HAT Enterprise LINUX SERVER BASIC
- RED HAT Enterprise LINUX SERVER STANDARD
- LINUX Ubuntu Desktop
- Ubuntu Server Edition

### **Compliance of Component**

- CE
- FCC

### **Other Features**

- Features:
  - Expansion Slots
  - (1) PCIe Gen.5 x8 slot
  - (4) PCIe Gen.5 x16 slots

\* Access to PCI Express slot requires expansion slot and a riser in some chassis models. Please check Chassis Specification section for more information.

OR

One(1) full-sized 3.5" HDD, and one(1) 2.5" SSD up to 15mm thick

- Chassis Warranty: 1 Year

### **Power**

- Remote Server Management:

If you have any questions, please discuss with our  
Sales Engineers.

- Motherboard Warranty: 1 Year



[www.superlogics.com](http://www.superlogics.com)  
Phone: 1-508-650-9500

[sales@superlogics.com](mailto:sales@superlogics.com)  
Fax: 1-508-650-9525