


Desktop PC Desktop

Configuration Number: BASE CONFIG
SL-DK-LLQ870A-FW



(Full size images available on web site)

Type:

- Desktop PC
- Dimension: 547mm x 240mm x 475mm

Motherboard:

- Featuring Intel Q870 Chipset and Intel Core™ Ultra Processors (Series 2), LGA1851 processor
- **Long Production Cycle Motherboard (Through Q3 2030)**
- **Full Height Slots:**
 - 2 - PCIe x16
 - 4 - PCIe x4
 - 1 - PCI
- **LAN:** 3x Ports (2.5GbE + 2.5GbE + 1GbE)
- **RAID:** 0,1,5,10 and NVMe 0,1
- **Video:** 2x DisplayPort, 1x HDMI
- **Audio:** Realtek ALC897
- **Ports:**
 - 2x USB 2.0 Ports (2 Internal Headers)
 - 4x USB 3.2 Gen 1 Ports (4 Front)
 - 6x USB 3.2 Gen 2 Ports (6 Rear)
 - 6x COM Ports (1 RS232 Rear, 4 RS232 Internal Headers, 1 RS232/422/485 Internal Headers)
 - 1x Parallel Port (Headers)
 - 1x Front Audio Port
- See specifications for more ports
- **Operating Temperature:** 0°C to 60°C (32°F to 140°F)

Configuration summary:

- **Processor:** Intel Core Ultra 5 225 Processor - 10 Cores (6P + 4E), 20MB Cache, 121W (PL2)
- **Memory:** 16GB DDR5 5600MHz RAM

- Non-ECC Unbuffered DIMM
- **Hard Drive:** 500GB M.2 2280 NVMe SSD or greater 5,000/3,000MB/s
- **Power Supply:** 550W Fully Modular ATX Power Supply - 80+ Bronze
- **Operating System:** Not Included -
- **Warranty:** One-Year Depot Warranty

Technical Specifications

MotherBoard Specifications:

Motherboard Model

- Motherboard Type: ATX
- Long Production Cycle
- Long Life: YES
- EOL Date: Q3 2030

Supported CPU

- Number of Processors: 1
- Processor Type: Intel Core™ Ultra Processors (Series 2), LGA1851

Chipset

- Chipset: Intel Q870 Chipset

Memory

- Memory Type: DDR5 4800MHz
- Memory Type: Non-ECC
- DIMMS: 4
- Maximum Memory: 192GB

On Board Audio

- Audio Type: Realtek ALC897

On Board Video

- Video Chipset: Supported by CPU - depends on CPU selected
- Video on IO: 2x DisplayPort, 1x HDMI
- Display Port Out: 2
- HDMI Out: 1

LAN

- LAN Ports: 3
- LAN Type and IPMI: 2.5GbE + 2.5GbE + 1GbE
- LAN Chipset: Intel 2.5Gb Ethernet
- Second LAN Chipset: Intel 2.5Gb Ethernet
- Third LAN Chipset: Intel i210AT
- Wireless LAN: No Integrated WLAN

Chassis Specifications:

General

- Form Factor: Full Tower
- Front Facing I/O
- Front Changeable Air Filter
- Color: Black
- Material: Metal/Steel
- Material Thickness: 1mm
- Motherboard Compatibility: E-ATX

Expansion

- Full Height Slots: 7
- Max Card Depth: Storage layout: 315 mm - Open layout: 491 mm (467 mm w/ front fan)"
- External 5.25" Bays: 1
- Internal 3.5" Bays: 6
- Internal 2.5" Bays: 2

Front Ports

- USB 3.2 Ports (Front): 5
- Front Audio Ports: 1

Cooling System

- Maximum Fan Count: 9
- Included Fans: 4

Physical

- Depth: 547mm
- Depth (Inches): 21.5
- Width: 240mm
- Height: 475mm
- Shipping Box - Depth: 558mm
- Shipping Box - Width: 363mm
- Shipping Box - Height: 641mm
- Shipping Weight: 36lbs

Other Features

- Chassis Warranty: 1 Year

Drive Interface

- SATA III Ports (6GB): 4
- RAID
- RAID Type: Software RAID
- RAID Levels Supported on Motherboard: 0, 1, 5, 10

Expansion Slots

- PCI Express x16 Slots On Motherboard: 2
- PCI Express x4 Slots On Motherboard: 4
- PCI Slots (Conventional 32-Bit): 1

M.2 Slot Specs

- Total M.2 NVMe SSD Slots: 2
- M.2 Slot #1 Specs
- 2242 - 22 mm x 42 mm.
- 2260 - 22 mm x 60 mm.
- 2280 - 22 mm x 80 mm.
- M.2 Slot #2 Specs
- 2280 - 22 mm x 80 mm.
- M.2 E-Key Slot
- 2230 - 22 mm x 30 mm.

Rear IO

- USB 3.2 Gen 2 Type A Ports (on IO): 6
- USB 3.2 Gen 2x2 Type C Ports (on I/O): 1
- Serial (Rear IO): 1
- Audio on IO

Headers

- USB 2.0 Ports (on Headers): 2
- USB 3.2 Gen 1 Ports (on Headers): 4
- USB 2.0 Ports (Type A): 1
- Serial (via Headers): 4
- Serial 232/422/485 Ports: 1
- Parallel Ports: 1
- FAN Connectors: 4
- Audio on Headers
- PS/2 Combo (Mouse/Keyboard) on Headers
- Chassis Intrusion
- TPM Support: Via 2.0 Header

Environmental

- Operating Temperature: 0°C to 60°C (32°F to 140°F)
- High Humidity: 95%
- Low Humidity: 10%

Operating System Support

- Windows 11 Pro (64 Bit)
- Windows 11 Pro for WS (64 Bit)
- Windows 11 IoT 2024 LTSC Value

- Windows 11 IoT 2024 LTSC High End
- RED HAT Enterprise LINUX SERVER BASIC
- RED HAT Enterprise LINUX WORKSTATION STANDARD
- RED HAT Enterprise LINUX SERVER STANDARD
- LINUX Ubuntu Desktop
- Ubuntu Server Edition

Compliance of Component

- CE
- FCC

Other Features

- Features:

Expansion slots

1x PCI Express 5.0 x16 slot (1 x16 mode / 2 x8 modes)

1x PCI Express 4.0 x4 slot (x2 mode, open slot)

1x PCI Express 4.0 x4 slot (x4 mode, open slot)

1x PCI Express 5.0 x16 slot (x8 mode)

1x PCI Express 4.0 x4 slot (x2 mode, open slot)

1x PCI Express 4.0 x4 slot (x4 mode, open slot)

1x PCI slot

M.2 Slots

1x M.2 socket 1 (Key E, 2230) for WiFi/BT devices
Supporting Intel CNVi

1x M.2 socket 3 (Key M, 2242/2260/2280) with
PCIe 5.0 x4 mode supporting NVMe

1x M.2 socket 3 (Key M, 2280) with PCIe 4.0 x4
mode supporting NVMe

- Motherboard Warranty: 1 Year



Simplifying Computing™

www.superlogics.com
Phone: 1-508-650-9500

sales@superlogics.com
Fax: 1-508-650-9525