HMI Panel PC Panel PC

Configuration Number: BASE CONFIG
SL-PPC-19A-LLA7425E-S17

Type:

- Panel PC
- **Screen:**
  - 19" 5-Wire Resistive, Native Resolution: 1280 x 1024, Front Panel Rating: IP65 / NEMA4
- **Mounting:** Bezel Mounting Hardware Included, Suitable for Mounting in Cut-Out

Motherboard:

- Featuring Intel ATOM SoC and Intel Atom x7425E Processor (Max Turbo 3.40 GHz Quad Core) TDP 12W
- **LAN:** 2x Ports (2.5GbE + 2.5GbE)
- **Video:** 2x HDMI
- **Audio:** Onboard Audio
- **Ports:**
  4x USB 2.0 Ports (2 Front, 2 Rear)
  1x USB 3.2 Gen 2 Port (1 Rear)
  1x USB 3.2 Gen 2 Type-C Port (1 Rear)
  6x COM Ports (5 RS232 Internal Headers, 1 RS232/422/485 Rear)
  See specifications for more ports
- **Operating Temperature:** -20ºC to 60ºC (-4ºF to 140ºF)

Configuration summary:

- **Memory:** 8GB DDR5 5600MHz RAM Non-ECC Unbuffered SODIMM
- **Hard Drive:** 500GB M.2 2280 NVMe SSD or greater 5,000/3,000MB/s
- **Power Supply:** AC/DC Power Adapter Included
- **Operating System:** Not Included -
- **Warranty:** One-Year Depot Warranty

Technical Specifications

MotherBoard Specifications:

Motherboard Model

- Motherboard Type: MiniITX
- Long Production Cycle

Supported CPU

- Number of Processors: 1
- Processor Type: Embedded CPUs (ultra-low power, soldered down)
- Embedded CPU: Intel Atom x7425E Processor (Max Turbo 3.40 GHz Quad Core) TDP 12W

Chipset

- Chipset: Intel ATOM SoC

Memory

- Memory Type: SO DIMM DDR5 4800MHz
- Memory Type: Non-ECC
- DIMMS: 1
- Maximum Memory: 32GB

On Board Audio

- Audio Type: Onboard Audio

On Board Video

- Video Chipset: Intel UHD Graphics
- Video on IO: 2x HDMI
- HDMI Out: 2

LAN

- LAN Ports: 2
- LAN Type and IPMI: 2.5GbE + 2.5GbE
- LAN Chipset: Intel i226-V 2.5GbE Ethernet
- Second LAN Chipset: Intel i226-V 2.5GbE Ethernet
- Wireless LAN: No Integrated WLAN

Drive Interface

- SATA III Ports (6GB): 1

M.2 Slot Specs

- Total M.2 NVMe SSD Slots: 1
- M.2 Slot #1 Specs
- M.2 SATA SSD
- 2242 - 22 mm x 42 mm.
- 2280 - 22 mm x 80 mm.
- M.2 E-Key Slot
- PCIe Signal

Display Specifications

Display

- Screen Size (inches): 19
- Touch Type: 5-Wire Resistive
- Front Panel Rating: IP65 / NEMA4
- Aspect Ratio: 5 : 4
- Native Display Resolution: 1280 x 1024
- Brightness (nits): 350
- Screen Refresh Rate: 60Hz
- Display Area (H): 376.32mm
- Display Area (V): 301.07mm
- Aspect Ratio: 5 : 4
- DisplayColors: 16.7 M
- Contrast Ratio: 1000:1
- Backlight: LED
- Viewing Angle(U) : 80
- Viewing Angle(D) : 80
- Viewing Angle(L) : 80
- Viewing Angle(R) : 80

Connectivity

- HDMI In: 1
- Display Port In: 1
- Touchscreen Interface USB Port (Front): 1

Mounting Options

- Mounting Options: VESA 75mm x 75mm, VESA 100mm x 100mm, Bezel Mounting Hardware Included, Other options sold separately
- Suggested Cut-Out Dimension (Width):
- Suggested Cut-Out Dimension (Height):

Physical

- Width:
- Height:
- Depth:
- Depth (Inches): Click Available Downloads Tab > Mechanical Drawings.
- Unboxed Weight: 14lbs
- Shipping Weight: 40lbs

Environmental

- MTBF: 30000hours
- Maximum Operating Temperature: 50C
- High Humidity: 90%

- USB
- 2230 - 22 mm x 30 mm.

Rear IO

- USB 2.0 Ports (on IO): 2
- USB 3.2 Gen 2 Type A Ports (on IO): 1
- USB 3.2 Gen 2 Type C Ports (on I/O): 1
- Serial 232/422/485 Ports: 1
- Audio on IO

Headers

- USB 2.0 Ports (on Headers): 2
- Serial (via Headers): 5
- Digital I/O (8 Bit) On Headers
- LVDS
- PS/2 Combo (Mouse/Keyboard) on Headers
- TPM Support: 2.0 Module Included
- DC Power: 12-28V DC-in jack

Environmental

- Operating Temperature: -20ºC to 60ºC (-4ºF to 140ºF)
- High Humidity: 90%
- Low Humidity: 5%

Operating System Support

- Windows 10 Home (64 Bit)
- Windows 10 Pro (64-Bit)
- SL-Windows 11PRO to 10PRO 64bit
- Windows 10 IoT 2021 LTSC Entry
- Windows 11 Home (64 Bit)
- Windows 11 Pro (64 Bit)
- Windows 11 IoT 2024 LTSC Entry
- LINUX Ubuntu Desktop

Compliance of Component

- CE
- FCC
- CB

Other Features

- Motherboard Warranty: 1 Year

Chassis Specifications:

General

- Form Factor: Micro PC
- Color: Black
- Material: Metal/Steel
- Material Thickness: 1mm
- Motherboard Compatibility: Mini ITX
- Low Humidity: 8%
- Storage Temp (High): 60C
- Storage Temp (Low): -10C
- Storage Humidity (High): 90%
- Storage Humidity (Low): 8%

Power

- Power Supply: AC 100~240V/12V DC
- Power Consumption (on): 18Watts

Compliance of Component

- CE
- RoHS
- CCC

Warranty

- Warranty: 1 year

Other

- Features:

Industrial Display

- Screen Size: 19"
- Touch Type: 5-Wire Resistive
- Front Panel Rating: IP65 / NEMA4
- Native Display Resolution: 1280 x 1024
- Brightness (nits): 350
- Wide Voltage 9-36VDC

Expansion

- Internal 2.5" Bays: 1
- Serial Port Punchouts: 2
- Parallel Port Punchouts: 1
- Antennae Punchout: 2

Front Ports

- USB 2.0 Ports (Front): 2

Cooling System

- Maximum Fan Count: 1

Physical

- Depth: 8.27"
- Depth (Inches): 8.27
- Width: 7.60"
- Height: 2.60"
- Shipping Box - Depth: 13"
- Shipping Box - Width: 9"
- Shipping Box - Height: 5"
- Shipping Weight: 8lbs

Other Features

- Chassis Warranty: 1 Year

Power

- Built-in Chassis Power Supply: AC/DC Power Adapter Included

SuperLogics®
Simplifying Computing™

www.superlogics.com
Phone: 1-508-650-9500

sales@superlogics.com
Fax: 1-508-650-9525