

4U Rack Mount Industrial PC Rackmount

Configuration Number: BASE CONFIG
SL-4U-SBC-H61-BA



10 Weeks Lead Time.

Type:

- 4U Rack Mount Industrial PC
- Depth: 26.80", Max Card Depth: Full Length", Locking Front Bezel

Motherboard:

- Featuring Intel H61 Chipset and 3rd Gen Core i3/i5/i7 (LGA1155, 'Ivy Bridge') processor
- **Long Production Cycle Motherboard (Through Q2 2018)**
- **Full Height Slots:**
 - 18 - PCI
- **LAN:** 2x Ports (GB (10/100/1000))
- **Video:** VGA + DVI-D
- **Audio:** Onboard Audio
- **Ports:**
 - 7x USB 2.0 Ports (2 Front, 1 Rear, 4 Internal Headers)
 - 2x COM Ports (RS232 Rear)
 - 1x Parallel Port (Headers)
- **Operating Temperature:** 10°C to 60°C (50°F to 140°F)



(full size images available on web site)

Configuration summary:

- **Processor:** G1620 - 2.7GHz Intel Dual Core Celeron CPU - 2MB Cache, HD Graphics (55W) (ERM)
- **Memory:** 4GB DDR3 1600MHz RAM
- **Hard Drive:** 1.0TB SATA 6.0Gb/s 7200RPM 64MB 3.5" - WD Blue
- **Power Supply:** 400W Power Supply

- **Operating System:** Not Included -
- **Warranty:** One-Year Depot Warranty

Technical Specifications

MotherBoard Specifications:

Motherboard Model

- Motherboard Type: Single Board Computer (SBC)
- Long Production Cycle
- Long Life: YES
- EOL Date: Q2 2018
- PICMG: 1.0

Supported CPU

- Number of Processors: 1
- Processor Type: 3rd Gen Core i3/i5/i7 (LGA1155, 'Ivy Bridge')

Chipset

- Chipset: Intel H61 Chipset

Memory

- Memory Type: DDR3 1333MHz
- Memory Type: Non-ECC
- DIMMS: 2
- Maximum Memory: 16GB

On Board Audio

- Audio Type: Onboard Audio

On Board Video

- Video Chipset: Intel HD Graphics
- Video on IO: VGA + DVI-D
- VGA Port Out: 1
- DVI-D Out: 1

LAN

- LAN Ports: 2
- LAN Type: GB (10/100/1000)
- LAN Chipset: Realtek RTL8111E
- Second LAN Chipset: Realtek RTL8111E
- Wireless LAN: No Integrated WLAN

Drive Interface

- SATA II Ports (3GB): 4

Mini PCIe

- mini PCIe
- mSATA

Chassis Specifications:

General

- Form Factor: 4U Rackmount
- Color: Black
- Material: Metal/Steel
- Material Thickness: 1mm
- Motherboard Compatibility: 20-Slot SBC
- Slide Rails: Optional

Expansion

- Full Height Slots: 20
- Max Card Depth: Full Length"
- External 5.25" Bays: 3
- Internal 2.5" Bays: 2

Front Ports

- USB 2.0 Port (Front): 2

Cooling System

- Maximum Fan Count: 3
- Included Fans: 3

Physical

- Depth: 26.80"
- Depth (Inches): 26.8
- Width: 19"
- Height: 7"
- Shipping Box - Depth: 19"
- Shipping Box - Width: 26.80"
- Shipping Box - Height: 7"
- Shipping Weight: 54.24lbs

Compliance of Component

- UL
- CE
- RoHS
- FCC

Other Features

- Chassis Warranty: 1 Year

- half and/or full size mini PCIe card: full/half size

Rear IO

- PS/2 Combo (Mouse/Keyboard)
- USB 2.0 Ports (on IO): 1
- Firewire Ports: 2
- Serial (Rear IO): 2

Headers

- USB 2.0 Ports (on Headers): 6
- Firewire Ports: 1
- Parallel Ports: 1
- FAN Connectors: 2
- Digital I/O (8 Bit) On Headers
- Floppy Connectors: 1
- TPM Support: Via 1.2 Header

Management Features

- Watch Dog

Environmental

- Operating Temperature: 10°C to 60°C (50°F to 140°F)
- High Humidity: 95%
- Low Humidity: 5%

Operating System Support

- Windows XP Pro (32-bit)
- Windows 7 Ultimate (64-bit)
- Windows 7 Pro (32-bit)
- Windows 7 Pro (64-bit)
- Windows 7 Pro (FES) 32-Bit
- Windows 7 Pro (FES) 64-Bit
- Windows 8.1 (32-bit)
- Windows 8.1 (64-bit)
- Windows 8.1 Pro (32-bit)
- Windows 8.1 Pro (64-bit)
- LINUX Ubuntu Desktop
- Ubuntu Server Edition
- VMWare Compatible

Compliance of Component

- UL
- CE
- RoHS
- FCC

Other Features

- Motherboard Warranty: 1 Year



Simplifying Computing™

www.superlogics.com
Phone: 1-508-650-9500

sales@superlogics.com
Fax: 1-508-650-9525