

HMI Panel PC Panel PC

Configuration Number: BASE CONFIG

SL-PPC-12-E3845





(full size images available on web site)

Type:

Can be Long Lead Time- Please Call for

- Fanless Panel PC
- Screen:

Current Status

• 12" 5-Wire Resistive, Native Resolution: 1024 x 768, Front Panel Rating: IP65

Motherboard:

- Featuring Intel ATOM SoC and Intel Atom E3845 Processor (1.91GHz Quad Core) **TDP 10W**
- Video: HDMI
- Audio: Onboard Audio
- Ports:

1x USB 2.0 Port(1 Rear) 1x USB 3.2 Gen 1 Port(1 Rear) 1x COM Port (RS232/422/485 Rear) See specifications for more ports

• Operating Temperature: -20°C to 60°C $(-4^{\circ}F \text{ to } 140^{\circ}F)$

Configuration summary:

- Memory: 4GB DDR3 1333MHz SODIMM RAM
- Hard Drive: 250GB SSD SATA 6.0Gb/s 560/530MB/s 2.5" - Samsung 870 EVO
- Power Supply: Wide Voltage +12V ~ +26V. Included 100 ~ 240Vac/ 50 ~ 60Hz Output: 60W Adapter (12V @ 5A Adapter)
- Operating System: Not Included -
- Warranty: One-Year Depot Warranty

Technical Specifications

MotherBoard Specifications:

Display Specifications

Motherboard Model

Motherboard Type: Panel

Fanless

Supported CPU

• Number of Processors: 1

 Processor Type: Embedded CPUs (ultra-low power, soldered down)

 Embedded CPU: Intel Atom E3845 Processor (1.91GHz Quad Core) TDP 10W

Chipset

• Chipset: Intel ATOM SoC

Memory

• Memory Type: DDR3 1333MHz

• Memory Type: Non-ECC

• DIMMS: 1

Maximum Memory: 8GB

On Board Audio

• Audio Type: Onboard Audio

On Board Video

 Video Chipset: Intel Valleyview SoC integrated Graphics

Video on IO: HDMIHDMI Out: 1

LAN

• LAN Ports: 2

• LAN Chipset: Intel i210AT

Second LAN Chipset: Intel i210ATWireless LAN: No Integrated WLAN

Drive Interface

• SATA II Ports (3GB): 1

Mini PCle

• mini PCIe

mSATA

• half and/or full size mini PCIe card: full size

Second mini PCIe

• 3G Data Support

• half and/or full size mini PCIe card: full size

Display

Screen Size (inches): 12Touch Type: 5-Wire Resistive

• Front Panel Rating: IP65

• Aspect Ratio: 4:3

Native Display Resolution: 1024 x 768

Brightness (nits): 500Display Area (H): 9.60"Display Area (V): 7.27"

Aspect Ratio: 4:3DisplayColors: 16.2 M

• Contrast Ratio: 700:1

• Backlight: LED

Viewing Angle(U): 70
Viewing Angle(D): 70
Viewing Angle(L): 80
Viewing Angle(R): 80

Mounting Options

 Mounting Options: VESA 75mm x 75mm, VESA 100mm x 100mm, Other options sold separately

Suggested Cut-Out Dimension (Width): 266mm

• Suggested Cut-Out Dimension (Height): 193mm

Physical

Width: 283mmHeight: 222mmDepth: 45mm

Depth (Inches): 1.75Unboxed Weight: 6.5lbsShipping Weight: 8.5lbs

Environmental

• MTBF: 50000hours

• Maximum Operating Temperature: 60C

• Low Operating Temp: -20C

High Humidity: 90%Low Humidity: 00

• Storage Temp (High): 70C

• Storage Temp (Low): -30C

• Storage Humidity (High): 90%

• Storage Humidity (Low): 00

Power

Rear IO

- USB 2.0 Ports (on IO): 1
- USB 3.2 Gen 1 Type A Ports (on IO): 1
- Serial 232/422/485 Ports: 1
- Audio on IO

Management Features

• Watch Dog

Environmental

- Operating Temperature: -20 $^{\circ}$ C to 60 $^{\circ}$ C (-4 $^{\circ}$ F to 140 $^{\circ}$ F)
- High Humidity: 90%
- Low Humidity: 00

Operating System Support

- Windows 7 Ultimate (64-bit)
- Windows 7 Pro (32-bit)
- Windows 7 Pro (64-bit)
- Windows 7 Pro (FES) 32-Bit
- Windows 7 Pro (FES) 64-Bit
- Windows Embedded 7 (32-Bit)
- Windows Embedded 7 (64-Bit)
- Windows Embedded 8 (32-bit)
- Windows Embedded 8 (64-bit)
- Windows 8.1 (32-bit)
- Windows 8.1 (64-bit)
- Windows 8.1 Pro (32-bit)
- Windows 8.1 Pro (64-bit)
- Windows 10 Home (64 Bit)
- Windows 10 Pro (64-Bit)
- Windows 10 IoT Entry
- Windows 10 IoT Entry 2019 LTSC

Compliance of Component

- CE
- FCC

Warranty of Component

• Motherboard Warranty: 1 Year

Chassis Specifications:

General

• Form Factor: Panel PC

• Color: Black

Material: Metal/AluminumMaterial Thickness: 1mm

Front Ports

USB 2.0 Port (Front): 1USB 3.2 Ports (Front): 1

- Power Supply: Accepts 12VDC, 100-240VAC/12VDC 5A 60W External Power Adapter included
- Power Consumption (on): 60Watts

Compliance of Component

- CE
- FCC

Warranty

• Warranty: 1 year

Other

Built-in Chassis Power Supply: Wide Voltage +12V
 +26V. Included 100 ~ 240Vac/ 50 ~ 60Hz
 Output: 60W Adapter (12V @ 5A Adapter)

Physical

• Depth: 45mm

• Depth (Inches): 1.75

Width: 283mmHeight: 222mm

Shipping Box - Depth: 4"Shipping Box - Width: 15"Shipping Box - Height: 14.70"

• Shipping Weight: 8.5lbs

Power

Built-in Chassis Power Supply: Wide Voltage +12V
 ~ +26V. Included 100 ~ 240Vac/ 50 ~ 60Hz
 Output: 60W Adapter (12V @ 5A Adapter)



www.superlogics.com Phone: 1-508-650-9500

sales@superlogics.com Fax: 1-508-650-9525