

Microbox PC Embedded PC

Configuration Number: BASE CONFIG
SL-EB-LL1900A-S19-1



Type:

- Microbox PC
- Dimension: 8.30" x 8" x 3.50"

Motherboard:

- Featuring Intel Celeron SoC and Intel Celeron J1900 Processor (2.0GHz Quad Core, Burst 2.42GHz) TDP 10W
- **Long Production Cycle Motherboard (Through Q1 2028)**
- **Low Profile Slots:**
1 - PCIe x1
- **LAN:** 2x Ports (1GbE + 1GbE)
- **Video:** 1x VGA, 1x HDMI
- **Audio:** Intel HD Audio
- **Ports:**
6x USB 2.0 Ports (2 Front, 2 Rear, 2 Internal Headers)
4x USB 3.2 Gen 1 Ports (2 Rear, 2 Internal Headers)
5x COM Ports (2 RS232 Internal Headers, 3 RS232/422/485 Rear)
1x Parallel Port (Headers)
See specifications for more ports
- **Operating Temperature:** 0°C to 60°C (32°F to 140°F)

Configuration summary:

- **Memory:** 4GB DDR3L 1600MHz SODIMM RAM 1.35V
- **Hard Drive:** 256GB mSATA SSD SATA 6.0Gb/s, 550/500MB/s read/write (or greater)
- **Power Supply:** Power Adapter Included
- **Operating System:** Not Included -
- **Warranty:** One-Year Depot Warranty

Technical Specifications

MotherBoard Specifications:

Motherboard Model

- Motherboard Type: MiniITX
- Fanless
- Long Production Cycle
- Long Life: YES
- EOL Date: Q1 2028

Supported CPU

- Number of Processors: 1
- Processor Type: Embedded CPUs (ultra-low power, soldered down)
- Embedded CPU: Intel Celeron J1900 Processor (2.0GHz Quad Core, Burst 2.42GHz) TDP 10W

Chipset

- Chipset: Intel Celeron SoC

Memory

- Memory Type: SO DIMM DDR3 1333MHz
- Memory Type: Non-ECC
- DIMMS: 2
- Maximum Memory: 8GB

On Board Audio

- Audio Type: Intel HD Audio

On Board Video

- Video Chipset: Intel 7th generation (Gen 7) Graphics
- Video on IO: 1x VGA, 1x HDMI
- VGA Port Out: 1
- HDMI Out: 1

LAN

- LAN Ports: 2
- LAN Type: 1GbE + 1GbE
- LAN Chipset: Realtek RTL8111G
- Second LAN Chipset: Realtek RTL8111G
- Wireless LAN: No Integrated WLAN

Drive Interface

- SATA II Ports (3GB): 2

Expansion Slots

- PCI Express x1 Slots On Motherboard: 1

Mini PCIe

Chassis Specifications:

General

- Form Factor: Embedded PC
- Color: Black
- Material: Metal/Steel
- Material Thickness: 1mm
- Motherboard Compatibility: Mini ITX

Expansion

- Low Profile Slots: 1
- Max Card Depth: 7.5""
- Internal 2.5" Bays: 2
- Serial Port Punchouts: 2
- Parallel Port Punchouts: 1

Front Ports

- USB 2.0 Ports (Front): 2

Cooling System

- Maximum Fan Count: 2

Physical

- Depth: 8.30"
- Depth (Inches): 8.27
- Width: 8"
- Height: 3.50"
- Shipping Box - Depth: 150mm
- Shipping Box - Width: 380mm
- Shipping Box - Height: 27mm
- Shipping Weight: 13lbs

Other Features

- Chassis Warranty: 1 Year

Power

- Built-in Chassis Power Supply: Power Adapter Included

- mini PCIe
- mSATA
- half and/or full size mini PCIe card: full size
- Second mini PCIe
- USB and PCIe signals (Internal)
- half and/or full size mini PCIe card: half size

Rear IO

- PS/2 Mouse on IO
- PS/2 Keyboard on IO
- USB 2.0 Ports (on IO): 2
- USB 3.2 Gen 1 Type A Ports (on IO): 2
- Serial 232/422/485 Ports: 3
- Audio on IO

Headers

- USB 2.0 Ports (on Headers): 4
- USB 3.2 Gen 1 Ports (on Headers): 2
- Serial (via Headers): 2
- Parallel Ports: 1
- FAN Connectors: 2
- Digital I/O (8 Bit) On Headers
- Audio on Headers
- LVDS

Management Features

- Watch Dog

Environmental

- Operating Temperature: 0°C to 60°C (32°F to 140°F)
- High Humidity: 90%
- Low Humidity: 5%

Operating System Support

- Windows 7 Ultimate (64-bit)
- Windows 7 Pro (32-bit)
- Windows 7 Pro (64-bit)
- Windows 7 Pro (FES) 32-Bit
- Windows 7 Pro (FES) 64-Bit
- SL-Windows 10PRO to 7PRO 32-bit
- SL-Windows 10PRO to 7PRO 64-bit
- Windows Embedded 7 (32-Bit)
- Windows Embedded 7 (64-Bit)
- Windows 8.1 (32-bit)
- Windows 8.1 (64-bit)
- Windows 8.1 Pro (32-bit)
- Windows 8.1 Pro (64-bit)
- Windows Embedded 8 (32-bit)
- Windows Embedded 8 (64-bit)
- Windows 10 Home (64 Bit)
- Windows 10 Pro (64 Bit)

- SL-Windows 11PRO to 10PRO 64bit
- Windows 10 IoT Entry
- Windows 10 IoT Entry 2019 LTSC
- Windows 10 IoT 2021 LTSC Entry

Compliance of Component

- UL
- CE
- RoHS
- FCC

Other Features

- Other Features:
1x PCE Express 2.0 x1 Slot

* Access to PCI Express slot requires expansion slot and a riser in some chassis models. Please check Chassis Specification section for more information.

If you have any questions, please discuss with our Sales Engineers.

- Motherboard Warranty: 1 Year



www.superlogics.com
Phone: 1-508-650-9500

sales@superlogics.com
Fax: 1-508-650-9525