

4U Rack Mount Industrial PC Rackmount

Configuration Number: BASE CONFIG

SL-4U-PD-Q170SSQ-HA





Type:

- 4U Rack Mount Industrial PC
- Depth: 17.70", Max Card Depth: 12.28", Locking Front Bezel

Motherboard:

- Featuring Intel Q170 Chipset and 7th and 6th Gen Core i7/i5/i3 (LGA1151) processor
- Long Production Cycle Motherboard (Through Q4 2025)
- Full Height Slots:
 - 1 PCle x16
 - 2 PCle x4
 - 1 PCle x1
- **LAN:** 2x Ports (1GbE + 1GbE)
- **RAID:** 0,1,5,10
- Video: 1x DVI-D, 1x HDMI, 2x DisplayPort
- Audio: 7.1 Channel HD Audio by Realtek ALC888S
- Ports:

8x USB 2.0 Ports (2 Front, 4 Rear, 2

Internal Headers)

4x USB 3.2 Gen 1 Ports (2 Rear, 2

Internal Headers)

4x COM Ports (RS232 Internal Headers)

See specifications for more ports

• Operating Temperature: 0°C to 60°C (32°F to 140°F)

Configuration summary:

Processor: G4400 - 3.3GHz Intel
Pentium Dual Core - 3MB Cache, HD
Graphics 510 (54W) (ERM) or Better

• **Memory:** 8GB DDR4 2666MHz RAM

• Hard Drive: 1.0TB SATA 6.0Gb/s

7200RPM 64MB 3.5" - WD Blue

Power Supply: 400W Power Supply
Operating System: Not Included Warranty: One-Year Depot Warranty

Technical Specifications

MotherBoard Specifications:

Motherboard Model

Motherboard Type: MicroATX

• Long Production Cycle

Long Life: YESEOL Date: Q4 2025

Supported CPU

• Number of Processors: 1

 Processor Type: 7th and 6th Gen Core i7/i5/i3 (LGA1151)

Chipset

• Chipset: Intel Q170 Chipset

Memory

• Memory Type: DDR4 2133MHz

• Memory Type: Non-ECC

• DIMMS: 4

• Maximum Memory: 64GB

On Board Audio

 Audio Type: 7.1 Channel HD Audio by Realtek ALC888S

On Board Video

 Video Chipset: Supported by CPU - depends on CPU selected

Video on IO: 1x DVI-D, 1x HDMI, 2x DisplayPort

DVI-D Out: 1Display Port Out: 1HDMI Out: 1

LAN

• LAN Ports: 2

LAN Type: 1GbE + 1GbELAN Chipset: Intel i210AT

Second LAN Chipset: Intel i219LMWireless LAN: No Integrated WLAN

Drive Interface

Chassis Specifications:

General

• Form Factor: 4U Rackmount

• Color: Black

Material: Metal/SteelMaterial Thickness: 1mm

Motherboard Compatibility: ATX

Redundant Power Supply Capable

• Slide Rails: Optional

Expansion

• Full Height Slots: 7

• Max Card Depth: 12.28"

• External 5.25" Bays: 3

• Internal 3.5" Bays: 2

• External 3.5" Bays: 1

Front Ports

• USB 2.0 Ports (Front): 2

Cooling System

• Maximum Fan Count: 2

• Included Fans: 1

Physical

• Depth: 17.70"

• Depth (Inches): 17.7

Width: 19"Height: 7"

• Shipping Box - Depth: 26"

• Shipping Box - Width: 23"

• Shipping Box - Height: 12"

• Shipping Weight: 45lbs

Other Features

• Chassis Warranty: 1 Year

- SATA III Ports (6GB): 6
- RAID
- RAID Type: Software RAID
- RAID Levels Supported on Motherboard: 0, 1, 5,

Expansion Slots

- PCI Express x16 Slots On Motherboard: 1
- PCI Express x4 Slots On Motherboard: 2
- PCI Express x1 Slots On Motherboard: 1

M.2 Slot Specs

- Total M.2 NVMe SSD Slots: 1
- M.2 Slot #1 Specs
- PCle Signal
- 2242 22 mm x 42 mm.
- 2260 22 mm x 60 mm.
- 2280 22 mm x 80 mm.

Rear IO

- PS/2 Combo (Mouse/Keyboard)
- USB 2.0 Ports (on IO): 4
- USB 3.2 Gen 1 Type A Ports (on IO): 2
- SPDIF Connector: 1
- Audio on IO

Headers

- USB 2.0 Ports (on Headers): 4
- USB 3.2 Gen 1 Ports (on Headers): 2
- Serial (via Headers): 4
- FAN Connectors: 4
- Chassis Intrusion
- TPM Support: Via 2.0 Header

Management Features

• Watch Dog

Environmental

- Operating Temperature: 0°C to 60°C (32°F to 140°F)
- High Humidity: 85%
- Low Humidity: 10%

Operating System Support

- Windows 7 Ultimate (64-bit)
- Windows 7 Pro (32-bit)
- Windows 7 Pro (64-bit)
- Windows 7 Pro (FES) 32-Bit
- Windows 7 Pro (FES) 64-Bit
- Windows 7 PRO (FES) DGS 32-BIT
- Windows 7 PRO (FES) DGS 64-BIT
- SL-Windows 10PRO to 7PRO 32-bit
- SL-Windows 10PRO to 7PRO 64-bit

- Windows Embedded 7 (32-Bit)
- Windows Embedded 7 (64-Bit)
- Windows 8.1 (64-bit)
- Windows 8.1 Pro (64-bit)
- Windows Embedded 8 (64-bit)
- Windows 10 Home (64 Bit)
- Windows 10 Pro (64-Bit)
- Windows 10 Pro WS (64-Bit)
- SL-Windows 11PRO to 10PRO 64bit
- Windows 10 IoT Value
- Windows 10 IoT Ent
- Windows 10 IoT Value 2019 LTSC
- Windows 10 IoT Ent 2019 LTSC
- Windows 10 IoT 2021 LTSC Value
- Windows 10 IoT 2021 LTSC High End
- Windows Server 2012
- Windows Server 2016 STD
- Windows Server 2019 Std
- RED HAT Enterprise LINUX SERVER STANDARD
- LINUX Ubuntu Desktop
- Ubuntu Server Edition

Compliance of Component

- UL
- CE
- RoHS
- FCC

Other Features

- Other Features:
 - 1 PCI-E 3.0 x16 (in x16) Slot
 - 2 PCI-E 3.0 x4 (in x4) Slot
 - 1 PCI-E 3.0 x1 (in x1) Slot
 - M.2 PCI-E x2 M Key 2242/2260/2280, PCI-E 3.0 x4 with open slots
 - * Access to PCI Express slot requires expansion slot and a riser in some chassis models. Please check Chassis Specification section for more information.

If you have any questions, please discuss with our Sales Engineers.

• Motherboard Warranty: 1 Year



www.superlogics.com sales@superlogics.com Phone: 1-508-650-9500 Fax: 1-508-650-9525